

A

-
- Abbreviations
 - accuracy 1221
 - geometric 609–614
 - mathematical and signs 2
 - scientific and engineering terms 2554–2555
 - symbols for mechanics 115
 - welding 1396
 - ABEC bearing tolerances 2256–2261
 - Abrasive
 - belt
 - grinding 1193–1194
 - selecting 1194
 - contact wheel
 - selecting 1195
 - cubic boron nitride (CBN) 755–757, 1140, 1157, 1166
 - cutting 1195–1196
 - diamond 1139
 - grains and materials 1139
 - grinding 1139
 - honing 1196–1199
 - lapping 1199–1202
 - polishing 1440–1441
 - ABS plastics 380, 579, 588, 601, 2511
 - Absolute
 - programming, NC 1240
 - system of measurement 114
 - temperature 2514
 - zero 2514
 - Acceleration 114, 151, 153–154
 - angular 153
 - constant 152
 - linear, of point on rotating body 154
 - of gravity, g 114
 - Accuracy
 - effect of, on part tolerances 1220
 - of NC machine tools 1218–1219
 - positioning 1216
 - repeatability, and resolution, NC 1216
 - significance of 1218–1219
 - Acetal plastics 380, 579, 588, 597, 601
 - Acetylene, specific gravity 371
 - Acme threads
 - abbreviations 1795
 - ANSI Standard 1792–1816
 - centralizing 1802–1811
 - checking 1870–1874
 - drill sizes for 901
 - Acme threads *(continued)*
 - general purpose 1792–1802
 - multiple start 1795, 1800
 - stub type 1811–1816
 - taps for 898–901
 - thread profile form 1793–1794
 - types of 1792, 1802, 1811
 - wire sizes for checking 1872–1874
 - Acres to hectares 2541
 - Acrylic plastics 380, 588, 597, 601
 - Active face width 1998
 - Active spline length 2127
 - Actual space width 2127
 - Actual tooth thickness 2127
 - Adaptive control, NC 1233
 - Addendum 1998
 - chordal 2017–2018, 2062
 - modification 2044
 - involute spur and helical gears 2044
 - Addresses, letter, NC 1243
 - Adhesives, bonding 2460–2466
 - one-component 2461–2463
 - retaining compounds 2463–2464
 - sealants 2464–2466
 - thread-locking 2463–2464
 - two-component 2460–2462
 - Adiabatic expansion and compression 395–401
 - Adjusting gear blanks for milling 2062
 - Aerodynamic lubrication 2321
 - Aging of metal 479
 - AGMA
 - backlash allowance and tolerance
 - fine-pitch spur, helical and herringbone gearing 2041
 - recommended backlash range
 - bevel and hypoid gears 2038
 - coarse-pitch spur, helical and herringbone gearing 2037
 - AGMA Standard
 - AGMA 112.05 2001
 - AGMA 115.01 2001
 - AGMA 116.01 2001
 - AGMA 202.03 2054
 - AGMA 208.03 2054
 - AGMA 209.04 2054
 - AGMA 330.01 2054
 - AGMA 370.01 2066
 - AGMA 390.03 2038
 - backlash recommendations 2037–2038, 2041

- Air**
- adiabatic expansion and
 - compression 395–396
 - compression and flow 393, 396–401
 - density 394
 - flow in pipes 401
 - isothermal expansion and
 - compression 396
 - power or work to compress 396, 398–400
 - pressure, temperature, and volume
 - relationships 395
 - properties of 393–394
 - velocity of escaping 401
 - volume and weight at different
 - temperatures 393
 - volume transmitted through pipes 401
- Air** dry wood, weight per cubic foot 377
- AISI**–SAE 406–408
- Alcohol**, specific gravity 371
- Algebra** and equations 20
- Algebraic**
- expressions and formulas 32
 - rearrangement and transposition of
 - terms 20–21
- Alignment** variation 2127
- Allowances** and tolerances for
- cylindrical fits, ANSI Standard for 627–657
 - fits 621–667
 - fits, preferred series 628–630
 - metric ISO fits, British Standard for 657–666
- Allowances** for bending sheet metal 1304–1310
- Alloy** cast iron 1330
- Alloy** steels 406
- AISI–SAE designations 409–410
 - basic numbering system 403, 405
 - carburizing grades 422–423
 - castings 1335
 - compositions 411–412
 - directly hardenable grades 424–425
 - effects of alloying elements 2114–2117
 - hardness of heat-treated 432–436
 - heat treatments 505
 - mechanical properties 432–436
 - numbering system 403, 405
 - quality variations 418
 - selection for making tools 452–456
 - speeds for drilling and reaming 1030–1033, 1035
 - speeds for milling 1014–1019
 - speeds for turning 996–999
 - strength of heat-treated 432–436
- Alloys**
- aluminum 542–557
 - bearing 1344, 2238–2242
 - brazing 1354–1361
 - cast iron 1328–1329
 - cast steels 1332–1335
 - copper 525–542
- Alloys** (*continued*)
- copper–beryllium 565–566
 - copper–silicon 565
 - die casting 1342–1344
 - magnesium 557–560
 - nickel 561–563
 - nonferrous 525–566
 - nonferrous, strength 477
 - numbering systems for 403
 - soldering 1352–1355
 - titanium 561, 564
- Alternating** current motors 2449–2452
- Alternating** stress 197
- Aluminum**
- alloys 542–557
 - Association 543, 546–548
 - bearings 2241
 - cast
 - composition of 546–548, 550–551
 - strength of 477
 - strength of 550–551
 - characteristics of 542–543
 - clad 546
 - composition of
 - wrought 556–557
 - designations 546
 - die casting 1342–1343
 - heat treatability of wrought 546
 - machining 1116
 - melting point 368–369
 - properties of 550–557
 - series groups 546–549
 - soldering 1352–1354
 - structural shapes 2498
 - temper designation 543–546
 - welding 1365, 1386–1387, 1390
 - wrought 477, 546–557
- Aluminum** bronze
- casting alloy 532
 - strength 477
 - cast 550–551
- American**
- Boiler Makers Association 268
 - Brass Company 565
 - Bureau of Shipping 355, 1335
 - Foundrymen's Association 479
 - Gear Manufacturers Association (AGMA) 2001, 2004, 2037–2038, 2041
 - Institute of Steel Construction 265
 - column formulas 267
 - Iron and Steel Institute (AISI) 360, 403, 405
 - Steel Products Manual 411–412
 - Wire and Rods, Carbon Steel 435
 - National fire hose connection
 - threads 1842–1845
 - Railroads, Assn. of 1335
 - Screw threads, wire sizes for
 - measuring 1861–1862
 - Society for Metals (ASM) 479, 521

- American *(continued)*
- Society for Testing and Materials (ASTM) 479, 520–521, 557–560, 1328–1331, 1335
 - annealing temperatures 496–497
 - copper alloys 525–542
 - Standard Code for Information Interchange (ASCII) 1295
 - wire gage 2499–2500
- American Standard B1.1 1712
- Ammonia, specific gravity 371
- in nitriding 417
- Amortization 27
- AMS 2404C 1447
- AMS 2405B 1447
- AMS 2433B 1447
- Analysis, break-even 40–42
- Angles
- bent to circular shape, lengths of 2488
 - between lines tangent to two circles 685
 - compound 688–690
 - cutting tool 723–730
 - cutting tool inserts 1281–1284
 - degrees into radians 90, 92
 - functions of 83–101
 - helix 1933
 - indexing 1950–1993
 - involute functions of 97–101
 - lead 1933
 - length of arc of given radius 80–81
 - length of chord 80–81
 - measuring by disc method 682–683
 - minutes into decimals of a degree 90, 92
 - moment of inertia 2495–2497
 - radius of gyration 2495–2497
 - section modulus 2495–2497
 - sine bar for measuring 673–682
 - structural 2495–2497
 - taper per foot corresponding to 684
 - rules for figuring 682–683
 - thread, tolerances on gages 1882
 - to find, for given taper per foot 682–685
 - useful relationships among 93
 - weight per foot 2495–2497
- Angular
- acceleration 153
 - torque, relation to 156
 - backlash in gears 2042
 - clearance for dies 1302
 - indexing 1956–1977
 - velocity 151–153, 187
 - of rotating bodies 187
- Annealing 414–415, 479, 495
- constant temperature, transformation 496–497
 - double 496
 - temperatures 496
- Annual cost method 27–29
- Annuities (calculation of) 26–27
- Anode 1319
- Anodizing 1444
- Anodizing *(continued)*
- hard 1448
 - ANSI / RMA IP-26, 1977 2398
 - ANSI B1.20.5 1854
 - ANSI B1.1 1506, 1508, 1712
 - ANSI B1.12 1786
 - ANSI B1.13M 1538, 1544, 1762
 - ANSI B1.18M 1755
 - ANSI B1.20 1848
 - ANSI B1.20.1 1848, 1851
 - ANSI B1.20.3 880, 1853–1854
 - ANSI B1.3 1879
 - ANSI B1.3M 1774
 - ANSI B1.5 1792, 1811
 - ANSI B1.9 1818, 1822–1823, 1877
 - ANSI B17.1 2342–2343, 2345–2347
 - ANSI B17.2 2348–2350
 - ANSI B18.1.1 1464, 1468–1470
 - ANSI B18.1.2 1464–1467
 - ANSI B18.16.1M 1542, 1547
 - ANSI B18.16.3M 1520, 1542, 1547
 - ANSI B18.17 1693–1701
 - ANSI B18.2.1 1492
 - ANSI B18.2.2 1492, 1510
 - ANSI B18.2.3.1M 1520–1521
 - ANSI B18.2.3.2M 1520, 1522, 1524
 - ANSI B18.2.3.3M 1520, 1523
 - ANSI B18.2.3.4M 1524
 - ANSI B18.2.3.5M 1520, 1524, 1530
 - ANSI B18.2.3.6M 1520, 1524, 1529
 - ANSI B18.2.3.7M 1520, 1528–1529
 - ANSI B18.2.3.8M 1520, 1525, 1532
 - ANSI B18.2.3.9M 1524
 - ANSI B18.2.4.1M 1520, 1542–1543
 - ANSI B18.2.4.2M 1520, 1542–1543
 - ANSI B18.2.4.3M 1520, 1542
 - ANSI B18.2.4.4M 1520, 1542, 1544–1545
 - ANSI B18.2.4.5M 1542, 1548
 - ANSI B18.2.4.6M 1520, 1542, 1548
 - ANSI B18.22.1 1512–1513, 1515
 - ANSI B18.22M 1520, 1549
 - ANSI B18.3 1541
 - ANSI B18.3.1M 1522
 - ANSI B18.6.1 1456
 - ANSI B18.6.3 1568–1577
 - ANSI B18.6.4 1620, 1622–1625, 1627, 1635
 - ANSI B18.6.7M 1568
 - ANSI B18.8.1 1649
 - ANSI B212.1 738–739, 741–746, 859–860, 862–864
 - ANSI B212.12 730
 - ANSI B212.4 731
 - ANSI B212.5 733–734
 - ANSI B27.7M 1665–1668, 1670, 1672–1673
 - ANSI B29.1M 2435
 - ANSI B32.1 2501
 - ANSI B32.4M 644
 - ANSI B4.1 627, 630, 634, 636, 638–640, 2267–2268
 - ANSI B4.2 642, 644, 646, 648–655, 657

- ANSI B4.4M 656
 ANSI B47.1 1882
 ANSI B5.18 920, 922–924
 ANSI B6. 7 2024
 ANSI B6.1 2004–2006, 2008–2009, 2011, 2019, 2023
 ANSI B6.7 2008, 2011, 2023–2026, 2079
 ANSI B6.9 2064–2065
 ANSI B7.1 1170, 1174, 1196
 ANSI B7.1-1988 1173
 ANSI B74.13 1141, 1166
 ANSI B74.2 1142–1143, 1148, 1150, 1204–1206
 ANSI B74.3 1163–1165, 1167
 ANSI B92.1 2130–2131, 2133–2134, 2137, 2139, 2149–2150
 ANSI B92.2M 2126, 2148–2150
 ANSI B94.11M 827, 837
 ANSI B94.2 813–820, 822–826
 ANSI B94.25 731
 ANSI B94.33 942–943, 945–950
 ANSI B94.35 848, 850
 ANSI Standard
 abbreviations 115, 2554–2555
 Acme threads 1792–1816
 bolts, nuts, screws, and washers, inch 1492–1519
 bolts, screws, and nuts, metric 1520–1524, 1548–1549
 boring tools, carbide 859–864
 buttress inch type threads 1818–1824
 cap screws, hex head 1496, 1520
 cap screws, metric 1520–1523
 castle and slotted nuts 1500–1502
 chain, transmission 2421–2426
 Class 5 threads 1786–1788
 cutting tools 730–746
 diamond wheels 1163–1168
 drafting practices 606
 drafting room practice 606–611
 drill drivers 848–850
 drive screws 1635
 electric socket and lamp base threads 1846
 engineering drawings 606
 fine pitch standard gear tooth parts 2009
 fine-pitch
 helical gears 2077–2080
 worm gearing 2064–2066
 fine-pitch worm gearing
 ANSI B6.9 2064
 flat metal products
 inch sizes 2501–2502
 metric sizes 2503
 gage usage, recommended 656
 gagemakers
 tolerances 656
 gages 1876–1884
 for self-holding tapers 914
 for Unified screw threads 1877–1884
 gear tooth forms 2004–2010
- ANSI Standard *(continued)*
 geometric characteristic symbols for engineering drawings 609–614
 geometric dimensioning and tolerancing 606–611
 grinding wheel safety 1170–1174
 grinding wheels 1141–1149, 1157, 1166
 hexagon socket head shoulder screws 1605
 hose coupling screw threads 1841–1845
 interference-fit threads 1786–1791
 involute spline symbols 2130
 involute splines
 inch dimensions 2126–2147
 metric module 2148–2155
 jig bushings 941–951
 key drive 911–912
 keys and keyseats 2342–2354
 keys and keyways for milling cutters and arbors 794
 knurls and knurling 1211–1215
 letter symbols for mechanics 115
 limits and fits 627–657
 lock washers 1515–1519
 machine screws 1568–1577
 binding head 1576
 fillister head 1574
 flat, countersunk head 1569–1571
 hexagon washer head 1571
 metric 1578–1585
 oval head 1574–1576
 pan head 1573
 round head 1577
 slotted hexagon 1572
 truss head 1572
 manufacturers' standard gage for sheet steel 2501–2502
 metric
 cap screws 1520–1523
 retaining rings 1666–1673
 screw threads, M profile 1755–1776
 screw threads, MJ profile 1777–1780
 screws, bolts, nuts, and washers 1520–1525, 1533–1534, 1546–1549
 microscope threads 1846
 milling cutters 772–795
 miniature threads 1781–1785
 numerical control 1226
 nuts 1492–1504
 nuts, metric 1541, 1543–1548
 pins 1648–1664
 pipe and pipe fittings 2504–2508
 pipe thread 1846–1855
 plain washers 1512–1517
 position symbols 1221
 preferred
 basic sizes 644
 fits 644–647
 metric limits and fits 632, 642–657
 metric sizes 642–644
 numbers 19

- ANSI Standard *(continued)*
- thicknesses, thin, flat metals 2501
 - reamers 813–815, 820–826
 - retaining rings 1666–1673
 - rivets 1464–1470
 - roundness symbols 1222
 - runout symbols 1224
 - screw thread symbols 1787, 1793–1794, 1811, 1816, 1824
 - metric 1756–1778
 - screw threads 1706–1710, 1712–1790, 1793–1816, 1818–1824
 - metric M profile 1755–1776
 - metric MJ profile 1777–1780
 - screws and bolts
 - inch 1492–1509
 - metric 1520–1527, 1529, 1532–1534, 1541
 - section lining symbols 606, 608
 - self-tapping thread inserts 1635
 - self-threading screws, inch 1620–1635
 - metric 1635–1644
 - serrations, involute 2126
 - set-screw heads and points 1606–1610
 - set-screws, socket type 1607, 1612
 - shoulder screws 1605
 - single-point tools and tool posts 740–746
 - slotted head cap screws 1599–1600
 - slotted headless set screws 1606
 - socket head cap screws 1601–1605
 - spindles and drives for portable tools 1207–1210
 - spline socket set screws 1607, 1612
 - splines, involute
 - inch dimensions 2126–2147
 - metric module 2148–2155
 - spur gear tooth forms 2004–2010
 - stub threads, 29- and 60-degree 1811–1816
 - stud threads 1786–1791
 - studs, drive 1659, 1662
 - surface texture 697–708
 - symbols
 - accuracy 1221
 - accuracy symbols 1221
 - comparison to ISO 609
 - concentricity 609, 1223
 - datum referencing 614
 - diameter 609, 1222
 - drawing practices for surface texture 704–708
 - parallelism 609
 - part tolerance 609, 642–644
 - perpendicularity 609
 - position 609
 - roundness 609
 - runout 609
 - section lining 606, 608
 - total runout 609
 - welding 1393
 - symbols for section lining 608
- ANSI Standard *(continued)*
- tang drives 909–910
 - tapers 906–918
 - taps and threading dies 872–898
 - threads for electric sockets 1846
 - T-nuts, T-bolts, T-slots 1645–1647
 - tolerances 630
 - gagemakers 656
 - symbols 578–579, 609–614, 622
 - tolerances and allowances for cylindrical fits 621–657
 - tooth proportions, fine-pitch involute spur and helical gears 2008
 - total runout symbols 1224
 - twist drills 827–849
 - Unified threads 1706–1710, 1712–1754, 1781–1786
 - washers, inch 1512–1519
 - metric 1547, 1549
 - welded and seamless wrought steel pipe 2505
 - wing nuts, wing screws, and thumb screws 1693–1701
 - wood screws 1456
 - woodruff keys 2348–2354
 - worm gearing, fine pitch 2064–2066
 - wrench openings 1510–1511
- ANSI Standard Z17.1-1973 19
- ANSI X3.37 1264
- ANSI Y10.4 115
- ANSI Y14.1 606
- ANSI Y14.2 1294
- ANSI Y14.2M 608
- ANSI Y14.36 606
- ANSI Y14.5M 1286
- ANSI Z136.1 1413
- ANSI 14.5M 1221
- ANSI, RMA IP-25 2402
- ANSI/AFBMA Std 10 2303, 2306
- ANSI/AFBMA Std 11 2291
- ANSI/AFBMA Std 11–1978 2297
- ANSI/AFBMA Std 18.1 2263, 2270–2271
- ANSI/AFBMA Std 18.2 2263–2264, 2269–2271
- ANSI/AFBMA Std 20 2256–2257
- ANSI/AFBMA Std 20, 1987 2258–2260
- ANSI/AFBMA Std 24.1–1989 2261
- ANSI/AFBMA Std 24.2 2262
- ANSI/AFBMA Std 24.2–1989 2261
- ANSI/AFBMA Std 7 2265, 2267–2268
- ANSI/AFBMA Std 8.2 2276–2279
- ANSI/AFBMA Std 9 2286, 2297
- ANSI/AGMA 2005 2054
- ANSI/AMSE B 18.16.3M 1546
- ANSI/ASME B 1.1 1712
- ANSI/ASME B 1.12 1788–1791
- ANSI/ASME B 1.13M 1755, 1757–1759, 1763–1764, 1766–1768, 1774, 1776
- ANSI/ASME B 1.2 1864, 1877, 1880, 1883–1884
- ANSI/ASME B 1.20.1 1847–1851

- ANSI/ASME B1.20.7 1841–1842
 ANSI/ASME B1.21M 1755, 1777
 ANSI/ASME B1.3M 1712, 1791
 ANSI/ASME B1.7M 1707, 1712
 ANSI/ASME B18.1.3M 1464
 ANSI/ASME B18.2.1 1492–1498, 1551
 ANSI/ASME B18.2.2 1492–1493, 1499–1502, 1510, 1551
 ANSI/ASME B18.2.3.4M 1527
 ANSI/ASME B18.2.3.5M 1530
 ANSI/ASME B18.2.3.9M 1526–1527
 ANSI/ASME B18.21.1 1515–1519
 ANSI/ASME B18.21.2M 1515
 ANSI/ASME B18.3 1601–1605, 1607–1608, 1611–1613
 ANSI/ASME B18.3.1M 1532, 1539, 1541
 ANSI/ASME B18.5 1505–1509
 ANSI/ASME B18.5.2.2M 1527–1528, 1531
 ANSI/ASME B18.6.2 1599–1600, 1606, 1609–1610
 ANSI/ASME B18.6.5M 1623, 1635–1640
 ANSI/ASME B18.6.7M 1577–1585
 ANSI/ASME B18.8.2 1651–1655, 1658–1664
 ANSI/ASME B29.1 M 2421
 ANSI/ASME B29.1M 2421–2422, 2425–2429, 2438, 2442
 ANSI/ASME B29.3M 2422
 ANSI/ASME B32.3M 2503
 ANSI/ASME B36.10M 2504–2505
 ANSI/ASME B5.1M 1645–1647
 ANSI/ASME B5.10 848, 909–914, 918
 ANSI/ASME B5.15 2156
 ANSI/ASME B5.50 1284–1286
 ANSI/ASME B92.2M 2156
 ANSI/ASME B94.11M 829, 839–841, 846–847, 849
 ANSI/ASME B94.19 772–795
 ANSI/ASME B94.6 1211, 1213–1214
 ANSI/ASME B94.9 872
 ANSI/ASME Y10.3M 115
 ANSI/ASME Y14.2M 607
 ANSI/AWS A2.4 1396
 ANSI/AWS 2.4-79 1408
 ANSI/EIA RS 274-D 1227, 1240–1241, 1243, 1245, 1248–1249, 1264
 ANSI/RMA IP-20 2379–2381
 ANSI/RMA IP-21 2386
 ANSI/RMA IP-22 2373–2375, 2377
 ANSI/RMA IP-23 2394–2396
 ANSI/RMA IP-24 2409, 2411–2414
 ANSI/RMA IP-25 2402–2403
 ANSI/RMA IP-26 2397, 2400
 ANSI/RMP IP-21 2387
 ANSI/RMP IP-24 2411
 ANSI/SAE AS568A 2482
 Antifriction bearings 2246–2302
 Apothecaries'
 fluid measure 2518
 weight 2519
 Application factor 2044–2045
 Applying surface texture symbols 706
 APT (automatically programmed tool) 1263–1280
 axis nomenclature 1235
 circles 1265–1270, 1272
 computational statements 1265
 example program 1277
 for turning 1279–1280
 geometry statements 1265
 geometry, 3-D 1274
 motion statements 1270–1275
 planes 1273
 points 1266
 postprocessor statements 1275–1280
 programming 1263–1280
 tabulated cylinder 1274
 Arbors
 circular saw 1203
 diameters for spring-winding 332
 dimensions of centers 813
 driving slots and lugs for shell reamer 823
 keys and keyways for 794
 lathe 858
 shell reamer 823
 standard milling machine 920–924
 steels for 456
 Arbor-type milling cutters 790
 Arc
 checking radius of 690–692
 electric, cutting of metals 1391, 1428–1429
 length of given angle and radius 80–81
 of action 1998
 of approach 1998
 of recession 1998
 plasma welding 1387–1391
 thickness of internal gear tooth 2047
 thickness of pinion tooth 2047
 welding 1362–1387
 Arc of recession 1998
 Area
 circle 63
 circular
 ring 64
 ring sector 64
 sector 63
 segments 63, 78, 80–81
 cycloid 63
 different sections 217–227
 ellipse 65
 enclosed by cycloidal curve 58
 fillet 64
 finding by Simpson's rule 57–58
 geometrical figures 60–65
 hexagon 62
 hyperbola 65
 irregular outline 57–58
 octagon 62
 parabola 64–65
 segment of 65

- Area *(continued)*
- parallelogram 60
 - plane figures 60–65
 - plane surface of irregular outline 57–58
 - polygon 62
 - rectangle 60
 - spandrel 64
 - square 60
 - surface of revolution 56–57
 - trapezium 62
 - trapezoid 61
 - triangle 61
- Areas and volumes 56–59
- Argon, welding gas 1364–1366, 1374, 1387–1388
- Arithmetical
- operations, sequence of 21
 - progressions 43–44
- ASA B1.10 1902
- ASA B1.12 1559
- ASA B17c 281
- ASA B18.2 1492, 1510
- ASA B5.38 1207–1210
- ASA B6.1 2005, 2009–2010
- ASA Code for transmission shafting 280
- Asbestos, specific gravity and weight 370
- ASCII, American Standard Code for Information Interchange 1295
- ASME Y14.5M 609
- ASME/ANSI B 1.8 1800
- ASME/ANSI B1.5 1807
- ASME/ANSI B1.1 1739, 1753–1754
- ASME/ANSI B1.12 1786
- ASME/ANSI B1.3M 1753
- ASME/ANSI B1.5 902, 1792–1794, 1796, 1799–1805, 1808–1811
- ASME/ANSI B1.8 1793, 1801, 1811–1813, 1815
- ASME/ANSI B29.1M 2423, 2443
- ASME/ANSI B94.9 872, 876–895, 897–898
- ASTM A 220 1331
- ASTM A297 1334
- ASTM A307 1488, 1495
- ASTM A325 1488
- ASTM A325M 1530
- ASTM A354 1488, 1496
- ASTM A449 1488, 1496
- ASTM A490 1488
- ASTM A490M 1530
- ASTM A563M 1542, 1544, 1547
- ASTM A574M 1531
- ASTM A743-81a 1335
- ASTM B23-83 2239
- ASTM B253 1447
- ASTM B438-83a 2243–2245
- ASTM B439-83 2243, 2245
- ASTM B633 1451
- ASTM E-140 2306
- ASTM E-18 2306
- ASTM F467M 1544
- ASTM F568 1530
- ASTM F594 1494
- ASTM F837M 1531
- ASTM 574M 1530
- Atmospheric pressure 393, 2519
- Austempering 479, 491–492
- Austenite 483–484, 514
- Austenitic manganese cast steel 1335
- Autocollimation 1219–1220
- Autogenous, (welding) 1362
- Automatic screw machines 1094–1099
- knurling on 1094
- Avoirdupois or commercial weight 2518
- Axial
- pitch 1998
 - plane 1998
 - thickness 1999
- Azimuth reading displacements 1219
-
- ## B
- B & S automatic screw machines 1094
- Babbitt metals 2238–2242
- properties of 2240–2242
 - SAE general information 2238
- Backlash 1999
- allowance in checking gears by the pin method 2103
 - control of allowances in production 2039
 - control of in assemblies 2041
 - determining proper amount of 2036
 - fine-pitch gears 2040
 - gearing 2036–2042
 - recommended 2038
- Bainite 481
- Balance wheels 173
- Balancing
- calculations 167–172
 - counterbalancing masses located in two or more planes 170–171
 - counterbalancing several masses located in single plane 168–170
 - dynamic 167
 - lathe fixtures 171–172
 - machines 167
 - rotating parts 167–172
 - running or dynamic 167
 - static 167
- Ball bearings 2246–2252, 2254–2261, 2264–2266, 2271–2301
- alignment and squareness 2273–2274
 - allowance for axial displacement in 2264
 - angular contact 2246–2248
 - cage materials 2254–2255
 - clamping and retaining methods 2274–2280
 - clearances, running 2282–2284
 - closures 2275, 2280
 - design and installation 2264
 - designations of 2267
 - failures 2285

- Ball bearings (continued)
- fits 2275, 2280
 - flanged housing 2254
 - friction losses 2280
 - handling precautions 2284–2285
 - housing bore tolerances 2267–2268
 - housings, soft metal and other 2274–2275
 - life 2285
 - life adjustment factors 2296
 - locknuts and shafts for 2277–2278
 - lockwashers for 2276
 - lubricants 2318–2320
 - lubrication 2282
 - materials for 2254
 - mounting 2271–2284
 - pillow block 2254
 - plastics 2254
 - quiet or vibration-free mountings 2275
 - radial and axial clearance 2283–2284
 - rating life 2287–2291
 - seating fits for 2275
 - selection 2281–2283
 - shaft
 - and bore limits 2267–2268
 - and housing fits for metric radial 2264–2266
 - tolerance
 - classifications, metric 2265–2266
 - limits, metric 2266–2267
 - special or unconventional types of 2254
 - squareness and alignment 2273–2274
 - starting torque 2281
 - static
 - equivalent loads 2300–2301
 - load ratings 2297–2300
 - thrust 2250
 - tolerances 2255–2261
 - types of 2246–2254
- Ball, roller, and needle bearings 2246–2302
- Balls, standard 2302–2310
- grades 2305
 - hardness corrections 2306
 - hardness ranges 2306
 - materials 2305
 - number per kilogram 2310
 - number per pound 2309
 - ordering specifications 2303
 - package markings 2293–2294
 - preferred gages 2303
 - preferred sizes 2306–2308
 - tolerances 2305–2306
- Band brakes 2337–2339
- Band saw
 - blade selection 1101–1102
 - break-in 1105–1106
 - speeds and feeds, metal cutting 1103–1105
- Bar, small diameter radius of gyration 147
- Barometer reading and equivalent pressure 395
- Barrel
 - liquid capacity 2518
 - volume 71
- Barrel effect 1319
- Base
 - circle 1999, 2127
 - diameter 2127
 - helix angle 1999
 - pitch 1999
 - tooth thickness 1999
- Base circle 1999
- Base circle, spur gear
 - diameter 2004
- Base helix angle 1999
- Base oils for metal cutting 1109
- Base pitch 1999
- Base tooth thickness 1999
- Basic
 - endurance limit 2044
 - gear dimensions 2010
 - rack profiles 2153
 - space width 2127
- Basic dimension 621
- hole 621
 - shaft or hole 621
- Baths, hardening or quenching 488–490
- for heating steel 487
 - tanks for 490–491
- Baumé's hydrometer 372
- conversion to specific gravity 371
- Beams 239, 241–242, 248–249, 251–259, 2488–2494
- channel 2494, 2498
 - combined stresses in 206–210
 - curved 254–257
 - deflections 236, 239, 241–242, 253–254
 - designing for 253–254
 - fixed at
 - both ends 252
 - one end 241–242, 249, 251
 - formulas 207
 - I-beams 2488–2493, 2498
 - reactions 236
 - rectangular solid 249
 - simple stresses in 204–205
 - stresses in 204–210, 236, 239, 241–242, 248, 252–258
 - stresses produced by shocks 257–258
 - supported at both ends 239, 249
 - uniform strength 248, 251–252
- Bearing lubricants
 - ball and roller bearings 2318–2320
 - plain bearings 2202–2205
- Bearing materials, plain 2236–2244
- aluminum 2238, 2241
 - ASTM compositions 2239–2245
 - babbitt metals 2238–2242
 - cadmium alloys 2240–2242
 - carbon-graphite 2241–2245
 - cast iron 2241
 - copper-lead 2238–2242

- Bearing materials, plain (continued)
- die casting in place 1344
 - graphitic 2242, 2245
 - laminated phenolics 2242
 - leaded bronze 2240–2242
 - nylon 2242
 - oil impregnated 2242–2245
 - plastics laminates 2242
 - porous 2241–2245
 - properties 2236–2237
 - rubber 2242, 2245
 - SAE compositions 2238–2239
 - seals 2198–2199
 - silver 2241
 - Teflon (TFE) 2242, 2245
 - tin-bronze 2240–2242
 - white metal 2238–2242
 - wood 2242, 2245
- Bearing spacing and shaft stiffness 2053
- Bearings 2193–2218, 2220–2244, 2246–2300
- guide 2236–2237
- Belleville springs or washers 326
- Belts and pulleys 2368–2420
- flat belts 2368–2371
 - V-belts 2372–2420
- Bending
- allowances, sheet metal 1304–1310
 - formulas
 - for beams 239, 241–242, 249, 251–257
 - for shafts 275–277
 - stress in beams 236, 239, 241–242, 248–249, 251–254
 - structural angles 2495–2497
- Bending load wood 375
- Beryllium and copper alloys 566
- Bevel gearing 2050–2063
- ANSI/AGMA Standard 2054
 - applications 2051–2053
 - applications of 2051
 - backlash 2037–2038
 - bearing spacing 2053
 - blank design 2052–2053
 - cutting teeth in 2053–2062
 - face angles 2054, 2056–2057
 - face widths 2054, 2056–2057
 - German standard tooth form 2090
 - Gleason system, straight bevel
 - gears 2054
 - Zerol bevel gears 2050–2051
 - hypoid gears 2051
 - materials for 2063
 - milled 2054, 2056–2062
 - milling cutters for 792, 2058–2060
 - milling setup 2061–2062
 - mountings 2052–2053
 - nomenclature 2054–2056
 - octoid tooth form 2053
 - planetary 2083, 2087
 - replacement gear dimensions 2122–2125
 - selecting formed cutters for 2060
- (continued)
- Blade gearing (continued)
- shaft stiffness 2053
 - spiral 2050
 - straight 1998, 2050, 2052, 2054
 - tooth measurement for milled 2062
 - types of 2050
 - typical steels used for 2063
 - Zerol 1998, 2050–2052
- Bilateral and unilateral tolerances 621–622
- Binary multiples 2533
- Birmingham wire gage 2499–2500
- Birnie's equation 272
- Blank diameters, drawing dies 1302–1307
- Blanks, sintered carbide 738–740
- Blast cleaning of castings 1338
- Block
- brakes 2340
 - NC 1241, 1243, 1245
 - or multiple indexing 1990–1991
- Blow, force of 159–160
- Boilers, strength of flat stayed surfaces 268
- Boiling temperature, various substances 364
- Bolt head
- markings, inch 1484–1488
 - metric 1532, 1534, 1560–1561
 - wrench and socket clearances 1510–1511
- Bolt hole circles
- chordal distance 78
 - coordinates for 953–970
- Bolts and nuts
- ANSI, inch dimensions
 - cap or acorn nuts 1503
 - countersunk bolts 1508–1509
 - fin neck bolts 1506
 - flat jam nuts 1500
 - heavy hex bolts 1495
 - heavy hex structural bolts 1493–1494
 - hex
 - bolts 1493
 - flat nuts 1500
 - high nuts 1504
 - nuts 1493–1494, 1499
 - slotted high nuts 1504
 - slotted nuts 1500–1502
 - thick slotted nuts 1501–1502
 - jam nuts 1499
 - machine screw nuts 1568
 - ribbed neck bolts 1507
 - round head bolts 1505–1507
 - square
 - bolts 1492–1494
 - neck bolts 1505–1508
 - nuts 1492–1493, 1502
 - step bolts 1508
 - T-bolts 1646
 - T-head bolts 1505
 - T-nuts 1647
 - types of 1492–1493
 - Unified 1489–1490, 1492–1496, 1499–1502
 - wing nuts 1693–1697

- Bolts and nuts** (continued)
- ANSI, metric dimensions
 - clearance holes 1532
 - designation 1532
 - diameters 1523
 - heavy hex
 - bolts 1529
 - nuts 1548
 - structural bolts 1529
 - hex
 - flange nuts 1545
 - jam nuts 1548
 - hex nuts 1543
 - identification symbols 1532
 - materials and mechanical properties 1534
 - prevailing torque hex
 - flange nut 1547
 - nuts 1546
 - reduced diameter bolts 1524, 1527
 - slotted hex nuts 1544
 - thread series 1532
 - British Standard
 - Fine thread 1552–1559, 1619, 1838–1840
 - hexagon 1551–1554
 - metric hexagon 1555–1561
 - standard thread 1839
 - Unified 1597
 - Whitworth 1551–1554, 1591, 1595–1598, 1619, 1836–1838, 1868
 - eye bolts and nuts 358–359
 - grade markings for steel 1484–1488, 1532, 1534, 1541, 1560–1561
 - load allowable on bolts 1489–1491
 - spacing for wrench clearances 1510–1511
 - tightening 1475
 - torque required to tighten 1475–1488
 - working strength of bolts 1489–1491, 1559–1560
 - wrench clearances for 1510
 - wrench openings 1510
 - Bolts and screws 1492
 - Bonding, adhesives 2460
 - Boring
 - carbide tools for 859–864
 - cutting time for 1044
 - wood 378
 - Boring-bar, cutters, carbide 859–864
 - Boron nitride
 - cubic (CBN) abrasive 982, 1140, 1157, 1166
 - cutting tool materials 982
 - speeds and feeds for 1002, 1008, 1018–1022
 - Bottom land 1999
 - Box wrench clearances 1510
 - Brads and wire nails 1455
 - Brakes
 - band 2337–2339
 - block type 2340
 - coefficient of friction 2338–2340
 - Brass
 - castings 525–532
 - coloring 1441–1442
 - strength and physical properties 477
 - wire, strength 477
 - EDM 1328–1329
 - Brazing 1354–1361
 - filler metals for 1354–1359
 - fluxes for 1354–1359
 - heating for 1360
 - symbols 1361
 - workholders for 1360
 - Break-even analysis 40–42
 - Bricks
 - specific gravity and weight 370
 - strength 478
 - Briggs (now ANSI) standard pipe
 - thread 1849–1850
 - Brinell hardness 473, 475, 516–524
 - aluminum alloys 550–555
 - cold-drawn carbon steel rounds, squares, and hexagons 395–396
 - heat-treated steels 432–436
 - magnesium alloys 560
 - Rockwell conversion tables 520
 - stainless steels 439
 - British Association
 - standard screw threads 1839
 - tolerance formulas 1839
 - British Standard
 - BS 1083 1551, 1553–1554
 - BS 1157 1838, 1903–1904
 - BS 1387 1857
 - BS 1449B 1565
 - BS 1580 1551
 - BS 1657 1825
 - BS 1768 1492, 1551
 - BS 1769 1492, 1551
 - BS 1807 2043
 - BS 1916 1650
 - BS 1981 1595, 1597
 - BS 2059 2156
 - BS 21 1856–1858
 - BS 235 2043
 - BS 2519 2043
 - BS 2693 1551, 1559, 1562
 - BS 2708 1551
 - BS 275 1464, 1471
 - BS 2779 1856–1857
 - BS 2827 1586
 - BS 2870 1565
 - BS 2963 1559
 - BS 3027 2043
 - BS 308 2043
 - BS 328 848, 850–856
 - BS 3382 1559, 1586
 - BS 3550 2156

- British Standard *(continued)*
- BS 3643 902, 904, 1560, 1587, 1826, 1831, 1834
 - BS 3692 1551, 1555–1559, 1904–1905
 - BS 3696 2043
 - BS 4084 1825
 - BS 4168 1613–1618, 1904–1905
 - BS 4183 1586, 1588–1589, 1592–1594, 1904–1905
 - BS 4186 1904
 - BS 4190 1551, 1904
 - BS 4235 2354–2355, 2357–2360
 - BS 4320 1565–1567
 - BS 436 2042–2045
 - BS 4464 1563–1565
 - BS 45 1840
 - BS 450 1586, 1595, 1598
 - BS 4500 657, 660–663, 665–666, 2356
 - BS 46 2359, 2361–2364, 2367
 - BS 4620 1473–1474
 - BS 545 2043
 - BS 57 1586
 - BS 6 2365
 - BS 6104 1613
 - BS 6105 1613
 - BS 6186 2156
 - BS 641 1472
 - BS 721 2043
 - BS 821 2043
 - BS 84 1551, 1838
 - BS 93 1551, 1839
 - BS 949 902–903
 - BS 970 2354
 - BS 978 2043
 - clearance holes for metric bolts and screws 1903–1904
 - combined drills and countersinks 847
 - countersunk head screws 1591–1598
 - dowel pins, metric 1648–1650
 - drills, metric 850–856
 - fasteners, mechanical properties 1559–1560, 1613
 - Fine threads (BSF)
 - basic dimensions 1838
 - tolerance formulas 1836
 - hexagon bolts 1551–1554
 - hexagon socket screws, metric 1613–1618
 - button head 1617
 - cap 1614–1615
 - set 1616–1618
 - Imperial wire gauge 2499–2500
 - interference fits 1551, 1562
 - ISO metric
 - grade markings 1559–1560
 - hexagon bolts, screws, and nuts 1555–1561
 - limits and fits 657–666
 - tapping drill sizes for 1903
 - taps 902–903
 - threads 1825–1834
- British Standard *(continued)*
- keys and keyways 2354–2367
 - limits and fits for holes and shafts 657–666
 - machine screws 1586–1598
 - metric
 - and inch pipe threads 1856–1858
 - basic sizes, preferred 667
 - bolts, clearance holes 1903–1904
 - comparison of British, French, German and Swiss 1780
 - dowel pins 1648–1650
 - drills 850–856
 - hexagon socket screws 1613–1618
 - keys and keyways 2354–2367
 - limits and fits 657–666
 - machine screws and nuts 1586–1595
 - series plain washers 1565–1566
 - series spring washers 1563–1565
 - taps, ISO 902–903
 - threads 1780
 - nuts 1552–1555, 1557–1559, 1586–1597
 - PD 3376 2043
 - PD 6457 2044
 - pipe threads, parallel 1856–1857
 - pipe threads, taper 1857–1858
 - preferred metric basic sizes 667
 - preferred numbers 667
 - rivets 1464, 1471–1474
 - screws 1551–1560, 1586–1598, 1613–1619
 - thread dimensions 1825–1858
 - thread profiles 1825, 1836
 - spark plugs 1840
 - spur and helical gears 2042
 - straight splines 2156
 - studs 1551, 1562
 - tapping drill sizes, ISO metric threads 1901–1903
 - taps, ISO, metric 902–903
 - thermal units, (BTU) 2514
 - converted into foot-pounds 2553
 - power and heat equivalents 2551
 - Unified
 - machine screws and nuts 1595–1597
 - screws and nuts 1595–1597
 - thread sizes 1706–1710, 1712–1754, 1781–1785
 - UNJ profile threads 1825–1826
 - washers, plain, metric 1565–1567
 - Whitworth threads (BSW)
 - machine screws 1595–1598
 - set-screws 1595–1598, 1619
 - thread form 1836–1837
 - tolerance formulas 1836
- Broaches
- chip breakers 930–931
 - clearance angles for teeth 930
 - depth of cut per tooth 929
 - depth of teeth 930
 - face angle or rake 930

- Broaches
 land width 930
 pitch of teeth 927–930
 radius of tooth fillet 930
 shear angle 930–931
 surface 928
 total length of 930
 types 926–927
- Broaching 926–932
 cutting oils for 1108–1109
 cutting speeds for 1043
 difficulties 932
 pressure 928
 types of machines 930–931
- Broken tap, removal of 1905–1908
- Bronze 525
 castings, strength 477
 strength 477
- Brown & Sharpe
 automatic screw machines 1094–1099
 milling machines 1979
 taper 906, 915–916
 taper reamers for sockets 825
 wire gage 2499–2500
- Brush finishing, power 1435–1438
- Buckingham formula for pin method of
 checking screw threads 1867–1870
- Buckling, columns 261–262
- Buffing and polishing 1439–1440
 wheels for 1440
- Built-up Sections, Moments of Inertia 217
- Bulk modulus of various material 384
- Bulk temperature thermal flash factor 2045
- Burs and files, rotary 1433
- Bushings
 gear 2117
 jig, materials for 941
 standard, for jigs 941–951
 steels for 456
- Butt joint, riveted 1457–1462
- Buttress threads 1817–1824
 allowances and tolerances 1821–1823
 ANSI Standard inch type 1818–1824
 basic dimensions 1817–1818
 British Standard 1825
 designations 1824
 diameter-pitch combinations 1817–1818
 miscellaneous types 1817–1824
 symbols and formulas 1820
 thread form 1818–1819
 wire method of measuring 1875–1877
- Byte 2533
- Byte, PLC 1229
- B18.2.1 1492
- B18.2.2 1492
- B18.6.7M 1577
- (continued)*
- ## C
- Cables, wire, breaking strength 336–341
- CAD/CAM 1287–1297
 drawing exchange standards 1294–1296
 projections 1289
 rapid prototyping 1296
 standard lettering sizes 1294
 tips 1290
- Cadmium
 bearing alloys 2240
 plating 1444
 vacuum coating 1451
- Cage materials, anti-friction bearings 2254–2255
- Calculation procedure 1137
- Calculations
 strength of materials, sample 212
- Caliper
 gear tooth 2018–2020, 2108–2111
 measurement of 2020
 vernier 669
- Calorie, kilogram 2514, 2546
- Cams and cam design 1098–1099, 2163–2188
 acceleration, velocity, and displacement
 formulas 2163–2167
 classes of cams and followers 2163–2164
 cylindrical cams 2185–2187
 design example 2181–2184
 displacement
 constant velocity 2165
 curves 2163–2167
 cycloidal 2166–2167
 diagrams 2163–2169
 harmonic 2165–2167
 parabolic 2165–2166
 synthesis of 2167–2169
 forces 2179–2184
 machining errors, effect on
 acceleration 2183–2184
 materials 2179–2186
 milling 2186–2188
 pressure angle 2171–2178
 profile determination 2168–2171
 radius of curvature 2178–2184
 rollers 2186–2187
 size determination 2172–2176
 stresses, contact 2179–2180, 2184
 threading cams, screw machine 1094–1098
- Canned (fixed) cycles, NC 1258–1262
- Cap screws 1496, 1599–1604
 button head 1604
 drill and counterbore sizes for 1601–1602
 fillister head 1600
 finished, hexagonal 1496
 flat head 1599, 1603

- Cap screws *(continued)*
- hexagon socket type 1601–1604
 - hexagonal 1496
 - metric 1521
 - round head 1600
 - spline socket type 1601–1604
 - tap drill sizes 1889–1907
- Capacitor 1319
- Capital recovery 28
- Carat 2518
- Carbide tools
- application of cutting fluids to 1111
 - boring 859–865
 - coated 980–981
 - cutting 738–740
 - grinding 937–940
 - insert holders 726, 732–738, 1281–1284
 - insert type 726, 730–738
 - materials for 747–757, 979–981
 - sharpening 937
 - standard blanks for 738–740
 - tips for boring tools 859–864
 - tips for turning tools 741–746
- Carbides and carbonitrides 747–752
- Carbon
- monoxide, specific gravity 371
 - steel castings 1333–1334
 - steels 403, 406
 - AISI-SAE designations 409–410
 - cold drawn 430–431
 - composition of, SAE 420
 - heat treatments 504
 - mechanical properties 432–436
 - numbering system 403, 405
 - quality variations 418
 - speeds for milling 1014–1019, 1022
 - speeds for turning 996–999
 - structure of 483
 - tool steel as a cutting tool material 978
 - unified numbering system 403, 405, 413
- Carbon dioxide
- solidification temperature 623
 - specific gravity 371
- Carbonaceous mixtures 498
- Carbon-graphite bearings 2242, 2245
- Carbonitrides and carbides 747–752
- Carbonitriding 417–418
- Carburizing 417, 479, 498
- gas 498
 - liquid 498
 - solid materials 498
 - steels for 422–423
 - temperatures 504–505
 - vacuum 499
- Cartesian coordinates 36
- Case hardening 416–418, 479, 498
- steel 497
- Cash flow 30–31
- discounted 30–31
- Cast iron *(continued)*
- alloy 1328–1329
 - bearings 2241
 - chilled 1328–1329
 - density 370
 - ductile 1332
 - gray 1328–1329
 - malleable 1330–1331
 - Meehanite 1328–1329
 - nodular 1332
 - speeds and feeds for
 - drilling, reaming, and threading 1037–1038
 - milling 1021–1022
 - turning 1002–1003
 - strength 476
 - white 1328–1329
- Cast roller chains 2421
- Cast steel 1332–1336
- strength 476, 1332–1335
- Casting processes
- aluminum alloys 1342–1343
 - die casting 1337–1344
 - ductile iron 1332
 - gravity die casting 1337–1338
 - gray iron 1336–1337
 - green-sand molding 1336–1337
 - investment casting 1345–1347
 - low pressure casting 1337–1338
 - permanent mold 1337–1338
 - shell-molding 1336–1337
 - squeeze casting 1337–1338
 - V-process 1336–1337
- Castings
- alloy steel 1332–1335
 - blast cleaning 1338
 - brass and bronze 525–532
 - bronze and brass for gears 2117–2119
 - carbon steel 1333–1334
 - cleaning methods 1338
 - ductile (nodular) iron 1332
 - finishing operations 1338
 - heat treatment 1338
 - heat-resisting 1328–1329
 - investment 1345
 - malleable iron 1330–1331
 - malleable iron, strength 476
 - manganese steel 1335
 - Meehanite 1328–1329
 - nodular cast iron 1332
 - nonferrous strength 477
 - removal of gates and risers 1338
 - shrinkage of 1339–1343
 - steel 1332–1336
 - steel, for gears 2063, 2113–2117
 - surface texture of 708
 - weight, obtained from pattern weight 1340
- Castle and slotted nuts 1493, 1500–1502, 1552, 1554
- Cathode 1319

- Cell, flexible manufacturing, NC 1235
- Celsius (Centigrade) and Fahrenheit temperatures 2514–2516
- Cement, strength of 478
- Cementation 479
- Cemented carbide tools 747–752
 - coated 750–752
 - grinding 937–940
 - materials for 979–981
 - speeds for drilling with 1030–1033, 1035–1041
 - speeds for milling with 1013–1022
 - speeds for turning with 996–1009
- Cementite 483
- Cements, pipe joints 2464–2466
- Center
 - distance, gear set 2010, 2012, 2080
 - drills reamers and machine countersinks 813
 - of oscillation 151
 - of percussion 151
- Center distance 1999
- Center distance, gearing 1999
- Center of gravity 136–142, 151
 - any four-sided figure 137
 - circle sector 138
 - circular arc 137
 - cone 140
 - cone, frustum 140
 - cylinder 139
 - cylinder, portion of 139
 - ellipse segment 138
 - ellipsoid, segment of 141
 - fillet 138
 - of two bodies 141
 - parabola, area of 139
 - paraboloid 141
 - part of circle ring 138
 - perimeter or area of parallelogram 136
 - pyramid 140
 - pyramid, frustum 140
 - spandrel 138
 - sphere, hollow 141
 - spherical sector 141
 - spherical segment 141
 - spherical surface 138
 - spheroid, segment of 141
 - trapezoid 137
 - triangle 136
 - wedge 140
- Centering tools
 - feeds for 1094–1095
 - length of point 925
- Centerless grinding 1183–1185
 - screw threads 1926–1927
 - troubles 1184–1185
- Centers, for arbors and reamers 813
- Centimeter-gram-second system of measurement 2520
- Centimeter-inch conversion tables 2533
- Centipoises 2201–2202, 2312–2313, 2319
- Centistokes 2201–2202, 2312–2313, 2319
- Central plane 1999
- Centralized lubrication systems 2313–2315
- Centralizing Acme threads 1802–1811, 1816
 - alternative series 1816
 - designation 1811
 - formulas for determining diameters 1804
 - limiting dimensions 1804–1807, 1811
 - major and minor diameter allowances and tolerances 1810
 - pitch diameter allowances 1808
 - thread data 1807
 - thread form 1794, 1803
- Centrifugal
 - clutches 2332
 - force 163–166
 - calculation 164
 - stresses in flywheels 178
- Ceramic cutting tool materials 752–755, 981
- Cermets 747
- Chain
 - cast roller 2421
 - close-link 355
 - crane and hoisting 351–360
 - detachable 2421
 - pintle 2421
- Chamfers and corner clearance, gearing 2135
- Change gears
 - helical gear hobbing 2080–2083
 - helical milling 1931
 - leads and angles for helical milling 1946–1947
 - relieving helical-fluted hobs 1916–1917
 - thread cutting, lathe 1912–1916
 - fractional ratios 1913–1914
 - fractional threads 1912
 - metric pitches 1912–1913
 - modifying the gearbox output 1913–1916
 - threads per inch with given combination 1912
- Channels
 - aluminum 2498
 - elements of 2494, 2498
 - moment of inertia 2494, 2498
 - radius of gyration 2494, 2498
 - section modulus 2494, 2498
 - steel 2494
 - structural 2494, 2498
 - weight per foot 2494, 2498
- Characteristic, logarithm 102, 104
- Charcoal, weight and volume 371
- Checking
 - Acme threads by three-wire method, table 1872
 - American standard threads by three-wire method, table 1866–1867
 - assembly 619
 - castings 619
 - dimensions 619
 - drawings 618–619

- Checking *(continued)*
- for strength 618
 - gear size 2094–2112
 - machined parts 620
 - radius of arc 690–693
 - Whitworth threads by three-wire method, table 1868
- Cheese head screws, British Standard 1591, 1595–1596, 1598
- Chemical
- treatment of metals 1440–1443
 - vapor deposition (CVD) 750
- Chilled cast iron 1330
- Chipbreakers 728
- grinding 939–940
- Chisels, cold steels for 456
- Chord
- length for given angle and radius 80–81
 - length for given number of divisions 955–958
- Chordal addendum 1999, 2018
- milled bevel gear teeth 2064
 - milled, full-depth gear teeth 2016–2017
- Chordal distance of bolt circle 78
- Chordal thickness 1999
- gear teeth 2015–2017, 2062
 - milled bevel gear teeth 2064
 - milled, full-depth gear teeth 2016–2017
 - OD is special 2018
 - OD is standard 2015
- Chrome 1445
- Chromium
- plating 1427
 - tool steels 458, 460, 462
- Chucking reamers 808–822
- expansion 814
 - rose 808, 822
- Chucks
- drill, tapers and threads for 919
 - hexagonal, for portable tools 1210
 - spindle, for portable tool grinders 1207
- Cincinnati milling machines, indexing movements 1986–1989
- Circles
- chords for dividing circumference of 955–958
 - dividing, on jig boring machine 959–970
 - enclosed within a circle 72–75
 - enclosed within a rectangle 77
 - geometry of 48–50
 - lengths of chords for dividing 955–958
 - packing
 - in circles 72–75
 - in circles and rectangles 72–77
 - in rectangles 77
 - programming in APT (NC) 1267–1270
 - segments 80–81
 - squares of equivalent areas 79
- Circular
- disk
 - radius of gyration 147
- Circular *(continued)*
- gear teeth 2006–2008
 - interpolation, NC 1254–1255
 - mil gage for wires 2517
 - pitch 1999, 2127
 - given center distance and ratio 2014
 - pitch gears, diameters of 2022
 - ring sector, area 64
 - ring, area 64
 - ring, thin flat 148
 - saws, arbors for 1203
 - sector segment 955–958
 - sector, area 63
 - segment, area 63
 - thickness 1999
 - milled bevel gear teeth 2064
 - outside diameter
 - has been enlarged 2015
 - has been reduced 2015
 - is standard 2014
- Circular arc
- enter of gravity 137
- Circular pitch 1999
- Circular pitch in gears 2022
- Circular thickness 1999
- Circumference, chords for dividing 955–958
- CL data, NC 1242
- Classical V-belts 2379–2386
- Clavirino's equation 271
- Cleaning castings 1338
- Clearance 1999
- angles
 - boring tools 859–864
 - milling cutters 800
 - punch and die 1301
 - reamers, tooth rest position 811
 - single-point tools 740–746
 - turning tools 740–746
 - drill sizes, machine screw 1900
 - for wrench 1510–1511
 - ANSI Standard 1532
 - British Standard 1903–1904
- Clevis pins 1648
- Closed-loop system 1233, 2468–2470
- Clutches 2329–2336
- centrifugal and free-wheeling 2332
 - cone 2330–2331
 - cutting with angular cutters 2334–2336
 - disk 2329
 - friction 2329–2330
 - friction coefficients 2330
 - magnetic 2331–2332
 - positive 2333–2334
 - power capacity of 2329
 - saw tooth 2335–2336
 - slipping 2332
 - wrapped spring 2332–2333
- CNC 1225–1226
- programming 1240–1280
- Coatings 1444–1451
- Coatings, conversion, of metals 1440–1443

- Cobalt 939
 - alloy 981
- Cobaltchrom steel 508
- Coefficient of friction 190–191, 2045, 2330, 2341
 - rolling resistance 191
- Coefficient of heat radiation 367
- Cold-form tapping 1904–1907
- Collets 971–973
- Colloidal suspension 1319
- Coloring metals 1440–1443
- Columns 261–267
 - American Institute of Steel Construction 264–265, 267
 - American Railway Engineering Association formulas 261
 - eccentrically loaded 262
 - Euler formula 261–263, 266–267
 - J. B. Johnson formula 262, 266–267
 - Rankine or Gordon formulas 261, 263
 - steel pipe, allowable concentric loads 264–265
- Combination
 - drill and tap 1909
 - shanks for end mills 781
- Combinations of involute spline types 2138
- Combined stress 206
 - normal stresses at right angles 206
- Combined stresses 207–210
- Compensation, insert radius, NC 1281–1284
- Complex conjugate 39
- Complex or imaginary numbers 38
- Composite, checking of gears 2042
- Compound
 - angles 688–690
 - indexing 1950–1956
 - thread cutting, NC 1263
- Compression
 - in beams 236, 256–257
 - in columns 261–267
 - of air 395–401
 - springs 285–305
- Compressive properties
 - ceramics 379
 - definitions 196
 - strength, values of 476, 478
 - wood 375–376
- Computer numerical control, CNC 1225–1226
 - programming 1240–1280
- Computer-aided (or-assisted)
 - design (CAD) 1287–1297
 - manufacturing (CAM) 1287
- Concave arbor-type milling cutters 790
- Concrete
 - specific gravity and weight 370
 - strength 478
- Conditional expressions, NC 1258
- Conductance, thermal 366
- Conductivity
 - electrical, of metals 1323–1324
- Conductivity (*continued*)
 - electrical, of plastics 580–581
 - thermal 368–370, 379
- Cone
 - center of gravity 140
 - clutches 2330–2331
 - frustum
 - center of gravity 140
 - polar moments of inertia 144
 - radius of gyration 150
 - frustum of 68
 - polar moments of inertia 144
 - radius of gyration 149
- Cone volume 68
- Conical pendulum 188–189
- Conjugate fractions 14–16
- Constructional steels 1150–1151
- Contact
 - diameter 1999, 2028
 - diameter, gearing 2028–2033
 - ratio 1999, 2029
 - face 1999
 - factor 2044–2045
 - total 1999
 - ratio, gearing 2024–2029
 - stress 1999, 2045
 - stresses, cams 2184–2186
- Contact diameter 1999
- Contact ratio 1999
- Contact ratio factor 2044–2045
- Contact stress 1999
- Contents of tanks 58–59
- Continued fractions 13–14
 - use of as conjugates 15–16
- Contour Milling 1994
- Contourmilling 1994
- Control, adaptive, NC 1233
- Convergents 13–16
- Conversational part programming, NC 1240–1241
- Conversion
 - coating of metals 1440–1443
 - cutting speed formulas 985
 - tables
 - angular measure 90, 92
 - cutting speed and diameter to rpm 986, 1174
 - cutting speed formulas 1908–1909
 - decimal equivalents of inch
 - fractions 2519
 - decimal multiples of SI units 2522
 - foot-pounds into Btu 2553
 - hardness 520–524
 - horsepower into kilowatts 2553
 - metric into English measure 2525–2550
 - miscellaneous English units 2532
 - oil viscosity unit 2201–2202, 2312–2313
 - pounds-force into newtons 2550
 - radians into degrees 90, 92

- Converting numbers to powers-of-ten notation 18
 Convex arbor-type milling cutters 790
 Coolants for
 lapping 1202
 machining
 aluminum 1116
 magnesium 1117–1118
 tool sharpening 939–940
 zinc alloys 1118
 tapping 1889–1890, 1909
 Coordinate system, converting to another 36
 Coordinates, for jig boring 953–970
 Copolymer 569
 Copper
 flat products, strength 477
 lead bearings 2238–2241
 linear expansion 368–369
 plating 1445
 silicon alloys 565
 wire, strength 477
 zinc-tin alloys, strength 478
 Copper and copper-base alloys
 cast 525–532
 classification 525
 Copper-beryllium 565–566
 die casting 1343
 passivation 1441–1442
 speeds, for drilling and reaming 1041
 for turning and milling 1006
 wrought 533–542
 Copper- and iron-base sintered bearings 2243–2245
 Copper Development Association 525–542
 Cordage Institute 353, 360
 Core drills 846–849
 Corner-rounding milling cutters 775, 790
 Corrosion-resisting alloys 425, 428, 525–566
 castings 1335
 Coscant 83
 Cosine 83
 Cosine law of 84
 Cotangent 83
 Cotter pins, standard sizes 1648, 1659, 1662
 Cotters 2354
 Coulomb shear theory (plastics) 584–585
 Counterbores 857–858
 Countersinks 813, 862
 combined with drills 845
 machine 813
 Countersunk head
 rivets 1466, 1470–1472
 British Standard 1464, 1472–1474
 screws 1569–1571, 1574–1575, 1591–1599, 1603
 British Standard 1591–1598
 Couples and Forces 120
 Couples of forces 121
 Couplings
 double-cone 2326
 Couplings *(continued)*
 fire-hose 1842–1845
 flexible 2327
 hose 1841–1843
 interference fits 2326
 knuckle joint 2328–2329
 safety flange 2325
 single keys used as fixed 2140, 2143
 slipping 2332
 universal 2327–2328
 CPVC plastics 380, 601, 2511
 Crane chain
 hoisting 351–360
 safe loads 352
 strength 351–354
 Crane motors 2456–2457
 Crane, hooks 351–360
 capacity of 357
 dimensions 357
 Crater-resistant carbide tools
 materials for 980
 Craters 1319
 Creep 524, 576–577
 rupture 524, 576–577
 Critical
 slenderness ratio 261–262
 speeds 185–186
 formulas for 185–186
 of rotating bodies and shafts 185
 speeds of rotating shafts 283
 temperatures, heat treatment 479, 485
 determining 486
 Crobalt alloy 981
 Croning shell mold process 1336–1337
 Crosby Group 356–359
 Cross recesses
 for machine screws 1577
 for self-tapping screws 1623
 Cross section lining, ANSI Standard for drawings 606, 608
 Crossed helical gears 1998
 Crowned
 involute splines 2145
 splines for large misalignments 2145
 Crowned involute splines 2145
 Crushing strength, wood 375
 Cryogenic treatment, steel 514–517
 Cube, volume 66
 Cubes of wire diameters 330
 Cubic
 boron nitride (CBN) 982, 1002, 1004, 1008, 1018, 1021–1022, 1139–1140, 1157, 1166
 grinding wheels 1157, 1166
 conversions 2542
 equations 33
 measure 2517, 2542
 Cumulative fatigue damage 198
 Cupola malleable iron 1330–1331
 Curve, normal distribution 1216–1219
 Cutoff 701

- Cutoff or roughness sampling length 707
- Cutter
- checking relief and rake angles 801, 805
 - clearance angles 800–801, 806
 - compensation, NC 1251–1253, 1281–1284
 - grinding 798–806
 - location data (CL data) 1242
 - radial relief, eccentric type 801–805
 - rake angles 800–801
 - spline 799
 - tooth rest positions 806
 - wheels for sharpening milling cutters 798–800
- Cutter compensation, NC 1251–1253, 1281–1284
- location data, NC 1242
- Cutters
- angular, milling 777, 783, 796–799
 - bevel gear, formed types 2058–2061
 - boring-bar 859–864
 - box-tool 1095
 - fluting, for reamers 808–810
 - helical gear, formed type 2077–2079
 - internal gear 2047
 - milling 771–806
 - speeds and feeds for sharpening 800
 - milling, steels for 452–456
 - roller chain sprocket 2439–2441
 - spur gear, formed type 2017–2021
 - T-slot 775
 - Woodruff keyseat 795
- Cutting
- abrasive 1204
 - electric arc 1428–1429
 - fluids 1106, 1108–1111
 - application of to carbides 1111
 - aqueous solutions 1107
 - broaching 1108–1109
 - carbides 1111
 - chlorinated oils 1107–1109
 - magnesium 1108–1109, 1111
 - mineral oil 1109
 - selection 1107–1109
 - soluble oils and compounds 1107
 - sulfurized oils 1107, 1109–1110
 - various alloys 1107–1109
 - gas torch cutting 1428–1429
 - roller chain sprocket teeth 2437
 - time for turning, boring and facing 1044
 - wire rope 344
- Cutting bevel gear teeth 2053
- Cutting speeds and feeds 978, 1040–1046
- automatic screw machine 1095
 - bandsaw 1103–1105
 - broaching 1043
 - chip thickness 992–994
 - cutting speed calculations 1005
 - cutting tool materials 444–471, 747–757
 - CVD diamond tools 982
- Cutting speeds and feeds (*continued*)
- diamond tools 981–982
 - drilling and turning titanium and titanium alloys 1007
 - drilling superalloys 1008–1009
 - drilling, reaming, and threading 1012–1043
 - copper alloys 1041
 - feeds 1012
 - ferrous cast metals 1037–1038
 - glass 1034
 - light metals 1039
 - plain carbon and alloy steels 1030–1035
 - stainless steels 1036
 - tool steels 1035
 - equivalent
 - chip thickness (ECT) 992–994
 - rpm for given cutting speed 986–990
 - rpm for given drill sizes and speed 986
 - formulas for 985, 1005
 - honing 1196–1198
 - metal cutting saws 1044
 - milling 1009–1012
 - feeds for high-speed steel cutters 1023
 - ferrous cast metals 1021–1022
 - plain carbon and alloy steels 1014
 - slit and slot 1012–1013
 - stainless steels 1019–1020
 - superalloys 1008–1009
 - titanium and titanium alloys 1007
 - with cemented carbide cutters 1009–1012
 - planing 1044
 - rpm for different speeds and diameters 987–990
 - shaping 1044
 - tapping 1012–1039, 1041–1043, 1959–1975
 - thread chasing 1041–1043
 - tool
 - angles 723–730
 - inserts 747–757, 1281–1284
 - life 982–983, 992–994
 - adjusting 755–757, 1004–1005, 1009, 1012, 1028
 - materials related to 978
 - tool steels 1000, 1018–1019, 1035
 - turning
 - copper alloys 1006
 - ferrous cast metals 1002–1003
 - hard-to-machine materials with CBN tools 1008–1009
 - light metals 1007–1008
 - plain carbon and alloy steels 996–999
 - stainless steels 1001
 - superalloys 1008–1009
 - titanium and titanium alloys 1007
 - tool steels 1000
 - unusual materials 1044
 - work materials 978

- Cutting tools 723–726
 angles 723–738, 1281–1284
 application codes, ISO 753
 carbide grade selection 747–757, 980–981
 carbon tool steels 978
 carbonitrides (cermets) 747–752, 981
 cast nonferrous alloy 981
 cemented carbides 747–757, 979–981
 ceramics 752–755, 981
 coated carbides 980
 coatings 750, 980
 compositions and properties 748–750
 crater-resistant carbides 980
 cubic boron nitride (CBN) 754–757, 982, 1140, 1157, 1166
 CVD diamond 982
 diamond 750–757, 981–982
 CVD 982
 polycrystalline 754–755, 981–982
 synthetic 755–757
 grades 752, 980–981
 high-speed steel 979
 inserts 1281–1284
 machining data 755–757
 materials 978–982
 sharpening 934–935
 single-point 723–738
 specifications, ISO 751–752
 titanium carbides 749–752, 980
 trouble-shooting checklist 983
 tungsten carbide 747, 979
 combined with other elements 749–750
 whisker-reinforced 754
- Cyanide
 bath for heating steel 487
 hardening 498
- Cyaniding 417–418, 480
- Cycloid 1999
 area 63
 curves, area enclosed by 58
- Cylinder
 center of gravity 139
 collapsing pressure 273–274
 hollow
 polar moment of inertia 144
 radius of gyration 149
 volume 68
 plates and shells 268–274
 polar moment of inertia 144
 portion of volume 67–68
 portion of, center of gravity 139
 radius of gyration 148
 strength to resist internal pressure 270–274
 working pressure vs. radius ratio 272
- Cylindrical coordinates 38
- Cylindrical grinding 1175–1183
 automation in 1178–1179
 basic process data 1178
- Cylindrical grinding (continued)
 high speed 1178–1179
 machines 1175
 operating data 1177
 selection of grinding wheels 1142, 1156–1157, 1166, 1176–1177
 traverse and plunge grinding 1175
 troubles 1179–1183
 workholding 1176
- Cylindrical tank, contents 58–59
- Cylindrical to rectangular coordinates 38
-
- ## D
- Data input, manual, NC 1240
- Datum referencing 610–611, 614
- Datum target points 616
- Datum targets 615
- Decalescence point in steel hardening 479, 485
- Decimal
 equivalents, fractions 2519
 multiples and submultiples of SI units 2522
 point programming, NC 1245
- Dedendum 1999
- Definitions
 gear terms 1998
 geometric dimensioning and tolerancing 610
 spline terms 2142
 surface texture 699
 surfaces of solid materials 697
- Deflection
 beams 236, 239, 241–242, 253–254
 calculating 206
 flat plates 268–270
 shaft, linear 280
 shaft, torsional 277–280
 springs
 compression and extension 302
 torsion 321–324
- Degrees, expressed in radians 90, 92
- Density 370
 air 394
 ceramics 379
 metals 368–370
 plastics materials 380
 powdered metals 383
 wood 376
- Department of Commerce 272–273
- Deposition rates (welding) 1367, 1375–1378, 1390–1391
- Depth of cut 982–983
- Depth of engagement 2127
- Derivatives of functions 34–35
- Detachable chains 2421
- Deviation, mean positional 1217
- Diameter of circle enclosing smaller circles 72–75

- Diameters for finished shafting 280
- Diametral
 - equivalent circular pitch and tooth proportions 2007–2008, 2091–2093
 - equivalent modules 2091–2093
 - pitch 1999
 - pitch knurls, (ANSI) Standard 1212–1215
 - pitch, gear teeth
 - sizes 2002–2004
- Diamond
 - concentration 937–938
 - dust for lapping 1201
 - grinding wheels 1152–1169
 - laps and lapping 1201
 - tool materials 754–757, 981–982
 - truing 1158–1162
 - wheels 937–939, 1163–1169
 - composition 1166
 - designation symbols 1163–1166
 - diamond concentration 937–939
 - feeds and speeds 1169
 - grades, grit sizes 937–938
 - modifications 1166
 - operating guidelines for 1169
 - selection of 1168
 - shapes of standard 1163–1166
 - speeds and feeds 1169
 - terminology 1163
 - thread grinding 1923
- Die blocks, steels for 452–456
- Die casting 1337–1344
 - alloys used 1342
 - bearing metals 1344
 - design 1341–1342
 - dies 1343–1344
 - machining zinc alloy 1118
 - porosity 1341
- Die sinkers' files 1432
- Diemaker's reamers 797
- Dies and punches, steel for
 - drawing 1302–1307
 - hot-working 452–454, 456
- Dies and taps
 - combination drill and tap 1909
 - maximum pitches 1929–1930
 - selection of 1885–1887
 - square thread 883, 887–890
 - tap drill size 901, 1889–1908
 - Acme threads 901
 - formula 1900–1901
 - metric 1903
 - pipe 1907–1909
 - Unified 1889–1902
- Dies, sheet metal
 - angular clearance for 1302
 - bending allowances 1304–1310
 - blank diameters for drawing 1304–1307
 - blocks, steels for 452–454, 456
 - clearance between punch and die 1301
 - diameter reductions in drawing 1305
- Dies, sheet metal (continued)
 - heat-treatment, steels for 452–454
 - lubricants 1302
 - press speeds and pressures 1302–1304
 - punching pressures 1302–1304
 - rectangular drawing 1302–1304
 - shut height of press 1302–1304
 - steels for various classes of die parts 452–454, 456
- Dies, steel rule 1315–1317
- Dies, threading, maximum pitches 1929–1930
- Differential
 - indexing 1976–1985
 - pulley 135
- Dimensioning and tolerancing,
 - geometric 606, 610–611
- DIN 867 2090
- Direct (or distributed) NC 1296
- Discounted cash flow 30–31
- Disk
 - circular, radius of gyration 147
 - clutches 2329
 - method of measuring tapers 682–683
 - springs 326
- Displacement in ball and roller bearings,
 - allowance for axial 2264
- Distance across bolt circle 687
- Distributed numerical control (DNC) 1296
- Distribution curve, normal 1216
- Dividing
 - circles 959–970
 - head
 - angular position 796–799
 - indexing 1947–1993
 - numbers written in powers-of-ten notation 19
- DNC 1296
- DOD-P-16232-F 1450
- Dolly bars for riveting 1467
- Double angle milling cutters 777
- Double V-belts 2386–2394
- Double-cone clamping couplings 2326
- Dovetail slides, measuring 682–683
- Dowel pins 1648–1654
 - metric 1648–1650
- Drafting practices, ANSI Standard 606–611
- Draw-in bolt ends 923
- Drawing
 - ANSI Standard
 - drafting practices 606–611
 - lines 606
 - sheet sizes 606
 - surface texture symbols 704–708
 - welding 1394–1409
 - bisect angle 52
 - checking 618
 - circle around square 54
 - circle around triangle 53
 - circular arc 53
 - data for gear blanks 2033

- Drawing** *(continued)*
- data for gears 2033–2036
 - data for involute splines 2139
 - divide line into equal parts 51
 - ellipse 54
 - equilateral triangle 52
 - helix 55
 - hexagon around circle 54
 - hyperbola 55
 - involute 55
 - metric dimensions on 708
 - parabola 55
 - parallel lines 52
 - perpendicular lines 51
 - sizes of sheets 606
 - square around circle 54
 - symbols
 - ANSI Standard 606–611
 - section lining 606
 - geometric 609
 - ISO 609
 - tangent to circle 53
 - triangle around circle 53
 - 45-degree angle 52
 - 60-degree angle 52
- Drawing data, splines 2140
- Drawing dies**
- annealing drawn shells 1302
 - blank diameters 1304–1307
 - brass 1302
 - depth drawn in one operation 1305–1307
 - diameter reduction in one operation 1305–1307
 - rectangular 1302–1304
- Drawing, or tempering, steel 493–495
- Drawings**
- checking
 - inspecting a new design 618
 - materials specified 618
 - method of making drawing 619
 - data for spur and helical gear 2036
 - metric dimensions on 710
 - scales of metric drawings 711
 - specifying spur and helical gear data on 2034
- Dressing grinding wheels** 1158–1162
- Drill**
- sizes for tapping Acme threads 901
 - sizes for wood screws 1456
- Drilling**
- accuracy of drilled holes 856–858
 - automatic screw machine feeds and speeds 1095
 - cutting speeds for 1094
 - ferrous cast metals 1037–1038
 - light metals 1039
 - superalloys 1008–1009
 - titanium and titanium alloys 1007
 - tool steels 1035
 - difficulties 1034
- Drilling** *(continued)*
- estimating thrust, torque, and power 1051–1055
 - feed rates for 1012
 - holes in glass 1034
 - holes, accuracy of 856–858
 - horsepower and thrust for 1051–1055
 - machine, shaftless motor type 2454
 - spade 865–871
- Drills**
- accuracy of drilled holes 856–858
 - angle of cutting point 934–936
 - chucks, tapers 919
 - cobalt high-speed steel 857
 - combined drills and countersinks 845–847
 - core, taper shank 847
 - cutting speeds and equivalent rpm 986
 - definitions of terms 827
 - diameters of tap 1889–1903
 - drivers 848–850
 - for taper pin reamers 1655–1658
 - grinding 934–937
 - jobbers length 829–835
 - length of point 925
 - metric, British Standard 847–856
 - nomenclature 827
 - screw machine drills 829–840
 - sharpening 935–937
 - sizes for tapping 1889–1903
 - for Acme threads 901
 - spade 865–871
 - steels for 856–857
 - straight-shank drill sizes
 - core drills 849
 - letter 833–834
 - metric 829–839
 - number 829–833
 - straight-shank, taper-length, drill sizes
 - fractional 830–839
 - letter 833–834
 - metric 830–839
 - number 830–833
 - screw machine length 840
 - tangs for 839
 - tap and clearance hole sizes 1900
 - taper-shank core drills 846–849
 - taper-shank drill sizes
 - fractional inch 841–846
 - metric 841–846
 - twist 827–858
 - types 827
- Drives**
- motors, NC 2471–2473
 - nose key 911–912
 - screws 1620–1621, 1635
 - square, for portable tools 1208
 - studs 1662
 - taper 910–911
- Driving slots and lugs for shell reamers and arbors** 823

Drop-forging dies, steels for 452–456
 Drums, chain and wire rope 342–343, 360
 Dry measure 2518, 2523
 Dryseal pipe threads 1852–1855
 taps for 881
 Ductile
 cast iron 1332
 iron 476, 1332
 Duranickel, machining 1118
 Durometer tests 521
 Dynamic
 balance 167
 stresses 257–258
 Dynamic factor 2044–2045
 Dynamic viscosity coefficient for
 lubricants 2324
 Dynamometers 2338–2341
 Dyne 2520

E

Earth, weight of 370
 Eccentricity 2136
 Economic Tool-life 1073
 ECT
 grinding 1121
 ECT (equivalent chip thickness) 992–994
 EDG (electrical discharge grinding) 1319
 EDM 1318–1329
 dielectric filter 1319
 dielectric fluid 1319
 dielectric strength 1319
 discharge channel 1319
 dither 1319
 duty cycle 1319
 electrode growth 1319
 electrode wear 1319
 electro-forming 1319
 Farad 1319
 gap 1320
 gap current 1320
 gap voltage 1320
 heat-affected zone 1323–1324
 ion 1320
 ionization 1320
 low-wear 1320
 negative electrode 1320
 no-wear 1320
 overcut 1320
 overcut taper 1320
 plasma 1320
 plunge (sinker) method 1321–1328
 electrode materials 1324
 machine settings 1322
 making electrodes 1327
 metal removal rates 1323
 positive electrode 1320
 power parameters 1320
 process 1321
 quench 1320

EDM *(continued)*
 recast layer 1320
 secondary discharge 1320
 spark in 1320
 spark out 1320
 square wave 1321
 stroke 1321
 UV axis 1321
 white layer 1321
 wire EDM 1321
 wire guide 1321
 wire method 1318, 1328–1329
 wire speed 1321
 workpiece materials 1323–1324
 Effective
 dimensions, splines 2127, 2136
 length of bolt 1479
 vs. nominal interest rates 25
 Efficiency 2000
 influence of friction on 191
 machine tool 1048–1051
 spade drilling 870
 riveted joints 1459–1462
 Elastic
 limit 196
 modulus 196
 for various materials 196
 plastics 583
 region 196, 1483–1484
 tightening fasteners in 1477–1481
 Elastic properties of material 384
 Elasticity (rigidity)
 modulus of 196
 in shear (torsion) 196
 spring materials 326–329
 various materials 196
 Elasticity factor 2044–2045
 Elastohydrodynamic lubrication 2321
 Electric
 arc, cutting metals 1428–1429
 dielectric strength
 ceramics 379
 plastics 380
 socket and lamp base threads 1846
 Electrical relationships 2532
 Electrodes (welding)
 characteristics of standard types 1378–
 1382
 AWS E60XX 1379–1383
 AWS E70XX 1381–1383
 current to use with 1367–1386
 deposition rates 1364, 1367–1370, 1375–
 1377
 diameter to use 1363–1364, 1372, 1381,
 1383
 selecting GTAW tungsten type 1385–
 1387
 wire, feed rates 1367–1375
 Electropolishing 1447
 Elements, table of chemical 363
 Elevation reading displacements 1219

- Ellipse
 area 65
 methods of drawing 54
 moment of inertia 222
 radius of gyration 222
 section modulus 222
 segment, center of gravity 138
- Ellipsoid
 polar moment of inertia 145
 radius of gyration 150
 volume 69
- Elongation
 carbon and alloy steels 432–436
 carbon steel rounds, squares, and hexagons 430–431
 copper alloys 526–542
 copper-beryllium alloys 566
 copper-silicon alloys 565
 high-strength, low-alloy steels 441
 Investment casting alloy 381
 magnesium alloys 560
 nickel alloys 562–563
 plastics 380
 stainless steels 439
 titanium alloys 564
 various metals 383
- Emery
 grades 1440
 grain numbers for polishing 1440
- End mills
 angles for milling teeth in 796–797
 ANSI Standard 779–789
 combination shanks for 781
 terminology of 778–779
- Endurance limit 197, 2044–2045
 for spring materials 295
- Energy 156–158, 1319
 kinetic 157–159
 of flywheels 173, 175
 potential 157–158
- Energy and momentum 154
- Engagement, length of thread 1489–1491
- Engine lathe, change gears 1912
- Enlarged pinions
 center-distance system for 2027
 in helical gearing 2077–2080
 in spur gearing 2019–2027
- Epicyclic gearing 2083–2087
 bevel gear type 2085–2087
 compound drive 2087
 ratios 2085–2087
- Epicycloidal curves, areas 58
- Equations
 cubic 33
 quadratic 33
 solution of
 first degree with one unknown 32
 first degree with two unknowns 32
 numerical with one unknown 35
 quadratic with one unknown 33
 using Newton-Raphson method 35
- Equilateral triangle 83
- Equivalent chip thickness (ECT) 992–994
- Equivalent pitch ratio 2000
- Equivalents, power and heat 2551
- Erg 2520
- Etching and etching fluids 1440–1441
- Euler's formulas for columns 261–263
- Evaluation length 701
- Evaporation, latent heat of 364
- Everdur copper-silicon alloy 565
- exbi 2533
- Expansion
 air 395–396
 chucking reamers 814
 coefficient of (linear)
 ceramics 379
 metals 368–370
 plastics 370
 fits 623
 hand reamers 817
 pipe 392
- Exponent 17
- External spline 2128, 2138
- External spur gear 1998
- Extrusion process 1347–1351
- Eye bolts and nuts 358–359
-
- ## F
- Fabric, bonding 2462–2463
- Face advance 2000
- Facing
 cutting time for 1044
 hard 1423–1427
- Factorial 97
- Factors
 of numbers 3–12
 prime number 3–12
- Factors of safety 199
 machine columns 265
 shafts 276, 283
 tubes subject to external pressure 274
 wire rope 339–340
- Fahrenheit and Celsius (Centigrade)
 temperatures 2514–2516
- Failure
 fatigue, modes of 199
 fatigue, springs 293–295
 of riveted joints 1458
 of springs 331
- Fatigue
 combined with creep 199
 contact 199
 corrosion 199
 cumulative damage 198
 failure, modes of 199
 influence of stress on 197–198
 low/high cycle 199
 properties 197
 S-N diagrams 197–198

- Fatigue
 springs 293–295
 surface 199
 thermal 199
- FCAW (flux-cored arc welding) 1371–1378
- Federal Specification
 gage blocks, inch and metric sizes 717
 GGG-G-15A 717
 GGG-G-15B 717
 GGG-G-15C 717–719
- Feed
 function, NC 1249–1250
 rate override, NC 1251
 rates
 centering tools 1095
 for drilling 868–870, 1012–1043, 1095
 for milling 1009–1012
 for turning 996–1009
 hollow mills 1095
- Feeds and speeds 597–599, 869, 978–1046, 1094–1095, 1103–1106
- Feet
 into meters 2541
 into millimeters 2538
 per minute into rpm 985–990, 1908–1909
- Fellows stub tooth gears 2010
- Ferrite 483
- Ferrous
 cast metals, speeds
 for drilling, reaming, and
 threading 1037–1038
 for milling 1021–1022
 for turning 1002–1003
 metals, properties of 473, 475–476
- Fiber, vulcanized, strength of 478
- Fiberglass sheet, properties 380
- Files 1430
 applications 1431–1432
 characteristics 1431
 classes 1431
 cross sections 1431–1432
 curved tooth 1431–1432
 machinists' 1431–1432
 mill or saw 1431–1432
 rasps 1432–1433
 rotary 1433–1434
 special purpose 1432
 steel for 854
 Swiss pattern 1432–1433
 teeth, cut of 1431
- Filler metals for brazing 1354–1359
- Fillet
 area 64
 center of gravity 138
- Fillet radius 2000
- Fillister head machine screws 1574
- Fine blanking 1312–1314
- Finishing of castings 1338
- Finishing, power brush 1435–1438
- Fire hose connection screw thread 1842–1845
- (continued)
- Fits
 and limits
 graphical representation 631–633
 tolerances designation 642–644
- cylindrical
 allowances and tolerances for 621–667
 ANSI Standard 627–657
 application of tolerances 622
 British Standard 657–667
 clearance 631–637
 definitions 621–644
 expansion 623
 forced 622, 640
 metric ISO, British 657–666
 metric radial, ball and roller bearing
 shaft and housing 2264
 preferred series 630
 running 631–635
 shrinkage 623–640
 transition 631, 633, 638
 pressure in assembling 622–623
- Fittings, pipe 2504–2512
 friction loss in 392
- Fixed (canned) cycles, NC 1258–1262
- Fixtures and jigs 941–951
- Flame
 cutting of metals 1428–1429
 hardening 417, 499–500
 spraying process 1351
- Flanged housing and pillow block bearings 2254
- Flank of tooth 2000
- Flat
 belts 2368–2369
 length formula 2369
 rivets for belts 1469
 rules for diameters and speeds of
 pulleys 2370–2371
 speed limitations 2368
 head cap screws 1599, 1603
 head machine screws 1569–1571, 1597–1598
 metal products, preferred
 thicknesses 2503
- plate
 circular 270
 square and rectangular 268–269
 strengths 268–270
 thin 148
 thrust bearings 2219–2225
 stayed surfaces in boiler work,
 strength 268
- Flat knurls 1213
- Flexible
 belts 2372, 2419
 couplings 2327
 manufacturing
 cell 1235
 module 1235
 systems, (FMS) 1234
- Floor and bench stand grinding 1192

- Flow of air in pipes 401
- Flow of water through nozzles 390
 - in pipes 388–389, 2509
- Fluid Maintenance 1114
 - biocide Treatment 1114
 - personal protective clothing 1114
 - system service 1114
- Fluidized bed furnace 479, 485
- Fluting cutters, reamers 808–810
- Fluxes
 - brazing 1354–1359
 - soldering 1352–1354
- Flywheels 173–184
 - bursting speed tests 182–183
 - calculations 173–184
 - centrifugal stresses in 178
 - classification 173
 - design, general procedure 174
 - energy of 173, 175
 - for presses, punches, shears 174–178
 - dimensions of 176
 - rim velocity 176
 - simplified calculations 177–178
 - weight of rim 177
 - pulley 173
 - spokes or arms of 184
 - stream engine 183–184
 - stresses 183
 - centrifugal in rim 178
 - combined bending and centrifugal 179
 - in rotating disks 183
 - types of 173
- Foot-pound
 - equivalents 2551
 - into British thermal units 2553
- Force 113, 195
 - acceleration resulting from 154–156
 - addition and subtraction of 118
 - algebraic composition and resolution of 121–129
 - algebraic solution
 - forces in same plane 122–124
 - forces not in same plane 126–129
 - and couples, work performed by 158
 - centrifugal 163–166
 - calculating 164
 - colinear 121
 - components of 118, 121
 - composition 118, 121
 - concurrent 121
 - components of single force 122
 - coplanar 121
 - couples of 120–121
 - differential pulley 135
 - for moving body on horizontal plane 135
 - friction 155
 - graphical representation 118–120
 - moment of 113, 120
 - noncoplanar 121
 - normal component 155
- Force
 - of blow 159–160
 - of gravity 155
 - on inclined plane 131
 - parallel 119
 - parallelogram of 119
 - polygon of 119
 - pound 114, 116
 - relationship to time 195
 - resolution of 118, 121
 - into rectangular components 126
 - resultant 118, 121
 - any number of concurrent forces 126
 - locating when components are known 129
 - non-intersecting forces 124–125
 - non-parallel, non-intersecting forces 128
 - parallel forces 123
 - parallel forces not in same plane 127
 - single force and couple 123
 - three or more concurrent forces 122
 - two concurrent forces 122
 - screw 135
 - systems 118–135
 - toggle joint 133
 - work performed by 158
- Forced fits, allowances 622, 640
- Forces and Couples 158
- Format
 - classification 1243–1245
 - detail, NC 1243–1245
 - word address, NC 1243–1245
- Formed cutters for internal gears 2047
- Forming tools 758–770
 - arrangement of 770
 - circular 760–770
 - diameters of 762–770
 - with top rake 762–764
 - feeds per revolution 770, 1094
 - speeds for 770, 1094
 - straight 758–761
 - with rake 758–761
- Formulas
 - algebraic 32
 - beam 207
 - calculating dimensions of milled bevel gears 2056
 - column
 - American Railway Engineering Association 261
 - Euler 261–262, 266–267
 - Johnson 262
 - Rankine or Gordon 261
 - straight-line 261
 - contour milling 1994
 - critical speeds 185–186
 - cutting speed 985
 - dimensions of milled bevel gears 2054
 - dimensions of SAE standard splines 2160
 - dimensions of standard spur gears 2004

- Formulas *(continued)*
- distance across bolt circle 687
 - internal gears 2048
 - linear motion, constant acceleration 152
 - pendulum 189
 - proportions of ANSI fine-pitch worms and wormgears 2065
 - rearrangement of 20–21
 - rotary motion, constant acceleration 153
 - tooth parts
 - former American Standard spur gear 2010
 - tooth parts, coarse pitch spur gear 2004
 - torque capacity of involute splines 2141
 - transposition 20–21
 - trigonometric 84–85
 - work and power 162
- Formulas for center of gravity 136
- Fourth powers of wire diameters 330
- Fractional threads 1912
- Fractions
- conjugate 14–15
 - continued 13–14
 - use of 15–16
 - decimal equivalents 2519
 - one inch into decimal inches 2519
 - one inch into millimeters 2538
- Free
- body diagram 155
 - cutting steels 409, 422
 - wheeling clutches 2332
- Freezing mixtures 367
- French
- metric screw threads 1780
 - thermal unit 2514
- Fretting damage 2145
- Friction 155, 190–192
- brakes 2337–2341
 - clutches 2328–2330
 - coefficients 191, 2330, 2338–2341
 - rolling resistance 191
 - static steel on various materials 191
 - effect on efficiency 191
 - laws of 190
 - rolling 191
 - wheels, power transmission 2339–2341
- Friction loss
- Elbow
- 45 degree 392
 - 90 degree 392
- in bearings 2280
- Standard tee
- Flow thru branch 392
 - Flow thru run 392
- Fuels
- average weights and volumes 371
 - weight 372
- Functions
- derivatives 34–35
 - involute 97–101
- Functions *(continued)*
- sevolute 97
 - trigonometric 83–85, 93
 - tables of 93–96
 - versed cosine 97
 - versed sine 97
- Functions of angles
- graphic illustration 92
- Furnaces, steel heat-treating 479, 484–485, 512–513
- Fusion, latent heat of 364
-
- ## G
- Gage block sets
- inch sizes 718
 - metric sizes 719
- Gage blocks 717
- Gage blocks, precision 717–719
- federal specifications for 717
 - inch sizes 718
 - metric sizes 719
- Gage tolerances 1883, 1885–1898
- Gagemakers tolerances 656–662
- Gages
- ANSI Unified thread
 - allowances and tolerances 1882–1884
 - angle tolerances 1882
 - classification 1877–1879
 - constants for computing dimensions 1883
 - diameter tolerances 1882
 - form 1879, 1883
 - formulas for limits 1883–1884
 - tolerances for plain gages 1883
 - tolerances on lead 1882
 - rods 2499
 - sheet metal 2501–2503
 - sheet zinc 2502
 - thickness and diameter sizes, galvanized sheet 2502
 - tubing 2499
 - usage, ANSI Standard recommended 656
 - wire 330, 2499–2500
 - zinc 2502
- Gaging methods and measuring instruments 669
- Gallons
- cylindrical tanks 58–59
 - in tank at given level 58–59
 - into cubic inches 2518
 - U.S. into liters 2545
- Galvanized, (welding) 1363
- Gas
- carburizing 417, 498
 - illuminating, specific gravity 371
 - metal arc welding (GMAW) 1363–1371
 - specific gravity 371
 - tungsten arc welding (GTAW) 1382–1387

- Gasket materials 1458–1459
 Gasoline, specific gravity 371
 G-code programming, NC 1243–1263
- Gear**
 blanks 2033–2034, 2052–2053
 crossed helical 1998
 helical 1998
 hypoid bevel 1998
 materials 2063, 2113–2120
 set, center distance 2010–2015
 shapers, root diameters of gears cut on 2011
 shaving 2011–2013
 size, checking 2094–2112
 specifications 2033–2036
 spur
 internal 1998
 spur, external 1998
 straight bevel 1998
 teeth
 induction hardening 502
 invention of 2121–2122
 tooth caliper, vernier 2020, 2108–2111
 trains, for fractional ratios 1913–1914
 worm 1998
 zerol bevel 1998
- Gear cutters, formed**
 involute 2017–2021, 2047, 2077–2079
 milling cutters for chain sprockets 792–793
 milling cutters for 14.5 deg. pressure angle gears 791
 milling cutters for 14.5 deg. pressure angles 791
 for miter and bevel gears 792
 number for bevel gears 2058–2060
- Gear cutting**
 block or multiple indexing 1990–1991
 excess depth to obtain backlash 2039–2040
 formed cutter selection 2021, 2058–2059, 2077–2079
 helical 2077–2078
 internal gears 2047
 methods for bevel 2053–2062
 shaving 2011–2013
- Gear ratio** 2000
- Gear teeth, comparative sizes and shape of** 2002
- Gear to Mesh with Enlarged Pinion** 2027
- Gear tooth stiffness constants** 2045
- Geared chucks, spindles for** 1203
- Gearing** 2048–2066, 2068, 2070, 2077, 2093–2125
 AGMA Standards 2037, 2041
 angular backlash 2036–2042
 backlash 2036–2042, 2103
 backlash, recommended 2038
 bevel 2050–2063
 bronze and brass castings for 2117
 calculating
- Gearing** (continued)
 helical gears 2068–2083
 replacement gear dimensions 2123–2125
 spur gears 2004–2033
 calculating dimensions of milled bevel gears 2056
 case hardening steels for 2113, 2117
 checking gear sizes 2094–2112
 checking pressures 2042
 chordal measurement of teeth 2015–2017, 2108–2111
 circular pitch system 2002
 compound 1912, 1978
 contact ratios 2024–2026
 design of bevel gear blanks 2052
 diametral and circular pitch 2003
 diametral pitch 1999, 2009
 diametral pitch system 2002
 drawing data 2033–2036
 efficiency 2000
 elasticity factor 2044–2045
 enlarged fine-pitch pinions 2023
 enlarged pinion and reduced dimensions to avoid interference 2019
 enlarged pinions meshing without backlash 2027
 epicyclic 2083–2087
 equivalent pitch radius 2000
 external spur gears 1998
 face advance 2000
 Fellows stub tooth 2010
 fillet radius 2000
 fillet stress 2000
 fine-pitch gears, blanks for 2033
 finishing gear milling cutters 2023
 flank of tooth 2000
 for given center distance and ratio 2010, 2012–2013
 forged and rolled
 alloy steels for 2113–2117
 carbon steels for 2113–2117
 formed cutters for milling bevel gears 2060
 geometrical factor 2046
 geometry factors 2045
 geometry of gear teeth 2002
 heat treatment to permit machining 2113–2114
 helical 2068–2083
 herringbone 2083
 highest point of single tooth contact (HPSTC) 2030–2031
 hypoid 2051
 idler gears 1977
 increasing pinion diameter to avoid undercut or interference 2022
 induction hardening 502
 information to be given on drawings 2043
 inspection 2042

- Gearing *(continued)*
- inspection of gears 2042
 - integral temperature criterion 2046
 - interference 2000
 - internal 2047–2048
 - internal diameter 2000
 - internal gear 2000
 - internal spur gears 1998, 2047
 - invention 2122
 - involute curve 2002
 - land 2000
 - lead 2000
 - length of action 2000
 - life factor 2044–2045
 - line of action 2000
 - load distribution 2044–2045
 - lowest point of single tooth contact (LPSTC) 2000, 2029
 - lubricant influence 2044
 - lubricant influence, roughness, and speed 2044
 - lubrication film factor 2045
 - material quality 2044
 - materials for 2063–2066, 2113–2120
 - measuring 2020, 2094–2112
 - methods of cutting internal gears 2047
 - metric
 - module gear cutters 2021
 - minimum demanded and actual safety factor 2045
 - minimum demanded and calculated safety factors 2045
 - minimum number of teeth to avoid undercutting 2027
 - module 2000
 - module system 2090–2093
 - mountings for bevel gears 2053
 - non-metallic 601–604, 2118–2122
 - outside diameter 2000
 - pin method of checking size 2094–2112
 - pitch diameter 2002
 - obtained with diametral pitch system 2003
 - pitch point 2000
 - plane of rotation 2001
 - planetary 2083–2087
 - pressure angle 2001, 2008
 - profile checker settings 2031
 - rack 2001
 - ratchet 2088–2089
 - relative sizes of internal gear and pinion 2047
 - replacement gear dimensions 2122–2125
 - roll angle 2001
 - root diameter 2001
 - selection of involute gear milling cutter 2021
 - size factor 2044
 - spur 2002–2033
 - standard normal diametral pitches 2043
 - steels for 2113–2117
- Gearing *(continued)*
- surface condition factor 2045
 - tangent plane 2001
 - tangential force 2044
 - terms used in specifications 2034
 - through hardening steels for 2113–2114
 - tip relief 2001
 - tooth face 2001
 - tooth proportions
 - fine-pitch involute spur and helical gears 2008
 - for enlarging fine-pitch pinions 2025–2026
 - tooth surface 2001
 - tooth thickness allowance for shaving 2013
 - tooth-to-tooth composite error 2042
 - total composite error 2042
 - total face width 2001
 - transverse load distribution factor 2045
 - transverse plane 2001
 - trochoid 2001
 - true involute form (TIF) 2030
 - true involute form diameter 2001, 2030
 - undercut 2001
 - undercut limit for hobbled involute gears 2030
 - welding factor 2045
 - work Hardening Factor 2045
 - work hardening factor 2044
 - working depth 2001
 - worm 2064–2066
 - worm gearing 2064
 - worm gears 1998
 - zone factor 2044–2045
- Gearing ratios
- change, for lathe 1912–1915
 - differential indexing 1976–1985
 - finding accurate 1915–1917
- Gears for given center distance and ratio 2012
- General purpose Acme threads 1792–1802
- data 1799
 - designation 1795
 - form 1793–1794, 1796
 - formulas for diameters 1796
 - limiting dimensions 1795, 1797, 1802
 - pitch diameter allowances 1800
 - thread form 1793–1794, 1796
- Geometric dimensioning and tolerancing 606, 610
- datum
 - feature 610
 - identifier 610
 - plane 611
 - reference frame 611
 - simulator 611
 - target 611
 - target areas 616
 - target lines 616
 - definitions 610

- Geometric dimensioning and (continued) Grams
 degrees of freedom 611
 dimension
 basic 612
 origin 612
 reference 612
 feature 612
 feature control frame 612
 free state 618
 least material condition (LMC) 612
 material removal required or
 prohibited 706
 maximum material condition
 (MMC) 613
 mean line 699
 modifiers 616
 position 613
 positional tolerance 616
 projected tolerance zone 616
 regardless of feature size (RFS) 613
 relation of surface roughness to
 tolerances 702
 size, actual 613
 size, feature of 613
 tangent plane 618
- Geometric symbols
 comparison of ANSI and ISO 609
- Geometrical
 constructions 51–55
 dimensioning and tolerancing 606, 610–
 611
 progression 43, 45
 propositions 46–50
 symbols for drawings 609–614
- Geometrical factor 2046
- Geometry factors 2045
- German standard
 gear tooth 2090
 screw threads, metric 1780
- Gib-head keys 2345–2367
- gibi 2533
- Gleason system
 bevel gears 2051–2054
 Zerol bevel gears 2050–2051
- Glue, pattern 1339–1340
- GMAW
 (gas metal arc welding) 1363–1371
 welding aluminum 1365–1366
 welding stainless steel 1364–1366
- GO and NOT GO gages 2147
- Gold
 plating 1447
- Goodman diagram 197–198
- Gordon formula for columns 261, 263
- Grade markings on bolts and nuts
 ASTM and SAE 1488–1489
 inch 1484–1488
 metric 1534, 1559–1560, 1586
- into ounces, avoirdupois 2547
 per cubic centimeter into pounds per cubic
 inch 2549
- Granite
 specific gravity and weight 370
 strength 478
- Graphical Resolution of Forces 118
- Graphical solution of force systems 118–120
- Graphitic materials for bearings 2242, 2245
- Gravel, weight 370
- Gravitational system of measurement 114
- Gravity 114
 acceleration due to 114
 center of, in various geometrical
 figures 136–142
 force of 155
 lubrication systems 2314–2316
 specific 370
 gases 371
 liquids 371
 plastics 380
 various substances 370–371
- Gray cast iron 1330
- Grease lubricants 2316–2318
- Greek symbols 2554
- Green sand molding 1336–1337
- Green wood, weight per cubic feet 377
- Grindability of tool steels 1151–1152
- Grinders
 safety for 1170
 spindles for portable 1207, 1209
- Grinding 1139–1193
 abrasive belt grinding 1193
 abrasives 1139–1141
 basic rules 1120
 carbide materials, diamond wheel 1135
 carbide tools 937–940
 cast iron 1132
 centerless 1183–1185
 centerless grinding troubles 1184–1185
 ceramic materials, diamond wheel 1135
 chip breakers 939–940
 cylindrical 1175–1183
 cylindrical grinding troubles 1179–1183
 diamond wheel 937–939, 1163–1169
 ECT 1121
 equivalent diameter (work conformity)
 factor 1125
 finishing 1128
 floor and bench stand 1192
 fluids 1107
 grindability groups 1128
 grinding cost, optimization and process
 planning 1138
 grinding cutting forces, torque and
 power 1126
 grinding data selection including wheel
 life 1127
 grinding rules and data selection 1120
 heat resistant alloys 1134

- Grinding *(continued)*
- internal centerless 1183
 - milling cutters 798–801
 - minimum cost conditions 1123
 - offhand grinding 1192
 - optimization 1138
 - optimum grinding data for roughing 1123
 - planing tools 729–730
 - plunge 1175
 - portable grinding 1192
 - procedure to determine data 1130
 - relative grindability 1129
 - rpm, various speeds and diameters 1174
 - screw threads 1923–1927
 - side feed, roughing and finishing 1128
 - silicon carbide wheels 937–939
 - spark-out time 1125
 - specific metal removal rates 1125
 - spindles for portable tools 1203
 - surface 1185–1192
 - surface finish, Ra 1124
 - surface grinding troubles 1190
 - swing-frame 1192
 - terms and definitions 1129
 - tool steels 1132–1134
 - tools
 - carbide 937–939
 - twist drills 934–937
 - traverse 1175
 - unhardened steels 1131
 - user calibration of
 - recommendations 1136
 - wheel life and grinding ratio 1120
 - wheel life relationships and optimum grinding data 1122
 - wheel life vs. cost 1138
 - wheel safety 1170–1174
 - handling 1170
 - inspection 1170
 - machine conditions 1170
 - mounting 1170
 - portable grinders 1172
 - safe operating speeds 1171–1174
 - speed conversion table 1174
 - speeds, maximum 1173
 - storage 1170
 - wheel safety grades 1140
 - wheels 1139–1162, 1170–1174
 - abrasive materials for 1139–1140
 - angles for eccentric type radial relief
 - angles on milling cutters 804
 - bond properties 1140
 - CBN 1140, 1157, 1166
 - cubic boron nitride 1139, 1157
 - diamond 754–755
 - truing of 1158–1162
 - dressing and truing of 1158–1162
 - faces, shapes of 1150
 - grades 1140
- Grinding *(continued)*
- markings, standard 1141–1142
 - mounted wheels and points 1205–1206
 - metric 1204
 - mounting and safety 1170
 - selection of 1142–1162
 - shapes and sizes, standard 1142–1150
 - metric 1148–1149
 - structure 1140–1141
 - truing
 - diamond feeds 1161
 - diamond sizes 1161
 - dressing of 1158–1162
 - wheel markings 1141
 - work speed and depth of cut selection 1121
 - work speeds in rough and finish grinding 1125
- Grooved pins 1656, 1658–1662
- Grooving and oil feeding of bearings 2204–2205
- Ground thread tap, designations 898
- GTAW (gas tungsten arc welding) 1382–1387
- Guide bearings 2236–2237
- Guldinus or Pappus rules 56
- Gutta percha, turning 1045
- G-word, NC 1245–1249
- Gyration radius of 146
 - bar, small diameter 147
 - circular disk, thin 147
 - circular ring, thin flat 148
 - cone 149
 - cone, frustum 150
 - cylinder 148
 - cylinder, hollow 149
 - ellipsoid 150
 - flat plate, thin 148
 - hollow cylinder, thin 148
 - hollow sphere 150
 - paraboloid 150
 - parallelepiped 149
 - parallelogram 148
 - prism, rectangular 149
 - ring 147
 - sphere 150
 - sphere, hollow 150
 - spherical shell, thin 150
 - thin flat plate 148
-
- ## H
- H- and L-limits 879–880, 896–897
- Hand
 - expansion reamers 817
 - of flute helix 774
 - of milling cutter 773
 - reamers 807–817
- Hard facing 1423–1427
- Hard rubber, machining 1119

- Hardenability 415–416
 test methods 416
 Hardening steel 479, 485–486, 491–492
 flame 499
 induction 500
 laser and electron beam 503
 Hardmetals 747–757
 carbonitride based 749–750
 coated 750–752
 ISO classifications 753
 tooling for wood and nonmetals 757
 Hardness 415
 aluminum alloys 550–555
 bearings 2199–2200
 ceramics 379
 heat-treated steels 430–436
 magnesium alloys 560
 O-ring 2483–2484
 plastics 380
 powdered metal alloys 383
 relation to tensile strength 473, 475, 521, 524
 steel
 carbon and alloy 432–436
 castings 1333
 cold drawn, rounds, square, and hexagons 431
 stainless 439
 tool steels 458, 460, 462, 464, 468, 471
 surface (case) 415–416
 testing 516–524
 Brinell 516–524
 conversion errors, causes 521
 conversion tables 520–524
 correction for curvature 2304
 diamond pyramid 518–520
 durometer 521, 2485, 2487
 Hultgren ball 517–521
 Keep's test 519
 Knoop hardness numbers 518–519
 Mohs hardness scale 521, 524
 monotron 518–519
 relationship between hardness and tensile strength 473, 475, 521, 524
 Rockwell 520–524
 scleroscope 518–521
 Turner's sclerometer 521, 524
 Vickers 518–521
 H-bands (hardenability) 416
 Heat
 absolute temperature and zero 2514
 coefficients of radiation 367
 coefficients of transmission 367
 Fahrenheit-Celsius conversion 2514–2516
 freezing mixtures 367
 ignition temperatures 367
 latent 364
 loss from uncovered steam pipes 365–366
 mechanical equivalent 2514
 power equivalents 2551
 quantity measurement 2514
 radiating capacity of bearings 2204
 radiation coefficient 367
 scales 2514
 specific 364
 temperature scales 2514–2516
 thermal energy 2514
 Heat radiating capacity of bearings 2206
 Heat treatment 479–483
 high-speed steels
 annealing 510–511
 furnaces for 512–513
 hardening 508–514
 steel 414–415, 479–517
 annealing 414, 479, 483, 495–497
 annealing temperatures 496–497, 503–505
 baths
 heating 487
 quenching 488–492
 tempering 492–495
 carbonitriding 417
 carburizing 417, 498
 temperatures 504–505
 case hardening 497–499
 case hardening steels 504–505
 cleaning work after case hardening 499
 colors for tempering 495
 cooling
 low-temperature, to stabilize dimensions 514–517
 subzero, to improve properties 516–517
 cyanide hardening 498
 decalescence point 479, 485
 defects in hardening 488
 double tempering 494
 flame hardening 499
 furnaces 479, 484–485
 hardenability test, Jominy 416
 hardening temperatures 479, 485–486, 504–505
 hardening, defects in 488
 heat treatments for SAE steels 503–505
 induction hardening 500–503
 interrupted quenching 490–492
 lead bath temperatures 487, 494
 liquid baths 487
 nitriding 417, 513
 normalizing 414, 496–497
 normalizing temperatures 503–505
 oil hardening steels 503–505
 pack-hardening 498
 protective coatings for molybdenum steels 512
 quenching 414, 481–485, 488–492, 510
 recalescence point 479, 485
 salt baths 487
 scale formation 488
 (*continued*)

- Heat treatment *(continued)*
 spheroidizing 496–497
 stabilizing dimensions 515
 strength and hardness of AISI steels 432–436
 stress relieving 415
 subzero treatments 516–517
 surface hardening 503
 tanks for quenching baths 490
 tempering 416, 482, 493–495
 time aging 515
 water quenching 489
- Hectares into acres 2541, 2544
- Helical
 gearing
 enlarged fine-pitch pinions 2077–2080
 fine pitch 2077–2079
 formed cutter number 2077–2079
 hobbing 2080
 replacement gear dimensions 2122–2125
 shafts
 at any angle 2069–2078
 at right angles 2072–2074
 parallel 2070
 interpolation, NC 1255
 milling 2077–2079
 change gears 1931–1948
 wire screw thread inserts 1635
- Helical gearing 1998, 2068–2083
 center distance for enlarged 2080
 change gears for hobbing 2080–2083
 checking gear size 2094, 2103–2109
 checking size by pin method 2103
 chordal thickness and addendum 2015–2017
 data on drawings 2033–2036
 direction of thrust 2068
 enlarged fine-pitch pinions 2080
 fine pitch 2006–2008
 helix angles 2069
 herringbone type 2083
 hobbing 2081–2083
 normal tooth thickness 2006, 2008
 pin method of checking size 2094–2109
 pitch of cutter 2069
 problems 2083
 spur gear replacement by helical gears 2122
 tooth number for selected formed cutter 2077–2079
 tooth proportions 2008
- Helical gears 1998
- Helical overlap 2000
- Helix 1933
 angle 2000
 angle factor 2045
 angles, screw threads 1740–1749
 constructing 55
 lead for given angle 1943–1948
 measurement of angle 1933
- Helix angle 2000
- Herringbone gearing 2083
- Hertz stress, 2000
- Hexagon
 area 62
 distance across corners 82
- Highest point of single tooth contact (HPSTC) 2000, 2030
- High-speed steels 457–460, 979
 as cutting tool materials 979
 cobalt 856–857
 cobaltchrom 508
 heat treatment 508–514
 annealing 510–511
 equipment 513
 forging 513
 hardening
 molybdenum 510–512
 temperatures 509–510
 tungsten 508–510
 nitriding 512–513
 preheating tungsten 508
 quenching
 molybdenum 512
 tungsten 509–510
 subzero treatment 514–517
 tempering
 molybdenum 512
 tungsten 510–511
 time for through hardening 509
 molybdenum 457–458, 464, 510–513
 tungsten 458, 460, 462, 508–511
- High-strength, low-alloy (HSLA) steels 409–410, 440–443
- Hob tip radius, maximum 2030–2033
- Hobbing helical gears, change gears 2080–2083
- Hobs
 change gears for relieving 1916–1917
 roller chain sprocket 2437, 2439
- Hobs, worm gear 2064
- Hoisting chain and wire rope 333–360
- Holder for NC, insert 732–738, 1281–1284
- Hold-on or dolly bars for riveting 1467
- Holes
 accuracy of drilled 856–858
 coordinate dimension factors for jig boring 959–970
 difficulties in reaming 812
 for riveted joints 1457
 for tapping 1889–1907
 in glass, drilling 1034
 sizes for self-tapping screws 1628–1635
 spacing of, on a jig borer 959–970
- Hollow
 cylinder 149
 mills, feeds and speeds 1095
 sphere 150
- Honing process 1196–1199
 abrasive stones for 1198
 adjustments 1198–1199

- Honing process *(continued)*
 carbide tools 939–940
 rotative speeds in 1196–1198
 stock removal, rate of 1197
 tolerances 1199
- Hooks, dimensions of crane 357
- Horsepower 113
 air compression 396–400
 chain transmission 2431–2444
 converted into kilowatts 2551, 2553
 disk clutches 2329
 drilling different materials 1051–1053
 dynamometer test 2338–2341
 electric motor ratings 2446
 equivalents 2551, 2553
 formulas 162
 friction wheels 2339–2341
 gearing 2118–2121
 helical gearing 2068–2083
 machining 1046–1051
 nonmetallic gears 2118–2122
 planing and shaping 1047–1049
 roller chains 2431–2444
 set-screw transmitting capacity 1619
 shafting 275–277
 spade drilling 870, 1051–1054
 spur gears 2118–2122
 torque equivalent 275–277
 V-belt drives 2372–2419
 water at a given head 389
- Horsepower-hour equivalents 2551
- Hose coupling screw threads 1841–1845
- Hot short alloy 1337–1338
- Hot-working, tool steels for 452–454, 456
- HSLA steels 409–410, 440–443
- Hydrant screw thread 1842–1845
- Hydrochloric acid, specific gravity 371
- Hydrometer, Baumé's, and specific gravity 371
- Hydrostatic bearings 2195–2196
- Hyperbola area 65
 constructing 55
- Hypocycloidal curves, areas 58
- Hypoid bevel gears 1998
- Hypoid gears 2049, 2051
 applications of 2051
- Hypotenuse 83
- Hysteresis 290
-
- I**
- I-beam
 aluminum 2498
 standard structural steel 2493
 structural
 moment of inertia 2489–2493
 section modulus 2489–2493
 steel 2489
 weight per foot 2489–2493
- Ice, specific gravity and weight 370
- Identities, trigonometric 84–85
- Idler gears 1977
- IGES (initial graphics exchange specification) 1294–1296
- Ignition temperature 368
- Impact force of 159
- Impact strength, Izod
 carbon and alloy steels 432–433
 plastics 380
- Impulse 160–162
- Impulse and momentum, angular 161
- Inch
 decimals of, into millimeters 2525–2535
 fractional, into millimeters 2538
 into centimeter and millimeter 2533
 millimeters into decimals of 2536
- Inclined plane 130, 155
 force for moving body on 130
 motion on 155
- Inclined plane, forces on 131
- Inconel metals 562–563
- Incremental programming, NC 1248
- Indexable
 carbide inserts 729–732
 insert holders, NC 732–738, 1281–1284
 inserts, single-point tools 729–732
- Indexing
 angular 1956–1976
 block or multiple 1990–1991
 compound 1947–1948, 1950–1956
 differential 1976–1985
 head worm wheel with 64 teeth 1992
 milling machine 1947–1993
 movements 1951–1975, 1979–1989,
 1992–1993
 rack cutting on milling machine 1993
 reamer teeth for irregular spacing 807–
 808
 simple 1947–1948, 1979–1985
- Indexing head, angular position for
 milling cams 2186–2188
 milling clutches 2334–2336
 milling end mills and angular
 cutters 796–799
- Induction hardening 417–418, 500–503
 equipment 500–501
 gear teeth 502–503
 quenching 502
 steels for 501
- Industrial assets, investments in 27–31
- Inertia 113
 moment of 217
 polar 277–278
- Initial graphics exchange specification (IGES), NC 1294–1296
- Inserts
 hardmetal materials 747–757
 holders for NC 732–738, 1281–1284
 indexable 730–738, 1281–1284
 radius compensation, NC 1281–1284

- Inserts *(continued)*
 screw thread 1635
 self-tapping screw 1635
 superhard materials 754–757
 Inspection methods 669–719
 Instrument maker's thread system 1846
 Instrumentation
 surface texture measurement 704
 Interest
 compound 24
 finding unknown rate 26
 formulas 28
 nominal vs. effective 25
 simple 24
 Interference 2000
 Interference fit threads 1786–1791
 British Standard 1551, 1562
 coarse threads 1789–1790
 designation symbols 1787
 dimensions 1788
 engagement lengths 1789
 interferences 1787, 1789
 lubrication 1789
 materials for 1789
 profile 1786
 spur gearing 2019–2022
 torques for 1791
 Interferometer 1219
 Internal diameter 2000
 Internal gear 2000
 Internal spur
 gear 1998
 gearing 2047–2048
 International System (SI) units 2520–2524
 Interpolation
 circular, NC 1254–1255
 helical and parabolic, NC 1255
 linear, NC 1253
 Interrupted quenching 490–492
 Inverse
 and direct proportions combined 23
 ratio or reciprocal 21
 Investment
 annual cost method 27–29
 casting 1344–1346
 in industrial assets 27–31
 present worth method 29–30
 prospective rate of return method 30–31
 Investment casting alloy
 aluminium 381–382
 bronge 381–382
 carbon and low alloy steel 381–382
 cobalt 381–382
 copper 381–382
 stainless steel 381–382
 Involute 2000
 constructing 55
 curve properties 2004, 2006
 curve, properties of 2002
 functions 97–101
(continued)
 Involute *(continued)*
 gear cutters, formed type 2021, 2047,
 2054, 2056–2060, 2077–2079
 serrations 2126
 splines 2126–2150
 ANSI Standard, inch dimensions 2126–
 2147
 basic dimension formulas 2131, 2151
 basic rack profile 2155
 chamfers and fillets 2135, 2155
 combinations of types 2138
 compressive stresses, allowable 2145
 crowning for misalignment 2145
 dimensions, effective and actual 2135–
 2151
 drawing data 2139
 fillets and chamfers 2135, 2155
 fits, types of 2133, 2148–2150
 fretting damage 2145
 inspection methods 2146
 interchangeability 2138
 metric module 2148–2155
 pin measurement of 2147
 reference dimensions 2138, 2155
 shear stresses allowable 2142
 sizes and lengths, estimating 2140,
 2143
 space width limits 2136–2138, 2151–
 2153
 symbols for 2129, 2139, 2148–2150
 tensile stresses, allowable 2145
 terms 2126–2129, 2148–2153
 tolerances 2133–2134, 2151–2153
 tooth numbers 2129, 2133
 tooth proportions 2129–2133, 2148–
 2155
 tooth thickness limits 2136, 2151–2153
 torque capacity formulas 2140–2145
 variations
 effect of 2135, 2153
 types of 2127, 2135, 2153
 Involute splines 2000, 2126, 2129
 American National Standard 2126
 basic dimension 2133
 classes of tolerances 2133
 diametral pitch 2128
 effect of spline variations 2136
 effective
 clearance 2128
 space width 2128
 tooth thickness 2128
 variation 2128, 2153
 effective and actual dimensions 2136–
 2137, 2147
 fillet 2128
 fillet root splines 2128, 2135
 fillets and chamfers 2135
 fit Classes 2152
 flat root splines 2128, 2135
 form circle 2129
 form clearance 2129

- | Involute splines | <i>(continued)</i> | ISO Standard | <i>(continued)</i> |
|-------------------------------------|--------------------|-----------------------------------|-------------------------|
| form diameter | 2129 | ISO DR 911 | 1559 |
| formulas for 2-pin measurement | 2148 | ISO DR 947 | 1559 |
| inspection | | ISO DR 950 | 1559 |
| types of gages | 2147 | ISO DR 952 | 1559 |
| inspection methods | 2146 | ISO DR 987 | 1559 |
| inspection with gages | 2147 | ISO Recommendation R273 | 1904 |
| interchangeability | 2138 | ISO R272 | 1559 |
| internal splines | 2129, 2138 | ISO R288 | 1559 |
| lead variations | 2129, 2136 | ISO R53 | 2043 |
| length of engagement | 2129 | ISO R54 | 2043 |
| length of splines | 2141 | ISO R773 | 2354 |
| load distribution factors | 2142 | ISO R861 | 1522 |
| machining tolerance | 2129, 2154 | ISO TC/600 | 2045 |
| major circle | 2129 | ISO 261 | 1777 |
| major diameter | 2129 | ISO 4032 | 1542 |
| major diameter fit | 2133 | ISO 4033 | 1542 |
| manufacturing | 2162 | ISO 4035 | 1542 |
| maximum | | ISO 4156 | 2148 |
| actual space width | 2137 | ISO 4161 | 1542 |
| effective space width | 2138 | ISO 4762 | 1522 |
| effective tooth thickness | 2137 | ISO 68 | 1755–1756, 1760 |
| maximum actual tooth thickness | 2137 | ISO 6983/1 | 1248 |
| minimum | | ISO 6983/2 | 1248 |
| actual space width | 2137 | ISO 6983/3 | 1248 |
| effective space width | 2137 | ISO 887 | 1549 |
| effective tooth thickness | 2138 | ISO 898/I | property class 8.8 1776 |
| minimum actual tooth thickness | 2137 | ISO 965 | 1755, 1766, 1768 |
| minor circle | 2129 | ISO 965/1 | 1762–1764, 1767–1768 |
| minor diameter | 2129 | ISO/TC2/WG6/N47 | 1549 |
| parallelism variation | 2129 | metric | |
| pitch | 2129 | British Standard taps | 902–903 |
| pitch circle | 2129 | grade markings on bolts | 1559–1560 |
| pitch diameter | 2129 | hexagon bolts, screws and nuts | 1555–1560 |
| pitch point | 2129 | limits and fits, British Standard | 657–666 |
| pressure angle | 2129 | thread | 1825–1834 |
| shear stress | | surface texture symbology | 713 |
| at the pitch diameter of teeth | 2144 | tapping drills for | 1901–1903 |
| under roots of external teeth | 2144 | washers, compared with ANSI | 1549 |
| side fit | 2133 | ISO surface finish | 711 |
| space width and tooth thickness | | ISO surface parameter symbols | 715 |
| limits | 2137 | Isosceles triangle | 83 |
| stub pitch | 2129 | Isothermal | |
| tooth numbers | 2133 | expansion, compression of air | 396 |
| tooth proportions | 2130 | quenching | 492 |
| tooth thickness modification | 2153 | Izod impact strength | |
| total index variation | 2129 | carbon and alloy steels | 432–433 |
| total tolerance | 2129 | plastics | 380 |
| types and classes of fits | 2133 | | |
| variation allowance | 2129, 2136 | | |
| wear life factors, flexible splines | 2142 | | |
| Iron- and copper-base sintered | | | |
| bearings | 2243–2245 | | |
| Iron castings | 1328–1331 | | |
| ISO Standard | | | |
| drawing symbols, compared with | | | |
| ANSI | 609 | Jacobs tapers | 919 |
| geometric dimensioning and | | Jam nuts, standard | 1493, 1499–1500 |
| tolerancing | 606 | metric | 1548 |
| | | Japanese Industrial Standard | |
| | | JIS B 1083 | 1482 |
| | | Jarno taper | 906, 917 |

J

- Jig
 boring 951–954
 hole coordinate dimension factors
 for 959–970
 transfer of tolerances in 952–954
 bushings 941–951
 definitions 941
 designation system for 942, 951
 locking mechanisms for 950
 materials 941
 plate thicknesses 941
 Jigs and fixtures 941–951
 definitions 951
 Jobbers reamers 818
 drills 829–835
 Johnson, J. B., column formula 262, 266–
 267
 Joints
 plastics pipe 2510–2512
 riveted 1457–1463
 toggle 133
 universal 2327
 Jominy hardenability tests 416
 Journal or sleeve bearings 2204–2219
-

K

- Keep's hardness test 519
 Kelvin, degrees 2514
 Kerosene, specific gravity 371
 Key and spline sizes and lengths 2140
 Keying bearings 2197–2198
 Keys and keyseats 2342
 ANSI Standard 2342–2354
 British Standard 2354–2367
 chamfered keys 2347, 2353
 cotters 2351, 2354
 depths for milling keyseats 2342–2344,
 2353
 effect on shaft strength 283
 estimating key sizes 2140
 filleted keyseats 2347, 2353
 fitting 2346
 gib-head keys 2345, 2359, 2363–2367
 key fitting 2346
 keyseat milling cutters, Woodruff 795
 keyseats, depth of 2343–2344, 2346,
 2353
 keyway stresses, nonmetallic
 gears 2121–2122
 metric 2354–2360
 milling cutters and arbors 794
 parallel 2342–2353
 plain 2345, 2363–2367
 setscrews for keys 2347
 size vs. shaft diameter 2342–2346, 2353–
 2357, 2361–2364
 strength considerations for shafts 283
 taper 2345–2354, 2359–2364
 tolerances 2345, 2347–2349, 2353

- Keys and keyseats (*continued*)
 transmission chain 2426
 Woodruff 2348–2365
 kibi 2533
 Kilogram calorie 2514
 Kilograms
 into pounds 2546
 per cubic meter into pounds per cubic
 foot 2549
 per square centimeter into pounds per
 square inch 2548
 per square meter into pounds per square
 foot 2548
 per square meter into pounds per square
 inch 2548
 Kilometers into miles 2541
 Kilopascals into pounds per square inch 2548
 Kilowatt
 into horsepower 2553
 power required for machining 1046
 Kilowatt-hour equivalents 2551
 Kinematics 113
 Kinetic energy 157–159
 Kinetics 113
 Kingsbury thrust bearing 2218–2219, 2232–
 2235
 Kips 1333–1334
 K-Monel, machining 1118
 Knee tools, speeds and feeds 1095
 Knoop hardness numbers 518–519
 Knuckle joints, proportions 2329
 Knurls and knurling 1211–1215
 ANSI 1211–1215
 automatic screw machines 1094–1099
 concave 1215
 diametral pitch knurls 1211–1215
 formulas 1213
 lathe knurls 1211
 revolutions required for top
 knurling 1094
 sizes, preferred 1211
 speeds and feeds 1095
 straight knurls 1213–1215
 tracking correction 1211
 work diameter tolerances 1214–1215
 Ksi 1333–1334
-

L

- Lag screws and threads 1497–1498
 metric 1525
 Lame's formula for internal pressure 271
 Laminated phenolic bearings 2242, 2245
 Land 2000
 Land, gear tooth
 drill 827
 Lapping
 abrasives 1202
 carbide tools 939–940
 grading abrasives for 1200

- Lapping *(continued)*
 grading diamond dust for 1201
 lubricants 1202
 pressures 1202
 tests 1203
 wet and dry 1202
- Laps 1199–1203
 charging laps 1200
 cutting properties 1201
 flat surfaces 1199
 materials for 1199
 rotary diamond 1200
 wear 1202
- Laser and electron beam surface hardening 503
- Lasers 1410–1422
 beam focusing 1410–1411
 beams 1410
 cladding 1421–1422
 cutting metal with 1414–1415
 cut edge roughness 1415–1416
 cutting speeds 1418–1419
 heat-affected zone 1416–1417
 kerf widths 1415–1416
 cutting nonmetals 1416–1417
 drilling 1420–1422
 heat treatment 1421–1422
 light 1410
 marking 1422
 safety 1413
 types of industrial 1411–1412
 welding 1418–1421
 joint design 1419–1420
 processing gas 1420–1421
 theory 1418–1419
 welding rates 1419–1421
- Latent heat 364
- Lathe
 arbors 858
 centers, steel for 456
 change gears 1912–1916
 fixtures, balancing 171–172
 screw constant 1912
 types of motors for driving 2449
- Law of
 cosines 84
 sines 84
- Lead 2000
 angle of cutting tools 723–730
 tool inserts 1281
 angle of screw thread
 finding 1863–1864, 1933
 tables for 1740–1749, 1784, 1799,
 1807, 1815, 1872–1874
 angle of screw thread tables for 1815
 of helix for given angles 1943–1948
 of helix known, find change gears for
 milling 1931–1943
 of helix, change gears and angles for
 milling 1863–1864, 1946–1947
 of milling machine 1931
- Lead *(continued)*
 of screw thread 1859–1864, 1933
- Lead bath
 alloys, temperatures 494
 for heating steel 487
 tempering 494
- Lead, melting point 494
 heat transmission coefficient 367
 solder 1353
 specific gravity 370
 strength 477
 tempering in 494
- Lead-base alloys, die casting 1343
- Leaded-bronze bearings 2238–2241
- Least material condition (LMC) 612
- Length
 differences due to temperature 668
 engagement of screw thread 1489–1491
 measures 2517, 2522
 of rivets for forming heads 1463
 standard 2522
- Length of action 2000
- Letter
 addresses, NC 1243
 symbols for mechanics 115
- Lever 132
- Life adjustment factors for rolling element bearings 2296–2297
- Life factor 2045
- Light
 duty V-belts 2390–2397
 laser 1410
 metals
 speeds for drilling, reaming, and
 threading 1039
 speeds for milling 1013–1014
 speeds for turning 1007–1008
 wave interference bands, measuring
 surface variations with 695–696
- Limestone
 cutting speed for 1045
 specific gravity and weight 370
 strength 478
- Limit
 elastic 196
 endurance 197
 proportional 195–196
- Limits and fits
 ANSI Standard preferred metric 632,
 642–657
 British Standard (metric ISO) for holes
 and shafts 658–666
 cylindrical fits, ANSI Standard 627–642
 definitions 632, 642, 644
 gages, plain 622, 656
 gages, thread 1877–1884
 graphical representation 632–633
 indicating on drawings 621–622
 metric 632, 642–651, 657
 screw thread gages 1877–1884
 symbols 642–644

- Limits and fits *(continued)*
- tolerance designation 642
 - Woodruff keys 2348–2349
- Limits, upper and lower (UL and LL) 613
- Line
- conventions and drawings 606
 - geometry of 48
- Line conventions and drawings 606
- Line of action 2000
- Linear
- coefficient of expansion 367
 - ceramics 379
 - metals 368–371
 - pipe material
 - copper 392
 - FRP 392
 - PP & PVDF 392
 - PVC 392
 - steel 392
 - plastics 380
 - deflection of shafting 280
 - interpolation, NC 1253
- Lines, points, circles (APT) NC 1265–1270
- Liquid
- baths, heating steel in 487
 - carburizing 417
 - depth to volume conversion 58–59
 - measure 2518, 2523
 - specific gravity 370–371
- Liters
- into cubic feet 2545
 - into U.S. gallons 2545
- Load
- rating, static, bearings 2297–2301
 - ratings and fatigue life, bearings 2285–2303
- Load distribution 2044–2045
- Lobing 694–696
- Lock wire procedure 1491
- Locknut threads, pipe 1848, 1851–1852
- Locknuts, ball and roller bearing 2277
- shafts for 2278–2279
- Lockwashers
- ANSI Standard 1515–1519
 - ball and roller bearing 2276
 - British Standard, metric
 - plain 1565–1566
 - spring 1563–1565
 - spring type 1516–1517
 - tooth type 1515, 1518–1519
- Logarithms 102–111
- avoiding negative characteristic 104
 - characteristic 102
 - common 102, 108–109
 - division by 105
 - extracting roots by 107
 - mantissa 102
 - multiplication by 104
 - natural 102, 104, 110–111
- Logarithms *(continued)*
- obtaining powers by 106
 - tables 108–111
 - common 108–109
 - natural 110–111
 - using calculator to find 104
 - Long angle lathe file 1433
 - Low pressure casting 1337–1338
 - Löwenherz thread 1825
 - Lubricants 2311–2320
 - application of oils 2312–2314
 - bearings 2202–2205, 2318–2320
 - cutting 1106, 1108–1111
 - density 2311–2313
 - dynamic viscosity coefficient 2324
 - electric motors 2458–2459
 - grease 2315–2318
 - oil mist 2315–2316
 - oils 2311–2320
 - pressure-viscosity coefficient 2324
 - presswork 1302
 - solid films 2318
 - specific gravity 2312–2313
 - temperature vs. viscosity 2202–2203, 2312–2313
 - viscosity 2311–2313, 2319
 - Lubrication 2201–2205, 2312–2320
 - aerodynamic 2321
 - analysis, journal bearings 2207–2219
 - application of oils 2315–2318
 - ball and roller bearings 2318–2320
 - centralized systems 2313–2315
 - chain 2443
 - density 2311–2313
 - elastohydrodynamic 2321
 - films 2318
 - gravity systems 2314–2316
 - grease 2315–2317
 - motors 2458–2459
 - oil mist 2315–2316
 - oils 2315–2318
 - plain bearings 2201–2204
 - relubrication with grease 2317–2318
 - roller chain 2443
 - selection for bearings 2202–2205
 - solid films 2318
 - specific gravity 2312–2313
 - systems 2313–2316
 - viscosity 2202–2203, 2311–2320
 - viscosity-pressure relationship 2324
 - wicks and wick feeds 2314–2316
 - Lubrication film factor 2045
-
- ## M
- Machinability of wood 377–378
- Machine
- accuracy, effect of on part
 - tolerances 1220
 - countersinks 813

- Machine *(continued)*
- elements, subjected to compressive loads 262
 - platens, NC ??–1285
- Machine screw taps 872, 883–886
- metric (ISO) 883–893
- Machine screws
- ANSI Standard 1568–1585
 - binding head 1576
 - British
 - metric 1586–1598
 - Unified 1595–1597
 - British Metric 1598
 - British Unified 1597
 - BSW and BSF 1586, 1591, 1595–1598
 - cheese head 1593
 - clearance holes, metric 1585
 - cross recesses 1577
 - fillister head 1574
 - flange head 1583
 - flat head 1569–1571, 1579
 - header points for 1574–1575, 1582
 - hexagon head 1572, 1583
 - hexagon washer head 1571
 - metric, ANSI standard 1577–1585
 - nuts for 1568
 - oval head 1574–1576, 1580
 - pan head 1573, 1581, 1591–1592
 - recommended nominal screw lengths, metric 1585
 - round head 1577
 - tap and clearance drills 1889–1903
 - tap drill sizes 1900
 - taps for 872, 883–893
 - truss head 1572
 - washerhead 1571
 - washers for 1512–1517, 1565–1567
- Machine tool
- lathe, change gears for fractional ratios 1913–1914
 - motor types 2456–2457
- Machinery noise 1297
- Machining
- aluminum 1116
 - bearings 2199–2201
 - copper alloys 1119
 - hard rubber 1119
 - magnesium 1117–1118
 - Monel and nickel alloys 1118–1119
 - nonferrous metals 1116–1119
 - power constants 1046–1047
 - power factors
 - chisel-edge 1053
 - drill diameters 1055
 - feeds 1047, 1054
 - machine tool efficiency 1049
 - metal removal rates 1050
 - tool wear 1048
 - work materials 1053
 - power, estimating 1046–1054
 - zinc alloy die castings 1118
- Machining processes
- ANSI Standard tolerance grade relationships 630, 657
 - effect on surface roughness 702–703
- Macro, NC 1257–1258
- Magnesium alloys 557–560, 1343
- applications 557
 - compositions 559
 - cutting fluids for 1111, 1117–1118
 - designations 557
 - die casting 1342
 - machining 1117–1118
 - properties 560
 - soldering of 1352–1354
 - strength 477, 560
- Magnesium, coating 1446
- Magnetic clutches 2331–2332
- Malleable
- cast iron 1331
 - iron castings 1330–1331
 - Iron Research Institute 1340
 - strength 1330–1331
- Malleablizing 481
- Manganese steel 411–412
- Manganese, in welding electrodes 1362–1363
- Manganese-bronze castings 529–530
- Manila rope, strength 354, 360
- Mantissa, logarithm 102
- Manual data input, NC 1240
- Manufacturers' standard gage for sheet steel 2501
- Manufacturing cell
- flexible, NC 1235
- Manufacturing cell, flexible, NC
- module 1235
 - system 1235
- Marble
- specific gravity and weight 370
 - turning 1045
- Martempering 492
- Martensite 484, 514
- Masonry, weight per cubic foot 370
- Mass 113–114, 116
- Material quality 2044
- Materials
- mechanical properties of 195–196
 - Materials for worm gearing 2067
- Mathematical signs and abbreviations 2
- Matter 113
- Maximum material condition (MMC) 613
- MBEC bearing tolerances 2240
- M-codes (M-words), NC 1249
- Mean positional deviation 1216–1219
- Mean proportional 22
- Measurement of backlash 2040
- Measurement over pins 687
- Measurements with pins 2147
- Measures and weights 2536–2553
- Measuring
- angles with sine-bar 673–682

- Measuring**
 compound angles 688–690
 dovetail slides 682–683
 gear size 2094–2112
 instruments and gaging methods 669–719
 radius or arc, over rolls 690
 surface texture 697–705
 tapers 682–686
 threads
 Acme 1870–1875
 American standard 1866–1867
 buttress 1875–1877
 tapered 1872, 1875–1876
 using micrometer 1859–1861
 using screw thread gage 1876–1884
 using three-wire method 1860–1877
 Whitworth 1868
 V-shaped groove, over pins 690
 with light-wave interference bands 695–696
 with micrometer 670–672, 1859–1861
 with vernier 669–670
 mebi 2533
Mechanical equivalent of heat 2514
Mechanical properties
 aluminum 550, 556–557
 bolts, inch sizes 1488–1489
 bolts, metric sizes 1520, 1559–1560
 ceramics 379
 copper 565
 magnesium 557–560
 nickel 561–563
 plastics 380
 powdered metal alloys 383
 spring wire 385
 steel 452–454, 473, 476
 strengths 473–478
 titanium 561, 564
 various materials 195–196
 wood 375–376
Mechanics of materials 113
 acceleration 151, 153–154
 due to gravity, g 114
 algebraic solution of force systems 118, 121–129
 angular
 impulse 161
 momentum 161
 velocity 151–154
 center and radius of oscillation 151
 center of gravity 136–142, 151
 center of percussion 151
 centrifugal force 163–166
 calculating 164
 couples 120–121
 differential pulley 135
 dynamics 113
 energy 156–158
 force 118–121
 force of a blow 159–160
 graphical solution of force systems 118–120
 impulse and momentum 160–162
 angular 161
 inclined plane 130, 155
 kinetic energy 157–159
 levers 132
 linear velocity 151–152
 metric SI units 113, 116, 118
 decimal multiples and submultiples of 2522
 moment of inertia 143–146
 momentum 160–162
 Newton's laws 154–155
 pendulums 188–189
 potential energy 157–158
 pound force 114
 power 162–163
 pulleys 134–135
 radius
 of gyration 146
 radius of gyration 147–151
 radius of oscillation 151
 scalar and vector quantities 118
 screw 135
 SI metric units 113, 116–118
 statics 113
 toggle joints 133
 torque 156
 units 113–116
 vectors 118
 velocity, angular 151–152
 velocity, linear 151–152
 wedge 130
 wheels 134
 work 158–159, 162–163
 work and energy relation 158–159
 work and power formulas 162–163
 work performed by forces and couples 158
Meehanite castings 1328–1329
Melting points
 alloys of copper and zinc 1356–1357
 alloys of lead and tin 1353
 brazing alloys 1356–1358
 metals 368–370
 solder 1353
 various metals 368–370
Mercury inches of, and equivalent pressure 388
Metal
 aluminum alloys 368–369
 balls, standard 2302–2310
 bonded grinding wheels 937–938, 1140
 bonding 2460–2463
 cast iron and steel 368–369
 coloring 1440–1443
 copper-base alloy 368–369
 foundry patterns 1340
 identification 521

- Metal** *(continued)*
- inert gas (MIG) welding 1362–1371
 - manganese bronze 368–369
 - melting points 368–369
 - nickel 368–369
 - numbering systems for 403, 405
 - plasma welding 1387–1390
 - properties of 473–478
 - slitting saws 776
 - specific gravity and properties 368–370
 - spraying process 1351
 - stainless steel 368–369
 - temperature effect on strength 475, 478
 - titanium alloy 368–369
- Metal working**
- application 1113
 - fluid selection 1113
 - use 1113
- Metal working Fluids**
- classes 1112
 - occupational exposure 1112–1115
- Metallurgy, powder** 1350
- Meters into feet** 2541
- Metric**
- basic sizes, British Standard
 - preferred 667
 - bolts and screws, British Standard
 - clearance holes for 1903–1904
 - conversion factors 2525–2531, 2533
 - tables 2525–2553
 - dimensions on drawings 708, 710
 - dowel pins, British Standard 1648–1650
 - equivalents 2525–2553
 - fasteners, ANSI 1520–1527, 1529, 1532–1534, 1541, 1544–1549
 - inch vernier, dual 670–671
 - International System of Units (SI) 2520–2524
 - ISO limits and fits, British Standard 657–666
 - keys and keyways, British Standard 2354–2360
 - micrometer, reading 671–672
 - module, gear cutter 2021
 - gear teeth 2090–2093
 - series British ISO
 - hexagon bolts, nuts, and screws 1555–1560
 - machine screws and nuts 1586–1595
 - metal washers 1565–1566
 - socket screws 1613–1618
 - spring washers 1563–1565
 - taps 902–903
 - SI system in mechanics, calculations 113, 116–118
 - SI units, factors and prefixes 2522
 - sizes, preferred for flat metal products 2503
 - systems of measurement 2520–2523
 - threads
 - British (ISO) 1825–1834
- Metric** *(continued)*
- SI 1825
 - twist drills
 - ANSI 827–846
 - British Standard 856
 - vernier, reading 670
 - washers, plain, ANSI 1547, 1549
 - Metric (SI) System 116
 - Metric module gear cutters 2021
 - Metric system 113–114
 - base units 116
 - in strength of materials calculations 195
 - use of 116
 - Microinch 2517
 - into micrometers (microns) 2539–2540
 - Micrometer
 - into microinches 2539–2540
 - reading 670–672
 - screw thread 1859
 - Microprocessor 1229–1230
 - Microscope screw thread 1846
 - Mil 2517
 - MIL-A-8625F 1444, 1448
 - MIL-C-13924C 1444
 - MIL-C-14538C 1444
 - MIL-C-14550B 1445
 - MIL-C-5541E 1445
 - MIL-C-8837B 1451
 - Miles into kilometers 2541
 - MIL-F-495E 1445
 - MIL-G-45204C 1447
 - Military plating specifications 1444–1451
 - Mill or saw files 1431
 - Millimeters
 - hundreds of, into inches 2533
 - into feet 2538
 - into inches 2533, 2536
 - thousandths of an inch, into 2534–2535
 - Milling
 - angular 777, 783
 - cam 2186–2188
 - change gears for helical or spiral 1931–1948
 - contour 1994
 - feeds for
 - cemented carbide cutters 1013–1022
 - high-speed steel cutters 1023
 - in inches per tooth for cemented carbide cutters 1013–1022
 - helical, change gears for different leads 1931–1948
 - horsepower for 1044–1051
 - short lead 1931
 - speeds and feeds 1009–1012
 - automatic screw machine 1095
 - copper alloys 1006, 1024
 - ferrous cast metals 1021–1022
 - light metals 1013–1014
 - metal slitting (saws) 776, 1012
 - plain carbon and alloy steels 1014
 - stainless steels 1019–1020

- Milling**
 superalloys 1008–1009
 titanium and titanium alloys 1007
 tool steels 1018–1019
 thread 1928–1930
- Milling cutters** 771–806
 ANSI Standard 772–795
 arbor keys and keyways 794
 arbor type 790
 bevel gear 792, 2058–2061
 casting 1346
 classification of 772–773
 concave and convex 790
 corner rounding 775, 790
 double angle 777
 eccentric type radial relief 801
 elements of 776–779
 end mills 779–789
 gear 791–792
 grinding or sharpening 798–806
 hand of
 cut 772
 cutter 773
 flute helix 774
 rotation 772
 helical gear 2077–2078
 hollow 1095
 indicator drop methods of checking relief
 and rake angles 801–805
 keys and keyways for 794
 keyseat 795
 metal slitting (saws) 776
 number of teeth 771–772
 plain 773
 rake angles 800–801
 roller chain sprocket 792–793
 selection of 771
 setting angles for milling teeth in 796–799
 shell mills 778
 side 774
 single angle 777, 783
 spline shaft 799
 spur gear 791, 2021
 steels for 452–456
 terminology 776–779
 T-slot 775
 Woodruff keyseats 795
- Milling machine**
 Brown & Sharpe 1979
 centering plugs 923
 Cincinnati 1986–1989
 cutters for 14.5-deg. pressure angle
 gears 791–792
 draw-in bolt ends 923
 indexing 1947–1993
 lead of 1931
 platens ??–1285
 spindle noses 920–921, 924
 tapers for 920, 1929–1930
 tool shanks 922
- Milling machine** (continued)
 V-flange, NC 1284–1285
 MIL-L-46010D 1448
 MIL-M-3171C 1446
 MIL-M-45202C 1446
 MIL-P-45209B 1449
 MIL-P-81728AT 1446
 MIL-R-27426 1674, 1676, 1678, 1680
 MIL-R-46085B 1450
 MIL-T-10727C 1451
 Miner's law of linear damage 198
 Miniature screw threads 1781–1785
 Minutes into decimals of a degree 90, 92
 Miscellaneous functions (M-words),
 NC 1249
- Module** 2000
 flexible manufacturing, NC 1235
 splines, metric 2148–2155
 system of gear teeth 2090–2093
- Modulus**
 polar moment 278
 polar section 278
- Modulus of elasticity**
 for various materials 196
 perforated metal 235
 shear 196
 elasticity, E (Young's) 196, 326–329
 for various materials 196
 iron and steel 476
 nickel-based alloy 289–290
 nonferrous metals 477
 plastics 380
 flexural 380
 rupture 375–376
 wood 375
 shear (G) 196
 for various materials 196
 in plastics 573–575
 in spring design 329
 spring materials 326–329
- Modulus section**
 polar 277
- Mohs hardness scale** 521, 524
- Molding**
 green sand 1336–1337
 shell 1336–1337
- Molds, steels for permanent** 468–469
- Molybdenum**
 high-speed steels 510–512
 heat treatment of 510–512
 tool steels 457–458, 460, 462, 464
 steels, SAE 409
- Moment of a force** 113, 120
- Moments of inertia** 143–146
 angles, steel 2495–2497
 built-up sections 217
 channels, aluminum 2498
 channels, steel 2494
 cross-sections 217–227
 formulas for various sections 217–227

- Moments of inertia
 I or S shapes, steel 2493
 I-beams, aluminum 2498
 I-beams, steel 2489–2493
 of complex areas 146
 pipe 2339–2341
 plane areas 143
 polar 143–146, 229, 277–278
 cone 144
 cone, frustum 144
 cylinder 144
 cylinder, hollow 144
 ellipsoid 145
 paraboloid 145
 prism 144
 pyramid 144
 solid ring 145
 sphere 145
 spherical sector 145
 spherical segment 145
 torus 145
 rectangles 228
 round shafts, table for 229–234
 structural channels 2494, 2498
 wide flange, steel 2489–2492
- Moments of Inertia, Section Moduli and
 Radius of Gyration 218
- Momentum 160–162
- Monel metals, machining 1118
 properties 562–563
- Monotron for hardness testing 518–519
- Morse
 reamers for sockets 824
 stub taper shanks 907–908
 tapers 906–917
 twist drill gage 2499
- Mortising wood 378
- Motion
 accelerated 153–156
 constant acceleration 152
 constant velocity 151
 force and work 154–155, 158
 general formulas 151–153
 linear motion, constant
 acceleration 152
 rotary motion, constant
 acceleration 153
 Newton
 first law 154
 second law 154–155
 third law 155
 on inclined plane 130, 155
 rotary, formulas 153
 uniformly accelerated 151
- Motion control
 analog transducers 2475
 closed-loop systems 2468–2470
 control function 2471
 features of controllers 2470
 control motors 2472–2474
 feedback transducers 2474
- (continued)
- Motion control (continued)
 hydraulic systems
 control systems 2476–2480
 electronic controls 2480
 proportional control 2479
 pumps and fluids 2475–2476
 mechanical stiffness and vibration 2471
 open loop systems 2467–2469
 pneumatic systems 2476–2477, 2481
 synchros and resolvers 2475
 system application factors 2467
- Motors, electric 2445–2459, 2472–2474
 adjustable-voltage, shunt-wound 2449
 alternating current 2449–2452
 characteristics 2448–2457
 classes of standards 2445
 compound-wound 2449
 control 2472–2474
 current definitions 2445–2448
 DC 2448–2449
 brushless, NC 2471–2473
 brush-type, NC 2472–2473
 design letters 2445
 direction of rotation 2447
 factors governing selection 2453–2455
 frame sizes, standard 2445
 high frequency induction 2451
 hydraulic, NC 2475–2476
 injurious operating conditions 2455
 inspection schedule 2458–2459
 locked rotor current and torque
 ratings 2445–2446
 lubrication, proper 2458–2459
 maintaining and repairing 2458–2459
 mounting dimensions, standard 2445
 multiple speed induction 2451
 NEMA 2445–2447
 standards for 2445
 polyphase 2445–2450
 polyphase wound-rotor 2446
 pull-up torque 2446
 rotation, standard direction 2447–2448
 selection 2453–2455
 shunt-wound 2448–2449
 single-phase motors 2451–2452
 speed reducer type 2452–2453
 squirrel-cage induction 2445–2449
 standards for 2445–2446
 stepper, NC 2471–2473
 synchronous 2451
 torque definitions 2445–2448
 type, dc and ac 2448–2453, 2472
 types and characteristics for different
 applications 2456–2457, 2472
 used for motion control 2472–2473
 variable speed 2447–2448
 wound rotor induction 2451
- Mounted wheels and mounted points 1204–
 1206
- Mounting bearings 2271–2284
- MS 16624 1682

MS 16632 1685
 MS 16633 1686
 MS 3215 1687
 Multiple or block indexing 1990–1991
 Multiplying numbers written in powers-of-ten notation 18–19
 Muriatric acid, specific gravity 371
 Music wire, gages 2499–2500
 spring material 286, 385
 M-words, NC 1249

N

Nails and spikes, standard 1455
 Narrow V-belts 2373–2379
 National Fire Protection Association
 NFPA No. 194 1843
 NFPA 1963 1844–1845
 National Tube Co. 274
 Nautical measure 2517
 NC programming 1240–1284
 Needle roller bearings
 designations of 2267
 fitting and mounting practice 2269
 roller and cage assemblies 2269
 shaft and housing tolerances 2270–2271
 tolerances 2261–2264
 types of 2253–2254
 Negative and positive numbers 16
 Negative functions of angles 93
 NEMA standards for electric motors 2445–2447
 Newton's laws of motion 154–155
 Newton's second law 117
 Newton-meters into pound-inches 2550
 Newton-Raphson method 35
 Newtons into pounds force 2550
 Nickel
 alloys 561–563
 machining 1118–1119
 chromium steels, SAE strength 476
 melting point 368–370
 plating 1447–1448
 Nickel steels 411–412
 Nickel-chromium steels, SAE 413
 Nitinol, machining 1118
 Nitralloy steels 498
 Nitric acid, specific gravity 371
 Nitriding 417, 498
 high-speed steel tools 512–513
 ion nitriding 498
 Nitrogen, liquid temperature 623
 Nodular cast iron 1332
 Noise, machinery 1297
 Nomenclature
 bevel gears 2054
 gear teeth 2002
 spur gears 2003
 Nominal clearance 2129
 Nominal vs effective interest rates 25

Nondestructive testing symbols 1408–1409
 Nonferrous alloys 525–566
 machining 1116–1119
 strength 473, 477–478, 525–564
 Nonmetals, strength of 478
 Normal
 distribution curve 1216–1219
 positional deviation 1216–1219
 Normal lane 2000
 Normal plane 2000
 Normalizing 414–415, 481, 495–496, 503–505
 temperatures 504–505
 Norton Company 1142, 1150–1156
 Nozzles, flow of water through 390
 Number of nails and spikes in a pound 1455
 Number of teeth 2000
 Numbering systems
 for metals and alloys 403, 405
 for steel 405, 409–410, 413
 Numbers
 positive and negative 16
 powers-of-ten notation 17, 19
 preferred series 19, 632, 642, 667
 progressions 43–45
 Numerical control 1225–1297
 absolute programming 1248
 accuracy, repeatability, and resolution 1216–1219
 adaptive control 1233
 addresses, letter 1243
 APT programming 1263, 1274–1280
 circles 1269–1270, 1272
 computational statements 1265
 example program 1277
 for turning 1279–1280
 geometry statements 1265
 lines 1267
 motion statements 1270–1275
 planes 1273
 points 1266
 postprocessor statements 1275–1280
 tabulated cylinder 1274
 automatically programmed tool (APT) 1263–1280
 axis nomenclature 1235–1239
 bit 1229
 block 1243–1245
 byte 1229
 CAD/CAM 1287, 1296–1297
 central processing unit 1229
 circular interpolation 1254–1255
 closed-loop system 1233
 computer-aided part programming 1241
 control, adaptive 1233
 cutter compensation 1251–1253, 1281–1284
 cutter location data 1242
 decimal point programming 1243
 direct (or distributed) NC 1296
 drive motors 2472–2473

- Numerical control *(continued)*
- feed rate override 1251
 - fixed (canned) cycles 1258–1262
 - flexible manufacturing
 - cell 1235
 - module 1235
 - system 1234
 - format detail 1243
 - F-word 1250
 - G-code addresses 1245–1249
 - helical interpolation 1255
 - incremental programming 1248
 - initial graphics exchange specification (IGES) 1294–1296
 - insert holders for NC 732–738, 1281–1284
 - insert radius compensation 1281–1284
 - interpolation
 - circular 1254–1255
 - helical and parabolic 1255
 - linear 1253
 - letter addresses 1243–1245
 - linear interpolation 1253
 - machine platens ??–1285
 - macro 1257–1258
 - manual data input 1240
 - microprocessor 1229–1230
 - miscellaneous functions, (M-Words) 1249
 - open-loop system 1233
 - parabolic interpolation 1255
 - parametric
 - expressions and macros, NC 1257–1258
 - programming, NC 1257–1258
 - subroutine 1257–1258
 - part programming 1240–1243
 - part tolerance symbols
 - ANSI 1221
 - compared to ISO 609
 - points, lines, circles (APT) 1266–1270
 - postprocessor 1243, 1265
 - preload registers (G92) 1249
 - preparatory word 1245–1249
 - programmable controllers 1229–1233
 - programming
 - absolute 1248
 - incremental 1248
 - NC 1240–1284
 - repeatability, accuracy, and resolution 1216–1219
 - sequence number 1245
 - standards 1226
 - subroutine 1256–1258
 - S-word 1251
 - thread cutting 1262, 1908–1909
 - tool
 - compensation 1281–1284
 - data table 1251
 - length offset 1253
- Numerical control *(continued)*
- nose radius compensation 1253, 1281–1284
 - offset 1252
 - total indicator reading 1238
 - turning cycles 1262
 - T-word 1251–1253
 - V-flange tool shanks 1285
 - word address format 1243–1245
 - zero suppression 1245
- Nut taps 872, 884, 890–891
- Nuts
- acorn 1503
 - ANSI, inch dimensions
 - flat jam 1500
 - hex 1493–1494, 1499
 - hex flat 1500
 - hex high 1504
 - hex slotted 1500–1502
 - hex slotted high 1504
 - hex thick slotted 1501–1502
 - jam 1499
 - machine screw 1568
 - square 1493–1494, 1502
 - T-type 1647
 - types of 1495
 - Unified 1492–1496, 1499–1502
 - ANSI, metric dimensions
 - heavy hex 1548
 - hex flange 1545
 - hex jam 1548
 - hex, styles 2 and 3 1543
 - prevailing torque, hex 1546
 - prevailing torque, hex flange 1547
 - slotted hex 1544
 - British Standard
 - Fine 1551–1554, 1586, 1598
 - ISO metric 1555–1561
 - metric 1586, 1589, 1591, 1595–1596
 - Unified 1595–1597
 - Whitworth 1551–1554, 1595–1598, 1619
 - crown, low and high (SAE) 1503
 - eye nuts 359
 - high, SAE 1504
 - slotted, high hex (SAE) 1504
 - wing nuts 1693–1696
 - wrench clearances 1510–1511
 - wrench openings 1510–1511
- Nylon
- bearings 2242
 - machining 597–599
 - properties 380, 579, 582–583, 588, 601
 - rope, strength of 353
-
- O**
- Oblique-angle triangles
 - solution 88–89
 - Octagon area 62

- Octoid gear teeth 2053
 Offhand grinding 1192
 Offset method of determining yield
 strength 196
 Ohm's law 2532
 Oil feeding and grooving of bearings 2204–2205
 Oil impregnated bearings 2242–2245
 Oilless bearings 2242, 2245
 Oils
 and compounds, machining 1106, 1108–1119
 emulsifying or soluble 1107
 mineral 1109–1110
 sulfurized and chlorinated 1109–1110
 coating 1448
 lubricating 2311–2314, 2319
 viscosity unit conversion 2201–2202, 2312–2313
 tempering 493
 Open-end wrench clearances 1511
 Open-loop system 1233, 2467–2469
 Operations on complex numbers 39
 Orbit 1320
 Order of performing arithmetic 21
 O-ring 2482–2486
 groove dimensions and clearances 2483–2485
 ring materials 2486–2487
 squeeze 2482–2483
 surface finish in contact with 2484–2485
 Oscillation, center and radius of 151
 Ounces, avoirdupois, into grams 2546
 Out of roundness 694–696
 Oval head machine screws 1574–1576
 Oxygen
 gas in welding 1364–1367, 1428–1429
 specific gravity 371
-
- P**
- Pack
 carburizing 417
 hardening 498
 Packing
 in circles 72–75
 in circles and rectangles 72–77
 in rectangles 77
 Palladium, plating 1449
 Pan head machine screws 1573
 Paper, bonding 2462–2463
 Pappus or Guldinus rules 56
 Parabola
 area 64–65
 center of gravity 139
 constructing 55
 segment of area 65
 Parabolic interpolation, NC 1255
 Paraboloid
 center of gravity 141
 Paraboloid (continued)
 polar moment of inertia 145
 radius of gyration 150
 segment volume 71
 volume 70
 Parallelepiped 149
 Parallelogram
 area 60
 center of gravity 136
 geometry of 48
 of forces 119
 radius of gyration 148
 Parametric subroutine, NC 1257–1258
 Passivation of copper 1441–1442
 Patenting process in wire making 481
 Patterns for castings 1339–1340
 materials 1339–1340
 metal 1340
 shrinkage allowances 1339–1340
 varnish 1339–1340
 weight of casting from 1340
 wood 1339–1340
 PD 6481 667
 Pearlite 483–484
 Pearlitic malleable iron 1330–1331
 pebi 2533
 PEEK plastics 380
 Pendulum 188–189
 calculations 189
 conical 188–189
 formulas for 189
 physical 188–189
 simple and compound 188–189
 torsional 188–189
 types of 188
 Percentage 23–24
 Percussion, center of 151
 Perforated metals, strength and stiffness of 235
 Permannickel, machining 1118
 PET plastics 380
 Petroleum, specific gravity 371
 Phenolic plastics 2242
 Phosphate coating 1449–1450
 Phosphor-bronze
 wire strength 477
 worm gearing 2117
 Phosphorus
 specific gravity and weight 370
 Physical vapor deposition (PVD) 750
 Piano wire, working stresses 293–295
 at elevated temperatures 295–297
 Piles, weight of 373
 Pillow block bearings 2254
 Pilot hole for wood screws 1456
 Pin method for checking
 gear sizes 2094–2108, 2111–2112
 allowance for backlash 2103
 for involute splines 2147
 wire diameters 2094, 2103
 screw threads 1860–1877

- Pin method for checking (continued)
- V-shaped grooves 690
- Pinion, spur gear
- checking by measurement over wires 2111–2112
 - enlarged to avoid undercut 2019–2028
- Pins
- clevis 1648
 - cotter 1648, 1659, 1662
 - dowel 1648–1654
 - grooved 1656, 1658–1662
 - metric dowel 1648–1650
 - spring 1663–1664
 - straight 1653–1655
 - strength of taper 215–216
 - taper 1655–1658
- Pintle chains 2421
- Pipe and pipe fittings 2504–2512
- ANSI Standard wrought steel 2507–2508
 - British threads 1857–1858
 - columns 264–265
 - cross-sectional area of metal 2507–2508
 - cubic contents for given length 392, 2507–2508
 - definitions 2504, 2510–2511
 - Dryseal 1852–1855
 - measuring by wire method 1872, 1875–1876
 - straight 1848, 1851–1852
 - taper 1846–1850
 - threads 1852–1855
 - flow in 2509
 - gallons per foot 392, 2507–2508
 - grades of 2505–2508
 - heat loss from uncovered steam 365
 - length per cubic foot 2507–2508
 - loads, table of 264–265
 - moment of inertia 2507–2508
 - plastics 2510–2512
 - radius of gyration 2507–2508
 - reamers, taper 825
 - schedule numbers 2505
 - sealing joints 1458–1459
 - section modulus 2507–2508
 - steel, welded and seamless 2505
 - taps, dimensions 879–882, 894
 - Briggs and Whitworth 1907–1908
 - British Standard 1901–1903
 - Internal Dryseal 1855
 - internal dryseal 1855
 - power for driving 1907–1908
 - straight 872, 879–896
 - taper 872, 879–881
 - threads
 - American National Standard 1846–1855
 - British Standard 1856–1858
 - weight per foot 2505–2508
 - wrought steel 2504–2505
- Pipe welding 1402
- procedure 1405
- Pitch 2000
- broach teeth 926–929
 - circle 2000
 - circular, of gears 2002–2004
 - diameter 2000
 - diameters, gears
 - bevel 2054–2057
 - circular pitch 2022
 - helical 1932, 2068
 - pin method of checking 2094–2108, 2111–2112
 - spur 2004, 2022
 - worms 2065
 - diameters, roller chain sprockets 2427–2428
 - diameters, thread
 - (see also type of thread)
 - lead angle at 1932
 - Unified 1716–1749
 - checking 1859–1877
 - for tensile stress area 1482
 - lead angle at 1932
 - metric, M profile 1766–1775
 - wire sizes for measuring 1861–1862
 - gear 2004
 - plane 2000
 - point 2001
 - rivets 1457, 1461–1462
 - screw threads, measuring 1859
 - worms 2064
- Plain bearings 2193–2210, 2214, 2220–2232, 2237–2244
- allowable pressures 2209
 - boundary lubrication mode 2195–2196
 - circumferential-groove 2193
 - classes of 2193
 - clearances 2209
 - cylindrical-overshot 2193–2195
 - cylindrical-undershot 2193–2195
 - design 2195, 2206–2218, 2220–2234
 - displaced elliptical 2193–2195
 - elliptical-overshot 2193–2195
 - full film operational mode 2197
 - grooving and oil feeding of 2204–2205
 - hardness and surface finish 2199–2200
 - heat radiating capacity 2204–2205
 - hydrostatic 2195–2196
 - journal or sleeve 2193–2196, 2205–2219
 - length-to-diameter ratio 2209
 - lubricants 2202–2205
 - lubrication analysis 2207–2219
 - lubrication methods 2201–2203
 - machining 2199–2201
 - materials 2236–2245
 - mixed-film lubrication mode 2197
 - modes of operation 2195–2197
 - multiple-groove 2193–2195
 - nutcracker 2195–2196
 - oil grooves 2204–2209
 - operating temperatures 2210–2219
 - pivot-shoe 2193–2195

- Plain bearings *(continued)*
- pressure 2193–2195
 - retaining methods 2197–2199
 - sealing methods 2198–2200
 - sleeve or journal 2193–2196, 2205–2219
 - surface finish and hardness 2199–2200
 - three-lobe 2193–2195
 - thrust, design 2218–2235
 - types 2193–2196
 - viscosity conversion table 2201–2202, 2312–2313
 - viscosity temperature chart 2202–2203
- Plain milling cutters 773
- Plain washers
- inch 1512–1519
 - metric 1549
- Plane figures, areas and dimensions 60–65
- Plane of rotation 2001
- Planetary gearing 2083–2087
- compound drives 2087
- Planetary thread milling 1929–1930
- Planing
- estimating cutting speeds 1044
 - power required 1046–1050
 - speeds and feeds 1044
 - time 1044
 - tool grinding 729–730
 - wood 378
- Plaster of Paris, weight 370
- Plastic region 196
- Plastics 567, 582–604
- assembly with fasteners 595–597
 - bonding 591, 2460–2466
 - chemical resistance of 583
 - definitions 568–571
 - design
 - for assembly 591–595
 - for injection molding 586–591
 - developing prototypes 599–600
 - draft angles and depth of draw 590
 - drilling speeds and feeds 598–599
 - effects of temperature 578–581
 - elastomers 567–570
 - electrical properties 581–582
 - environmental effects 581–584
 - finishing 600
 - gearing 601–604
 - accuracy 603–604
 - backlash 603–604
 - service factors 603
 - tooth form factors 602
 - machining 597–600
 - materials 567–570
 - machining 600
 - mechanical properties 570–579
 - effect of temperature on 578–581
 - related to time 576–577
 - mixtures 567–570
 - modulus, E 576
 - modulus, G 573–575
 - opacity 569
- Plastics *(continued)*
- physical properties 571
 - density 568–569
 - opacity 569–570
 - shrinkage 568–569
 - water absorption 568–569
 - pipe and fittings 2510–2511
 - sawing, speeds and numbers of teeth 599
 - structural analysis 582, 584
 - structures 567–570
 - thermal properties 578–579
 - thermal stresses 585–586
 - thermoplastic 567–570
 - thermosetting 567–570
 - Vicat softening point, plastics 578–579
 - wall thicknesses 587–588
- Plastics bearings
- anti-friction 2254
 - laminated, plain bearings 2242, 2245
 - sleeve 2242, 2245
- Plastics pipe 2510–2512
- joining 2510–2511
 - pressure ratings 2512
 - properties and use of 2511
 - weights and dimensions 2510
- Platens, machine, NC ??–1285
- Plates
- flat, strength and deflection of 268–270
 - shells and cylinders, strength of 268–274
- Plating 1444–1451
- chromium 1427
 - Plating, chromium 1427
- PLC (programmable logic control) 1229–1233
- Plow steel haulage rope, strength of 336–341, 352–354
- Points, lines, circles, (APT) NC 1265–1270
- Poise 2201–2202, 2312–2313, 2319
- Poisson's ratio 268
- for various materials 270
- Poisson's ratio 196, 268
- for various materials 196
 - of various material 384
 - perforated metal 235
 - plastics 573–574
- Polar
- coordinates 36
- Polar moment of inertia 143–146, 229, 277–278
- cone 144
 - cone, frustum 144
 - cylinder 144
 - cylinder, hollow 144
 - ellipsoid 145
 - masses 143
 - paraboloid 145
 - plane areas 143
 - prism 144
 - pyramid 144
 - solid ring 145
 - sphere 145

- Polar moment of inertia *(continued)*
 spherical sector 145
 spherical segment 145
 torus 145
- Polar moments of inertia 144
- Polar section modulus 229, 277–278
- Polishers, spindles for portable 1209
- Polishing and buffing 1439–1440
 abrasives 1439
 speeds 1440
 wheels for 1439–1440
- Polycarbonate plastics 380, 579, 588, 598, 601
- Polygon
 area 62, 78
 formulas and table 78
 length of side 78
 of forces 119
 radius of circumscribed circle 78
 radius of inscribed circle 78
 shafts 2160–2161
- Polygon-type shaft
 connections 2160
 dimensions of 2161
 three- and four-sided designs 2161
- Polyphase motors 2445–2450
- Polypropylene plastics 380, 579, 588, 598, 2511
- Polysulphone plastics 579, 588, 598
- Polyurethane plastics 380, 579, 588, 598, 601, 2486
- Porosity, pressure die castings 1341
- Porous bearings 2241–2245
- Portable grinding 1192
 safety 1172
- Portable tools
 hexagonal chucks for 1210
 hexagonal shanks for 1210
 spindles and drives for 1207–1210
- Positional deviation, mean 1216–1219
- Positional tolerances 611
- Positioning accuracy 1216–1219
- Positive and negative numbers 16
- Positive clutches 2333
- Positive functions of angles 93
- Postprocessor, NC 1243, 1265
- Potential energy 157–158
- Pound force 114
- Pound-inches into newton-meters 2550
- Pounds
 force 114, 116
 force into newtons 2550
 mass 116
 per cubic foot into kilograms per cubic meter 2549
 per cubic inch into grams per cubic centimeter 2549
 per square foot into kilograms per square meter 2548
 per square inch into kilograms per square centimeter 2548
- Pounds *(continued)*
 per square inch into kilopascals 2548
- Powder metallurgy 1350
- Powdered metal bearings 2242–2245
- Power
 brush finishing 1435–1438
 constant for machining 1052
 for driving pipe taps 1907–1908
 general formulas 162
 heat equivalents 2551
 in mechanics 113
 required for machining 1046–1055
- Power and roots of numbers 17
- Power of ten notation 17, 19
 expressing numbers in 18
- Power transmission
 belting 2368–2369, 2372–2417
 chain 2431–2435, 2442
 friction wheels 2339–2341
 wire rope 336–344
- Precipitation
 hardening 480
 heat-treatment 546
- Precision
 bolts and screws, British 1552–1553, 1559
 gage blocks 717–719
 investment casting 1344–1346
- Precision gage blocks 717
- Preferred 646
 basic sizes, ANSI Standard 628–644
 fits, ANSI Standard 646–647
 hole basis metric fits, ANSI Standard 651
 metric sizes
 ANSI Standard 642–644
 British Standard 667
 numbers 19
 British Standard 667
 series for tolerances and allowances 630
 series of basic sizes 628
 shaft basis metric fits, ANSI Standard 646, 652–655
 thicknesses for flat metal products, metric 2503
 thicknesses for uncoated metals and alloys 2501
- Preferred roughness average values (Ra) 708
- Preferred roughness values and roughness grades 716
- Preferred series maximum waviness height values 708
- Preload registers, (G-114 word) NC 1249
- Preparatory word, (G-word) NC 1245–1249
- Present
 value and discount 26
 worth 27, 30–31
 method 29–30
- Press work 1301–1311
- Presses power, shut height 1302–1304
- Pressure 117
 and flow of water 386–392

- Pressure *(continued)*
- comparison of various unit of 388
 - head in feet of water 387
 - head in foot to psia relation 386
 - head of mercury in mm 387
 - pascal 387
 - psia 387
 - to Head in feet relation 386
 - unit conversion 388, 2519, 2548–2550
- Pressure angle 2001
- Pressure effect on wood property 376
- Pressure for composite checking of fine-pitch gears 2042
- Pressure-viscosity coefficient for lubricants 2324
- Prime numbers and factors 3–12
- Principle reference planes 2001
- Prism
- polar moment of inertia 144
 - rectangular 149
 - volume 66
 - volume formula 56
- Prismoidal formula for volume 56
- Profile checking, gearing 2030–2031
- Programmable logic controller, NC 1229–1233
- Programming
- absolute, NC 1248
 - APT 1263–1280
 - G-code 1243–1263
 - incremental, NC 1248
 - numerical control 1240–1280
- Progression
- arithmetical 43–44
 - geometrical 43, 45
- Projected tolerance zone 611
- Prony brake dynamometer 2339–2341
- Properties 464
- mechanical 195–196, 430–436, 439–441, 476–478
 - compressive 196
 - fatigue 197
 - perforated metal 235
 - shear 197
 - strength 385, 430–436, 439, 441, 476–478, 550–555
 - effect of heat or temperature on 475–478
 - thermal 364, 367–370, 478
- of materials 473–478
- Air 393
 - air 393–394
 - aluminum alloys 542–557
 - ceramics 379
 - copper alloys 525–542
 - copper-silicon and copper-beryllium alloys 565–566
 - copper-zinc-tin alloys 478
 - magnesium alloys 557–560
 - metals 473, 475–478
- Properties *(continued)*
- nickel alloys 561–563
 - nonferrous alloys 477, 525–566
 - pipes 392
 - plastics 380
 - powdered metal alloys 383
 - specific gravity 370–371
 - spring wire 385
 - standard steels 403, 413, 420–428, 430–443
 - titanium alloys 561, 564
 - tool steels 444–458, 460, 462, 464–471
 - water 386–388
 - wood 375–377
- strength
- effect of heat or temperature on 578–581
- Proportion 21–23
- compound 21–22
 - inverse 23
- Proportional limit 195
- plastics 583
- Prospective rate of return method 30–31
- Protractor, reading vernier scale on 669
- Providing backlash 2039
- PTFE plastics 380, 598, 2242, 2465–2466
- Public Law 101-592 1492
- Pulley flywheel 173
- Pulley taps 884, 890–891
- Pulleys
- center distances, V-belt 2372–2419
 - diameter of V-belt 2374–2420
- Pulleys (sheaves)
- differential 135
 - flat belt 2369
 - rules for calculating diameters and speeds 2370–2371
 - speeds, rpm into feet per minute 985–990, 1908–1909
- Pulleys and belt drives 134–135, 2368–2371, 2373–2419
- flat belt 2368–2371
 - lengths of open and crossed belts 2369, 2371
- Pulleys and wheels in mechanics 134–135
- Pulleys, V-belt 2372–2419
- Pull-up torque 2446
- Punch presses speeds and pressures 1302–1304
- Punches and dies 1301–1306
- pressures required 1302–1304
 - steel for 452–456
 - steel for hot-working 452–456
- Punches, steels for 452–456
- PVC plastics 380, 598, 601, 2511
- PVDF plastics 380
- Pyramid
- center of gravity 140
 - frustum center of gravity 140
 - frustum of volume 67

Pyramid
 polar moment of inertia 144
 volume 66

Q

QQ-C-320B 1445
 QQ-N-290A 1448
 QQ-P-35C 1449
 QQ-P-416F 1444
 QQ-S-365D 1450
 Quadrant 93
 Quadratic equations 33
 Quartz, specific gravity and weight 370
 Quenching 414
 baths 414, 491–492
 media 415–416
 tanks for 490
 interrupted 490–492
 isothermal 492
 media 416

R

Rack 2001
 gear 2005
 milling, indexing 1993
 spline, metric 2155
 Radian per second conversion from rpm 187
 Radians equivalent to degrees 90, 92
 Radius
 of arc, checking 690–692
 of curvature 2178–2184
 of gyration 146–151
 angles, steel 2495–2497
 bar, small diameter 147
 channels, aluminum 2498
 channels, steel 2494
 circular disk, thin 147
 circular ring, thin flat 148
 cone 149
 cone, frustum 150
 cylinder 148
 cylinder, hollow 149
 ellipsoid 150
 flat plate, thin 148
 hollow cylinder, thin 148
 hollow sphere 150
 I-beams 2489–2492
 I-beams, aluminum 2498
 paraboloid 150
 parallelepiped 149
 parallelogram 148
 pipe 2507–2508
 prism, rectangular 149
 ring 147
 S- or W-shape, steel 2493
 sphere 150
 sphere, hollow 150

Radius *(continued)*
 spherical shell, thin 150
 structural angles 2495–2497
 thin flat plate 148
 thin spherical shell 150
 wide flange, steel 2489–2492
 of oscillation 151
 radius
 of gyration 150
 Radius of gyration
 various cross-sections 217–227
 radius of gyration 148–150
 Rails
 size to carry given load 259
 strength of 259
 Rake angles
 checking milling cutter 801–805
 turning tool 723, 726–728
 Rankine's formulas for columns 261, 263
 Rankine, degrees 2514
 Rasps 1432–1433
 Ratchet gearing 2088–2089
 Rate of return (interest) 24–27, 30–31
 prospective 27, 30–31
 Rating life, bearings 2286–2296
 Ratio 21–23
 and proportion 21–23
 compound 21
 contact, in gearing 2024–2029
 epicyclic gearing 2083–2087
 fractional, change gears for 1913–1914
 gear
 for differential indexing 1976–1978
 geometrical 43, 45
 inverse or reciprocal 21
 of volumes 71
 Poisson's 196
 slenderness, columns 261
 V-belt drives 2372–2419
 Ream, paper 2519
 Reamer arbors, driving slots and lugs for shell 823
 Reamers 807–826
 ANSI Standard 813–826
 arbors for shell 823
 Brown & Sharpe taper socket 825
 center and countersink 813
 centers for 813
 chucking 815, 820–822
 die-maker's 826
 difficulties with 812
 drills for taper pin 1656–1658
 driving slots and lugs for shell 823
 expansion chucking 814
 expansion hand 817
 finishing 824
 fluting cutters for 808–810
 fluting to obtain negative rake 807
 hand 816–817
 jobbers 818
 machine 819–820

- Reamers *(continued)*
- Morse taper socket 824
 - pipe 825
 - rose chucking 808, 821–822
 - shell 822
 - steels for 452–456
 - stub screw machine 819–820
 - taper pin 826
 - taper pin reamers, drills for 1655–1658
 - taper pipe 825
 - taper, milling teeth 796
 - teeth, irregular spacing 807–808
 - terms applying to 814–815
 - threaded end, hand 807–808
 - tooth-rest position for grinding clearance 811
- Reaming
- cutting speeds for
 - copper alloys 1041
 - ferrous cast metals 1037–1038
 - light metals 1039
 - stainless steels 1036
 - tool steels 1035
 - difficulties 812
 - feeds and speeds on automatic screw machines 1095
 - taper pin 1657
- Rearrangement and transposition of terms in formulas 20–21
- Recalescence point in steel hardening 479, 485
- Recesses, square and cross-shaped, for machine screws 1577
- for self-tapping screws 1623
- Recessing tools, speeds 1095
- Reciprocal or inverse ratio 21
- Reciprocals of numbers 17
- Rectangle
- area 60
 - table of section moduli 229
- Rectangular and spherical coordinates, relationship 37
- Rectangular coordinates 36
- Rectangular to cylindrical coordinates 38
- Refrigeration of steel 514–517
- Relative density 370
- Relief and rake angles
- for single-point cutting tools 726
 - for single-point thread cutting tools 1910–1911
 - indicator drop method of checking 801–805
- Repeatability, accuracy, and resolution 1216
- Replacement-gear dimensions, calculating 2122–2125
- Resinoid bonded wheels 937–938, 1140
- thread grinding 1923
- Resolution of force systems 121
- Resultant 154
- Retaining rings
- ANSI Standard
- (continued)*
- Retaining rings *(continued)*
- metric 1666–1673
 - failure of 1683–1690
 - groove design and machining 1687–1688
 - inch 1674–1689
 - selection 1665, 1669, 1678, 1683–1687
 - standards 1689–1692
- Retarded motion motion 151
- Retention knobs, V-flange tool shanks 1284–1285
- Reyn 2201–2202, 2312–2313
- Rhodium plating 1450
- Right-angle triangles
- solution 86–87
- Rigidity
- modulus of (shear) 196
 - spring materials 326–329
- Ring
- area and volume 56
 - radius of gyration 147
 - stresses in loaded 215
- Rivet
- ANSI Standard 1464, 1468–1470
 - belt 1469
 - British Standard 1464, 1471–1474
 - button head 1465, 1470
 - cone head 1465
 - cooper's 1468
 - countersunk 1463, 1466, 1468–1472
 - diameters for given plate thicknesses 1457
 - excess length to form head 1463
 - flat head 1470
 - hold-on or dolly bar sets 1467
 - large rivets, standard 1464–1466
 - material 1458
 - pan head 1465, 1470
 - pitch 1457, 1461–1462
 - sets, dimensions of impressions in 1467
 - shearing strength 1461–1462
 - small rivets, standard 1464, 1468–1470
 - spacing 1457
 - steel 1458
 - strength 1459
 - tinner's 1469
 - truss 1468
 - types of 1457
- Riveted joints 1457–1463
- allowable stresses 1459
 - design of 1457–1463
 - double and triple 1301, 1461
 - efficiency 1459–1460
 - holes for 1457
 - joint failure 1458–1459
 - joint strength 1459–1460
 - rivet length for forming heads 1463
 - rivet materials 1458
 - types of riveted joints 1457
 - working strength 1459
- RMS (root mean square) 702
- Rockwell hardness

- Rockwell hardness *(continued)*
 relationship to Brinell 521, 524
 test 517–524
- Rockwell-Brinell hardness conversion
 tables 520–524
- Rod gages 2499
- Roebbling wire gage 2499–2500
- Roll angle 2001
- Roll threads, electric socket and lamp
 base 1846
- Roller bearings 2246–2302
 ABEC and RBEC tolerances 2267
 alignment and squareness 2273–2274
 allowance for axial displacement 2264
 barrel type 2253
 bearing closures 2280
 cage materials 2254–2255
 clamping and retaining methods 2275
 clearances, running 2283–2284
 closures 2280
 cylindrical type 2249–2253
 design and installation
 considerations 2264
 designation of 2267
 failures 2285
 fits 2275, 2280
 flanged housing 2254
 friction losses in 2280
 handling precautions 2284
 housing bore tolerances 2267–2268
 housings, soft metal and resilient 2274–
 2275
 life 2285
 life adjustment factors 2296
 limitations for 2291
 location and seating 2271–2280
 locknuts and shafts 2277–2279
 lockwashers 2276
 lubricants 2318–2320
 lubrication 2282
 materials for 2254
 method of designation 2266–2267
 mounting 2271–2284
 needle type 2253–2254, 2269–2271
 pillow block 2254
 plastics 2254
 quiet or vibration-free mountings 2274–
 2275
 radial and axial clearance 2283–2284
 rating life of radial 2291–2296
 seating fits for 2274–2275
 selection 2282–2283
 self-aligning 2250–2251
 shaft and housing fits for 2275, 2280
 metric radial 2264–2266
 special or unconventional types of 2254
 spherical type 2253
 squareness and alignment 2273–2274
 static equivalent load 2301–2302
 static load rating of 2300–2301
 tapered 2252–2254
- Roller bearings *(continued)*
 tapered roller thrust type 2252–2254
 thrust 2251–2252, 2262
 tolerances for 2255–2264
 torque, starting 2281
 types of 2249–2254
- Rolling
 contact bearings 2246–2302
 friction 191
 resistance 191
- Rolling screw threads 1918–1922
 cylindrical die machines 1918
 diameter of blank 1918–1919
 diameter of threading roll 1919
 flat die machines 1918
 in automatic screw machines 1919
 speeds, and feeds 1920–1922
 steels for 1918–1919
- Root diameter 2001
- Roots
 and powers of numbers 17
 finding square and cube 17
 mean square, surface texture 702
- Rope
 Manila, safe loads and strength 354, 360
 nylon, safe loads and strength 353
 safe loads for 352–354
 slings, strength 353–354
 weight per 100 feet 360
 wire 333–350
 definitions of terms 333–334
 strength and properties 336–341
 winding drum, grooves for 342–343,
 360
- Rose chucking reamers 808, 821–822
- Rotary file or burs 1433–1434
- Rotary motion
 formulas 153
 formulas for accelerated 153
- Rotating parts, balancing 167–172
- Roughness
 control of 697–708
 cutoff 697, 707–708
 height values 699–700
 parameters
 rules for determining 715
 rules for measurement of 716
 symbols indicating degree of 697–700
- Round head machine screws 1577
 British Standard 1591–1598
- Rpm
 conversion to radian per second 187
 for various cutting speeds and diameters,
 inch units 987–990
 metric units 989–990
 for various grinding speeds and
 diameters 1174
- RS-232-D interface 1227
- Rubber
 bearings 2242, 2245
 bonded grinding wheels 1140

Rubber *(continued)*
 bonding 2461–2462
 mold casting 1337–1338
 turning 1044
 Rules to compare measured values 715
 Running
 balance 167
 fits, allowances 631–635

S

SAE General Information 2238
 SAE Grade 1 1488
 SAE Grade 2 1488
 SAE Grade 4 1488
 SAE Grade 5 1488
 SAE Grade 5.2 1488
 SAE Grade 7 1488
 SAE Grade 8 1488
 SAE Grade 8.2 1488
 SAE J1199 1530
 SAE J429 1496
 SAE J995 1489, 1494
 SAE Recommended Practice J483a 1503
 SAE Standard 2352
 steel specification numbers 409–412
 SAE Standards
 babbitt metals 2239–2240
 bearing metals 2239–2240
 crown or acorn nuts 1503
 die casting alloys 1342–1343
 high nuts 1504
 J482a 1504
 spark plug threads 1840
 steel specification numbers 409
 taper shaft ends 2352
 V-belts 2420
 Woodruff keyseat cutters 795
 SAE steels
 basic numbering system 409–412
 castings 1335
 compositions 409, 411–412
 heat treatments for 443, 503–505
 numbering system for 409–412
 Safe loads for wire rope 336–341
 Safe speeds grinding wheels 1171–1174
 Safety
 factor 2044–2045
 factors of 199
 flange couplings 2325
 for wire rope 339–340
 Salt baths for heat treating 487
 Salt, common, weight 370
 Sample calculations 212, 215
 strength of materials 212–215
 Sand blast cleaning 1338
 Sand, weight 370
 Sanders, spindles for portable 1209
 Sanding wood 378

Sandstone
 and limestone, strength 478
 specific gravity and weight of 370
 Saw tooth
 clutches 2335–2336
 threads 1817
 Sawn lumber size 378
 Saws
 band 1101, 1105–1106
 circular, arbors for 1203
 metal-cutting, speeds 1044
 metal-slitting 776
 sharpening files 1431–1432
 Saybolt Universal Seconds (SUS) 2312–
 2313, 2319
 Scalar and vector quantities 118
 Sclerometer 521, 524
 Scleroscope 518–521
 Screw
 force for turning 135
 mechanical principle of 135
 Screw machines
 automatic 1094–1099
 automatic box-tools 1095
 cam and tool design, pointers 1098–1099
 drilling speeds and feeds 1095
 drills 833, 840
 forming speeds and feeds 1095
 forming tools 758–770
 forming tools with rake 758–764
 knurling 1094–1095
 reamers, stub 819
 reaming speeds and feeds 1095
 speeds and feeds 1095
 stock required for given production 1099
 thread rolling 1919–1922
 threading cams 1094
 Screw stock 422
 Screw threads and thread systems 1706–
 1712, 1754–1781, 1790–1858
 Acme 1792–1816
 American National form 1706
 angle test by wire method 1872–1875
 ANSI
 Acme 1792–1816
 buttress 1818–1824
 form or profile 1706
 head recesses 1577, 1623
 head types 1620–1621
 ANSI M profile 1755–1776
 allowances 1762–1764
 basic profile 1756–1757
 coarse pitch 1759–1760
 coated threads 1764–1765
 crest and root form 1756–1762
 data 1758
 design profile, M series 1756, 1759–
 1760
 designations 1774, 1776
 fine pitch 1761–1762
 formulas for limiting dimensions 1765

- Screw threads and thread systems *(continued)*
- lengths of engagement 1763–1766
 - limiting 1769–1780
 - limits and fits 1757
 - limits of size 1765
 - major diameter tolerances 1768
 - minor diameter tolerances 1764, 1767, 1774
 - pitch diameter tolerances 1766–1769
 - profile data 1758
 - symbols 1756
 - thread series 1761–1762
 - tolerance grades 1762–1765
 - ANSI MJ profile 1775–1778
 - ANSI M-profile
 - limiting 1781–1787
 - ANSI Unified 1706–1710, 1712–1754
 - basic dimensions 1740–1749
 - classes 1752–1753
 - definitions 1707–1712
 - designations 1754
 - internal and external profile 1713
 - standard series, tables of 1716–1739
 - symbols 1753–1754
 - thread form 1706, 1712–1714
 - British Standard
 - buttress threads 1825
 - ISO metric 1825–1834
 - pipe 1856–1858
 - UNJ profile 1825–1826
 - Whitworth 1836–1838
 - changing pitch slightly 1929–1930
 - classes of tolerance 1742–1753, 1801–1802, 1821–1823
 - cutting, change gears 1912
 - fractional ratios 1913–1914
 - definitions 1707–1712
 - designation of Unified threads 1716–1754
 - diameters of wires for measuring
 - American and Whitworth 1861
 - Dryseal pipe 1852–1853
 - electric socket and lamp base threads 1846
 - formulas for three-wire measurement 1860–1861
 - gages for screw threads 1877–1884
 - classification 1877–1878
 - for Unified screw threads 1877–1878
 - standard tolerances 1882–1884
 - grinding 1923–1927
 - centerless method 1926–1927
 - helix angle 1740–1749
 - hose coupling 1844–1845
 - inserts 1635
 - instrument makers' 1846
 - interference fit threads 1786–1791
 - International Metric thread system 1825
 - ISO metric 1825–1834
 - lag screw 1497–1498
- Screw threads and thread *(continued)*
- metric 1525
 - length of engagement 1489–1490
 - limits
 - Class 1A and 1B 1717–1739
 - Class 2A and 2B 1716–1739
 - Class 3A and 3B 1716–1739
 - Class 5 1786–1789
 - lock-nut pipe 1848, 1851–1852
 - Löwenherz 1825
 - measuring 1859–1877
 - metric series threads
 - ANSI M profile 1755–1776
 - ANSI MJ profile 1775–1778
 - British Standard ISO metric 1825–1834
 - micrometers for measuring pitch diameters 1859
 - microscope 1846
 - milling 1625, 1928–1930
 - classes of work 1929–1930
 - miniature 1781–1785
 - modified square thread, 10-degree 1817
 - multiple, designation 1754
 - National standard form or profile 1706
 - nonstandard small size 0000, 000, and 00 screws 1573
 - pipe
 - ANSI Standard 1846–1855
 - Dryseal 1852–1855
 - measuring 1872–1876
 - straight 1848–1852
 - taper 1846–1850
 - pitch, changing slightly 1929–1930
 - pitch, maximum when die cut 1929–1930
 - profiles 1860–1861
 - rolled threads 1846
 - rolling 1918–1922
 - in automatic screw machines 1919
 - saw-tooth 1817
 - selection of Unified threads 1752–1753
 - sharp V-type thread 1706
 - spark plugs 1840
 - standard series Unified threads 1715
 - strength of 1489–1491
 - stress areas 1482, 1489–1491, 1794
 - stub Acme screw threads 1793, 1811–1816
 - stub thread, 60-degree 1816
 - stub-Acme screw threads 1793
 - stud threads ??–1780|1781–1791
 - studs, tolerances 1788–1789
 - symbols used for standard 896–897
 - tap drill sizes 1889–1907
 - taper, measurement by wire method 1872–1876
 - thread forms 1706
 - trapezoidal metric threads 1779
 - Unified
 - allowances 1716–1739, 1750–1753
 - coarse thread series 1715–1740
 - coated 1750–1754

- Screw threads and thread *(continued)*
- combination of classes 1752–1753
 - crest clearances 1750–1753
 - design profile 1713
 - designation 1753–1754
 - dimensions 1716–1739
 - external and internal thread
 - forms 1706, 1712–1714, 1781–1783
 - fine and extra fine series 1715–1745
 - hole sizes for tapping 1754
 - limits 1716–1739, 1750–1753
 - miniature screw thread 1781–1785
 - selection 1752–1753
 - thread classes 1742–1745, 1750–1753
 - thread form, data and formulas
 - for 1713–1714
 - thread forms 1712–1713
 - thread minor diameter tolerances, M series 1764, 1767, 1774
 - thread series 1712, 1715
 - tolerances 1750–1754
 - UN and UNR 1712–1713
 - uniform 4-, 6-, 8-, 12-, 16-, 20-, 28-, and 32-pitch series 1715–1749
 - US Standard 1706
 - watch 1781–1785
 - wire method of checking 1860–1877
 - wire sizes for checking pitch
 - diameters 1861–1862
 - worm threads 2064–2066
- Screw threads and thread systems ANSI M profile
- design profile, M series 1759
 - designations 1764, 1767, 1774
 - limits of size 1775
- Screws
- and bolts 1492
 - British Standard
 - inch 1551–1554, 1586–1598, 1613–1619
 - ISO 1825–1834
 - metric 1555–1559, 1586–1595, 1613–1618
 - Whitworth 1551–1554, 1595–1598, 1619
 - British Unified 1595–1597
 - cap 1496, 1599–1604
 - cap, metric 1521
 - drive 1620–1621, 1635
 - grade markings for steel 1488–1489
 - heavy hex 1496
 - hex 1493–1494
 - lag 1497–1498, 1525
 - load to break threaded portion of 1490–1491
 - Metric
 - cap 1521
 - clearance holes 1532
 - designation 1532
 - diameters 1523
 - flange 1526–1527
- Screws *(continued)*
- formed 1522
 - heavy hex 1523
 - identification symbols 1532
 - ISO 1556–1560
 - ISO British Standard 1825–1834
 - materials and mechanical properties 1534
 - reduced body diameter 1524
 - socket 1613–1614
 - thread series 1532
 - self-threading 1620–1644
 - set 1606–1619
 - shoulder 1605
 - sockets for 1608, 1615
 - tap drills 1889–1907
 - thumb 1697, 1700–1701
 - Unified Standard 1492–1496, 1595–1597
 - wing 1697–1699
 - wood 1456
- Screws, jig and fixture
- button head 1617
 - heavy hex 1496
 - hex 1493–1494
 - load to break threaded portion 1490–1491
- Sealants 2463–2464
- gasket materials 2463–2465
 - pipe joining 2464–2466
- Sealing bearings 2198–2200
- Seasoning steel, sub zero 514–517
- Secant 83
- Secant modulus (plastics) 572–573
- Section lining, standard for drawings 606, 608
- Section modulus
- angles 2495–2497
 - for torsion 229, 258
 - formulas for various sections 217–227
 - I-beams 2489–2493
 - pipe 2507–2508
 - polar 229, 277–278
 - rectangles, table for 228–229
 - round shafts, table for 229–234
 - structural shapes
 - angles, steel 2497
 - channels, aluminum 2498
 - I-beams or S-shapes
 - aluminum 2498
 - steel 2493
 - wide flange, steel 2489–2492
 - steel 2494
- Segment
- circular 80–81
 - area 80–81
 - height for given angle and radius 80–81
- Seizing and cutting wire rope 344
- Self-threading screws 1620–1635
- cross recesses 1623
 - designations 1620–1621
 - drive type 1620–1622, 1624

- Self-threading screws *(continued)*
- head types 1620–1621
 - hole sizes for 1628–1635
 - self-tapping inserts 1635
 - thread and point types 1622–1623
 - thread cutting types 1620, 1623, 1625
 - thread forming types 1620–1622, 1624, 1626
 - torsional strength requirements 1635
 - types of 1620–1621
- Self-threading screws, metric 1635–1644
- designations 1635–1636
 - head types 1635–1636
 - hole sizes for 1640–1644
 - material 1639
 - recommended lengths 1638
 - thread and point types 1636
 - thread cutting types 1635–1639
 - thread forming types 1635–1638
- Sensitivity Factor 2044
- Sequence number, NC 1245
- Series, infinite 33–34, 97
- Set-screws
- American National Standard 1606–1610
 - British Standard metric 1613–1619
 - British Standard Whitworth 1619
 - fluted socket type 1612
 - headless 1606
 - hexagon socket type 1612–1618
 - holding power 1619
 - spline socket type 1612
 - square head type 1609–1610, 1619
- Sevolute functions 97
- Shackle and end-link chain 356
- Shaft deflection
- linear 280
 - torsional 277–280
- Shafts 275–284
- allowances and tolerances for fits 621–667
 - British Standard for fits 657–666
 - brittle materials, formulas for 283
 - checking for various conditions of 692–694
 - critical speeds of 283
 - effect of keyways on strength 283
 - factor of safety 276, 283
 - hollow 283–284
 - horsepower transmitted by 275–277, 280
 - linear deflection 280
 - maximum allowable working stress 282
 - moment of inertia, polar 229–234, 277–278
 - polygon type connections 2160–2161
 - round, section moduli 229–234
 - steel, diameters of 280
 - strength 275–277
 - taper ends, SAE Standard 2352
 - torsional
 - deflection 277–280
 - strength 275–277
- Shafts *(continued)*
- hollow vs. solid 283–284
 - transmission, design of 280–283
- Shanks
- brazing carbide tips to 1365–1366
 - brazing high-speed steel tips to 1360
 - hexagonal, for portable tools 1210
 - taper 906–917
- Shapes
- of grinding wheels 1142–1150
 - of mounted wheels and points 1204–1206
- Shaping wood 378
- Shaping, speeds and feeds 1044
- Sharp V-thread 1706
- Sharpening
- carbide tools 937
 - drills 936
- Shaving, gear teeth 2011–2013
- Shear
- formulas for 204
 - modulus 196
 - of various material 384
 - of various materials 196
 - of, G
 - plastics 573–575
 - spring materials 326–329
 - modulus of, G
 - plastics 575
 - properties 197
 - spring design 329
 - steel for hot-working 456
 - stress 195, 206
 - combined with tension or compression 206–207
 - in beams 207–210
- Shearing strength
- cast iron 476
 - rivets 1461–1462
 - steels 476
 - wrought iron 476
- Shearing strength wood 376
- Sheaves
- for V-belt drives 2373–2420
 - for wire rope 332, 334
- Sheet metal
- and wire gages 2499–2503
 - bending allowances 1304–1310
 - screws 1620–1635
- Sheet sizes for drawings 606
- Shell
- blanks, diameters 1304–1307
 - mills 778
 - molding 1336–1337
 - reamer arbors, driving slots and lugs for 823
 - reamers 822
- Shells, plates and cylinders, strength of 268
- Shielded metal arc welding (SMAW) 1378–1382
- Shielding gases 1364–1366

- Shipping measure 2518
Shocks, stresses in springs 258
 stresses produced by 257–258
Shore's scleroscope 518–521
Shoulder screws 1605
Shrinkage
 allowance, patterns 1345
 investment casting 1345
Shrinkage allowance, patterns 1339–1344
Shrinkage fits 623–627, 631–632, 640
Shut height, power press 1302–1304
SI
 binary prefixes 2533
SI units
 in strength of materials calculations 195
 metric 116
Side milling cutters 774
Sigma (standard deviation) 1217–1218
Significance of accuracy 1216–1219
Signs and abbreviations
 mathematical 2
 scientific and engineering 2554–2555
Signs of trigonometric functions 84
Silicon
 carbide grinding wheels 937–938
 in steel (welding) 1362–1363
Silver
 bearings 2241
 brazing filler alloys 1356
 plating 1450
Simple
 indexing 1947, 1979–1985
 proportion 22
 stresses 204–206
Simpson's rule 57–58
Sine 83
Sine bar constants 675–681
Sine bar, use of 673–682
Sine law of 84
Single tooth contact 2000
Single-angle milling cutters 777, 783
Single-point cutting tools 723–746, 859–864
 angle tolerances 740–746
 carbide tips and inserts for 738–746
 chipbreakers 728–730
 definitions and terms 723–726
 end cutting edge angle 728
 indexable inserts 729–732
 insert toolholders 730–738, 1281–1284
 lead angles 727–728
 nose radius 728, 745
 numerical control tool
 compensation 1281–1284
 planing tools 730–731
 rake angles 726–728
 relief angles 726
 relief angles for thread cutting 1910–
 1911
 side cutting edge angles 727–728
 tip overhang 740
 tool contour 723
Single-point cutting tools (*continued*)
 tool holders, indexable inserts 730–738
Sinking funds 27
Sintered carbide tools, ANSI Standard 738,
 747–757
 tool materials 979–981
Sintered metal bearings 2242–2245
Sixty (60)-degree stub threads 1816
Sixty (60)-degree V-belts 2407
Size factor cover 2044
Sizes of sawn lumber 378
Skin effect in castings 1341
Slate
 cutting speed for 1044
 specific gravity and weight 370
Sleeve bearings 2204–2219
Sleeves, Morse taper 915
Slenderness ratio of columns 261
Slides, measuring 682–683, 690
Slings and fittings for wire rope 345–348
Slings, strength of rope and chain 354–355
Slipping clutches, couplings 2332
Slitting saws, metal 776
Slots for T-bolts, ANSI Standard 1645
Slug 114
SMAW (shielded metal arc welding) 1378
S-N diagrams 197–198
Socket
 ANSI hexagon and spline 1608
 head, screw type
 British Standard metric 1613–1618
 cap 1601–1604, 1614
 drill and counterbore sizes for 858,
 1602
 keys and bits for 1611
 set 1612–1618
 shoulder 1605
 reamers, Morse taper 824
 taper shank 906–917
 threads for electric 1846
 wrench clearances 1511
Soldering 1352–1355
 alloys for 1353
 aluminum 1354
 fluxes 1352–1354
 magnesium 1352–1354
 methods 1352–1355
 stainless steel 1352–1354
 ultrasonic fluxless 1352–1355
Solders 1352–1353
 brazing 1354–1359
 silver 1352–1353
Solid figures, volumes and dimensions 66–
 71
Solid film lubricants 2318
Solid ring
 polar moment of inertia 145
Soluble oils for machining operations 1107
Solution heat treatment 480
Sorbite 493
Sound level specifications 1297

- Space cutters, roller chain sprockets 2437, 2440–2441
- Spacing holes on jig borer 953–970
- Spade drills and drilling 865–871
 feed rates for 868–869
 geometry of 865–867
 power consumption and thrust for 870
- Spandrel
 area 64
 center of gravity 138
- Spark plugs, screw threads 1840
 British Standard 1840
 taps 876, 891
- Spatter, (welding) 1381–1387
- Specific gravity 370–371
 conversion to, from Baumé's hydrometer 371
 gases 371
 liquids 371
 miscellaneous substances 370
 of various metals 370
 of various substances 370
 oils 2312–2313
 plastics 380
- Specific heat 364
 gasses 365
 of various metals 368–369
- Speed reducers, motors, built-in 2452–2453
- Speeds
 calculating cutting speeds 985–990
 critical, of rotating shafts 283
 pulleys, rules for calculating 2370–2371
 rpm for different diameters and cutting speeds 985–990
- Speeds and feeds, machining 978–1046
 abrasive belt grinding 1193
 bandsawing 1103, 1105–1106
 CBN grinding wheels 1157
 cutting 597–599, 868, 983, 985, 1040, 1094, 1103, 1105–1106
 cylindrical grinding, high-speed 1178
 drilling 1012–1039, 1095
 diameters and rpm 986
 feeds for spade drills 868–869
 end milling 1009
 face milling 1009
 form-turning 1095, 1111
 general 978, 1040, 1094–1095
 grinding wheels
 maximum peripheral speeds 1173
 truing and dressing 1160–1161
 wheel and work speeds 1925
 grinding with diamond wheels 1169
 honing 1195–1198
 milling 991, 1009–1012
 nonferrous metals 1116–1119
 plastics 597–599
 reaming 1012–1040, 1095
 reaming and threading 991
 rotary burs and files 1433–1434
 sawing
- Speeds and feeds, machining (*continued*)
 band 1103, 1105–1106
 circular 1044
 shaping 1044
 slit and slot milling 1009, 1012–1027
 superalloys 1008–1009
 surface grinding 1190–1192
 tables, how to use 991–994
 tapping and thread cutting 1030–1039, 1041–1043, 1095, 1886–1887
 thread rolling 1920–1922
 titanium and alloys 1007
 tool life 982–983, 994
 adjusting 755–757, 1004–1005, 1009, 1012, 1028
 tool steels
 drilling reaming, and threading 1035
 milling 1018–1019
 turning 1000
 turning 991, 995–1009
 carbon and alloy steels 996–999
 copper alloys 1006
 ferrous cast metals 1002–1003
 hard-to-machine materials 1008–1009
 light metals 1007
 speeds and feeds 995–1009, 1095
 stainless steels 1001
 superalloys 1008–1009
 titanium 1007
 tool steels 1000
- Sphere
 hollow
 center of gravity 141
 radius of gyration 150
 polar moment of inertia 145
 radius of gyration 150
 volume 69
- Spherical
 sector
 center of gravity 141
 polar moment of inertia 145
 volume 69
 segment
 center of gravity 141
 polar moment of inertia 145
 segment volume 69
 shells, strength to resist internal pressure 271–272
 wedge volume 70
 zone volume 70
- Spherical and rectangular coordinates, relationship 37
- Spherical coordinates 37
- Spherical shell, thin 150
- Spherical surface
 center of gravity 138
- Spheroid segment of
 center of gravity 141
- Spheroidal graphite iron 476, 1332
- Spheroidize, annealizing 415
- Spheroidizing 414, 495–497

- Spikes and nails, standard 1455
- Spindle
 - for portable tools 1207–1210
 - function, NC 1251
 - noses 920–924, 1251, 1285
- Spiral bevel and hypoid gears 2052
- Spiral bevel gears 1998, 2051
 - applications 2051
 - tooth contact 2050
- Splines 2129
 - application factors 2141
 - comparison of symbols 2150
 - data and reference dimensions 2140
 - fatigue-life factors for 2142
 - formulas for SAE standard 2160
 - machining tolerances and variations 2153
 - SAE standard spline fittings 2160
 - SAE standard splined fittings 2157–2160
 - terms, symbols, and drawing data 2139
 - variations 2135
- Splines, involute 2126–2155
 - milling 799
 - socket keys and bits 1611
 - straight-sided 2157–2160
- Spray transfer (welding) 1364–1365
- Spraying process, flame (metal) 1351
- Spring 285–332
 - arbor diameters for 332
 - Belleville 326
 - clock 326
 - compression, formulas for 299
 - conical compression 326
 - constant force 326
 - copper-base spring alloys 288–289
 - deflections for
 - compression 302–305
 - extension 302–305
 - torsion 321–324
 - design data 296–332
 - elevated temperature stresses 295–296
 - endurance limit for spring materials 295–296
 - extension 307–311
 - extension spring design 309–311
 - failure in 331
 - flat 326
 - heat treatment of 326–329
 - helical
 - compression spring design 297–306
 - helical, shock stresses produced in 258
 - high-carbon spring steels 286
 - index 296–298
 - materials 286–290
 - miscellaneous 326
 - moduli of elasticity 326
 - motor 326
 - music wire arbor diameters 332
 - nickel-base spring alloys 288–290
 - pins 1663–1664
 - shock stresses produced in helical 258
 - spiral 326
- Spring (continued)
 - stainless spring steels 287–288
 - steels for 286–288
 - stresses 291–297
 - produced by shocks 258
 - tolerances
 - for compression and extension 310–314
 - for torsion 325–326
 - torsion
 - bars 326
 - design 314–325
 - modulus 326–329
 - volute 326
 - wire
 - diameters for 286
 - maximum working temperature 289
 - tensile strength 385
- Sprockets
 - chain transmission 2421–2444
 - idler 2436
 - roller chain 2423–2442
- Spur gearing 2002–2033
 - AGMA tolerances for fine pitch gears 2037–2041
 - American National Standard tooth forms 2004–2008
 - angular backlash 2042
 - backlash 2036–2042, 2103
 - basic dimensions 2010–2012
 - blanks for fine pitch gears 2033–2034
 - caliper measurement of tooth 2020
 - cast 2113–2117
 - center distance
 - calculations 2010–2015
 - variable 2010, 2012–2015
 - checking gear size 2094–2112
 - chordal
 - addenda and thicknesses for milled full-depth teeth 2015–2017
 - addendum 2017–2018
 - measurement 2108–2111
 - thickness 2015–2017, 2062
 - circular
 - pitch system 2002–2015, 2022
 - thickness for given outside diameter 2014–2024
 - composite
 - error inspection 2042
 - teeth 2004–2010
 - contact
 - diameter 2028–2032
 - highest point of single tooth 2033
 - lowest point of single tooth 2029–2032
 - ratio 2024–2027, 2029
 - data on drawings 2033–2036
 - diameters for hobbing, preshaving, and shaping 2011
 - diametral pitch
 - system 2002
 - diametral pitch shown full size 2002

- Spur gearing *(continued)*
 dimensions, formulas for 2004
 drawing data 2033–2036
 enlarged pinions 2019–2028, 2077–2080
 external 1998
 Fellows stub tooth systems 2010
 fine-pitch 2008, 2024–2027, 2033–2034, 2077–2079
 formulas for basic dimensions 2131
 full-depth, teeth 2004–2010, 2015–2017
 gear milling cutters, series of 2017–2021
 metric module 2021
 gear tooth parts 2005–2010
 checking 2094–2112
 German standard tooth form 2090
 hob tip radius, maximum 2030–2033
 interference, avoiding 2019–2022
 internal 1998, 2047–2048
 involute curve properties 2002
 measurement of tooth with caliper 2020
 measurement over pins 2094–2112
 milling cutters for 2021
 metric module 2021
 module system 2090–2093
 nonmetallic 601–604, 2118–2122
 outside and root diameters 2011, 2022
 pin method of checking 2094–2112
 pitch diameters, tabulated 2022
 profile checker settings 2030–2031
 reduced gear 2019–2028
 replacement gear dimensions 2122–2125
 root and outside diameters 2011, 2022
 set center distance 2010–2015
 shaving 2011–2013
 steels for industrial 2113–2117
 tooth
 dimensions 2005–2010
 forms 2004–2010
 proportions 2008
 thickness allowance for shaving 2011–2015
 thickness measurement 2014–2022, 2039–2040, 2108–2111
 true involute form (TIF) diameter 2030–2033
 undercut, avoiding 2019–2028
 undercut, limit for hobbled gears 2030–2033
 wire method of checking 2094–2108, 2111–2112
- Square
 area 60
 circles of area equal to 79
 distances across corners 82
 of wire diameters 330
 prism volume 66
 recesses, for machine screws 1577
 for self-tapping screws 1623
 roots of numbers 17
- Squeeze casting 1337–1338
- Squirrel cage induction motors 2445–2446
- S-shapes, structural steel 2493
 moment of inertia 2493
 radius of gyration 2493
 section modulus 2493
 weight per foot 2493
- Stabilizing gages 514–515
- Stainless steels 406, 413, 425, 428
 characteristics and applications 425
 compositions 413
 cutting, flame 1428
 mechanical properties 439
 soldering 1352–1354
 ultrasonic 1352–1354
- speeds
 for drilling, reaming, and threading 1036
 for milling 1019–1020
 for turning 1001
- strength 476
- Stamping
 blank diameters 1304
 die clearances 1301
 drawing operations 1302–1304
 fine blanking 1312–1314
 lubricants for 1302
 pressures required 1302–1304
 punches, dies and presswork 1301–1311
 steel rule dies 1315–1317
- Standard
 deviation 1216–1218
 steels 403, 406–418, 420–428, 430–436, 439–443
 classification 403, 406–410
 hardenability 415–416
 hardness 415–416
 numbering system 409, 413
 wire gage (SWG) 2499–2500
- Standards, NC 1226
- Static 113
 balancing 167
 equivalent load, bearings 2297–2301
 load rating, bearings 2297–2301
- Statistical tolerance 617
- Stayed surfaces, flat 268
- Steel
 alloy
 compositions of SAE 411–412
 general properties 432–436
- Bessemer 422
- carbon
 SAE compositions 409, 420–422
 steel structure 484
 carbon steel structure 483
 carburizing grades 504–505
 carburizing methods 498
 case hardening 497–505
 cast 1332–1335
 castings 1332
 chromium
 compositions 413, 428
 nickel austenitic 413, 425, 428

- Steel *(continued)*
- classification 406
 - cobalt high-speed 856–857
 - cobaltcrom 508
 - color of heated 495
 - columns, pipe 264–265
 - compositions
 - for tools 464–476
 - of SAE 409–412
 - corrosion-resisting 425–428
 - deep-drawing 420
 - Founders' Society of America 1333–1340
 - free-cutting 422
 - manganese 447
 - stainless 425
 - gages 456
 - gear castings 2113–2117
 - gearing, industrial 2113–2117
 - hardenability 415–416
 - hardening 479, 485–492
 - hardness 415–416
 - and tensile strength relationships 521
 - of heat-treated 432, 473–476
 - heat treatment 414–415, 479–517
 - of high speed steel 508–514
 - high-speed 451
 - high-strength, low-alloy 409–410, 440–443
 - hot-working, for dies, shears 452–454
 - hypereutectoid 483
 - hypoeutectoid 483
 - induction hardening 500
 - manganese, SAE compositions 409–412, 447
 - molybdenum
 - compositions 409–412, 425, 428
 - heat-treating 511–512
 - high-speed 457–458, 510–511
 - nickel
 - chromium, SAE compositions 409–412, 425, 428
 - nickel, SAE compositions 425
 - SAE compositions 411–412
 - nitriding 417, 498
 - numbering systems for 409–412
 - oil-hardening types 464
 - pipe
 - ANSI standard 2505
 - columns, allowable concentric loads 264–265
 - properties of heat-treated 452–454, 473, 476
 - quality
 - classification 418
 - variations 418
 - rivets 1458
 - rolled, shape designations 2488
 - rule dies 1315–1317
 - SAE
 - compositions 409–412
- Steel *(continued)*
- heat treatments recommended 443, 503–505
 - specification numbers 409–410
 - screw stock 422
 - sheet, standard gage 2501–2502
 - silicon-manganese, SAE
 - compositions 411–412
 - stainless 413, 425, 428
 - strength 473–476
 - and hardness data 432–436, 473, 475–476
 - of heat-treated 473, 475–476
 - structural shapes 2488–2497
 - subzero treatment 514–517
 - taps 452–456, 1885–1886
 - tool 444–458, 460, 462, 464–471
 - die 452
 - of different types 452–456
 - tungsten
 - compositions 458, 460
 - heat treating 508–511
 - high-speed 458–460, 462, 508–511
 - twist drill 856–857
 - vanadium 447
 - wrought 2504
 - Stellite alloy 981
 - Step bearings 2219, 2224–2227
 - Stock, amount required for screw machine production 1099
 - Stoke 2201–2202, 2312–2313, 2319
 - Straight
 - line column formula 261
 - pins 1653–1655
 - pipe threads 1848–1852
 - Straight bevel gears 1998
 - Strain
 - lateral 196
 - longitudinal 196
 - ratio of 196
 - Strength
 - hollow vs. solid shafts 283–284
 - of polygon connections 2161
 - of screws and bolts 1490–1491, 1534, 1559–1560
 - riveted joints 1459
 - tensile 196
 - wood 376
 - ultimate 196
 - yield
 - perforated metal 235
 - Strength of materials 195
 - angles, lengths of bent 2488
 - beams 236, 249
 - shock stresses in 257–258
 - channels, elements of 2494, 2498
 - columns 261–267
 - AISC formula 267
 - AREA formula 261
 - Euler formula for 261–262, 266–267
 - Gordon formula 261, 263

- Strength of materials *(continued)*
- Johnson formula for 262
 - combined stresses 206–210
 - compression 196
 - critical speeds of shafts 283
 - curved beams 254–257
 - cylinders 270–274
 - definitions 195–196
 - deflection of beams 236, 239, 241–242, 253–254
 - Euler formula 261–263, 266–267
 - factors of safety 199
 - ferrous metals 473, 475–476
 - flat plates 268–270
 - heat-treated steels 432–436
 - hoop stress 585–586
 - thick-walled tube 584–585
 - thin-walled tube 584–585
 - influence of temperature 475–478
 - Izod impact 380, 432–433
 - J. B. Johnson column formula 262, 266–267
 - keyways in shafts 283
 - linear deflection in shafts 280
 - mechanical properties 195–196
 - metals, properties of 473, 475–478
 - miscellaneous materials 478
 - modulus
 - elasticity 196
 - shear 196
 - moment of inertia
 - built-up sections 217
 - table 217–227
 - nonferrous metals 473, 475, 477
 - perforated metals 235
 - pipe columns 264–265
 - plates, shells, and cylinders 268–274
 - polar
 - moment of inertia 229, 277–278
 - section modulus 229, 277–278
 - rails 259
 - Rankine, column formula 261, 263
 - rings, stresses and deflections 215
 - section moduli tables 217–234
 - shafts 275–284
 - brittle material formula for 283
 - critical speeds of 283
 - effect of keyways on strength of 283
 - former American Standard design code for 280–283
 - horsepower transmitted by 275–277, 280
 - torsional strength of 275–277
 - shear 195, 197
 - shells, spherical 271–272
 - shocks, stresses produced by 257–258
 - simple stresses 204–206
 - springs, shock stresses in 258
 - steels 473, 475–476
 - straight-line column formula 261
 - stress 117, 195
- Strength of materials *(continued)*
- analysis 521
 - areas of screw threads 1489–1491
 - concentration factors 200–201
 - filleted shaft in tension 201
 - filleted shaft in torsion 201
 - grooved shaft in bending 203
 - grooved shaft in torsion 203
 - shaft with shoulder in bending 202
 - shaft with transverse hole in bending 204
 - shaft with transverse hole in torsion 202
 - relieving 415
 - working 200
 - struts or columns 261–267
 - taper pins, strength of 215–216
 - temperature effects 475–478
 - tensile
 - strength 376, 379, 385
 - stress 195
 - torsional strength of shafting 275–277
 - tubes 272–274
 - working stresses 200
 - yield 376, 379, 385
 - Young's modulus 196
- Strength of wire rope 334–341
- Stress 117
- alternating 197–198
 - area of thread 1482, 1490–1491, 1794
 - bending in flywheels 179
 - centrifugal in flywheels 178
 - combined 206–210
 - concentration factors 200–204
 - filleted shaft in tension 201
 - torsion 201
 - grooved shaft in bending 203
 - torsion 203
 - shaft with
 - shoulder in bending 202
 - transverse hole in bending 204
 - transverse hole in torsion 202
 - contact, in cams 2184
 - cyclic 197
 - hoop in flywheels 178–179
 - in beams 204–210, 236, 241–242, 249, 251–258
 - in bolts when tightening 1477–1487
 - in flywheels 183
 - in involute splines 2142
 - in loaded ring 215
 - in rotating disks 183
 - in shafting 280–283
 - in splines
 - allowable compressive 2145
 - allowable contact stress 2045
 - allowable shear 2144
 - allowable tensile stress 2145
 - in springs 258, 291–297

- Stress *(continued)*
- produced by shocks 257–258
 - shear 206
 - in beams 207–210
 - simple 204–206
 - spline teeth
 - compressive 2144
 - superposition of 206
 - three-dimensional, or triaxial 210–212
 - working, of various materials 200
- Stress concentration factors 200–201
- filleted shaft in
 - tension 201
 - torsion 201
 - grooved shaft in
 - bending 203
 - torsion 203
 - shaft with
 - shoulder in bending 202
 - transverse hole in
 - bending 204
 - torsion 202
- Stress relieving 415
- Stress-strain curves 195–196
- Structural shapes
- aluminum 2498
 - steel 2488–2497
 - angles, properties of 2495–2497
 - channels, properties of 2494
 - I- or S-shapes, properties of 2493
 - standard designations 2488
 - strength 476
 - wide flange, properties of 2489–2492
- Structure of Carbon Steel 483
- Struts or columns, strength of 261–267
- Stub Acme screw threads 1793, 1811–1816
- alternative 1816
 - ANSI Standard 1811–1815
 - designations 1814
 - formula for determining diameters 1812
 - limiting dimensions for 1813–1814
 - thread data 1815
 - thread form 1793, 1812
 - wire sizes for checking 1872–1874
- Stub screw machine reamers 819–820
- Stub threads, 29- and 60-degree 1929–1934
- Stub tooth gearing 2005, 2010
- Fellows 2010
 - former American Standard 2005, 2010
 - outside and root diameters 2004, 2011
- Stub's iron and steel wire gage 2499–2500
- Stud
- British 1551, 1562
 - threads 1786–1791
- Studs
- British
 - drive 1659, 1662
 - Subprogram, NC 1256
 - Subroutine, NC 1256–1258
 - Subzero treatment of steel 514–517
- Superalloys, speeds for turning, milling and drilling 1008–1009
- Superhard tool materials (CBN) 754–757, 982, 1008–1009, 1140, 1157, 1166
- Surface
- finish and hardness of bearings 2199
 - grinding 1185–1192
 - advantages 1185
 - common faults and possible causes
 - in 1191–1192
 - table of 1191
 - principal systems 1186, 1189
 - process data for 1190
 - selection of grinding wheels for 1139–1150, 1185–1187, 1190
 - hardening
 - electron beam 503
 - laser 503
 - of revolution, area 57
 - roughness
 - measurements 703–704
 - produced by common production methods 702–703
 - produced by laser cutting 1415–1416
 - relationship to tolerances 702–704
 - speeds, diameters and rpm
 - grinding wheels 1171, 1174
 - pulleys and sheaves 985, 987–990, 1908–1909
 - speeds, diameters and rpm cutting speeds
 - formula 985–990, 1908
 - texture 697–702
 - measurement by light wave interference bands 695–696
- Surface coatings 1444–1451
- Surface condition factor 2044
- Surface finish
- differences between ISO and ANSI symbology 711
- Surface texture 699
- applying symbols 706–708
 - castings 708
 - comparing measured values to specified limits 715
 - control and production 697
 - cutoff for roughness measurements 704
 - drawing practices for symbols 704–705
 - error of form 697
 - flaws 697
 - graphical centerline. 699
 - instruments 704
 - instruments of measurements 704
 - lay 697, 708
 - lay symbols 709
 - measurement instrumentation 704
 - measurement of 697–702
 - measurements
 - area averaging methods 704
 - max rule 715
 - non-contact instruments 704
 - probe microscope 704

- Surface texture *(continued)*
- skidless instruments 704
 - 16% rule 715
 - profile 699
 - measured 699
 - modified 699
 - nominal 699
 - real 700
 - total 700
 - variation 2129, 2136
 - root mean square 702
 - roughness 697
 - roughness average (Ra) 701–702, 707
 - roughness evaluation length 702
 - roughness parameters 701
 - roughness profile 700
 - roughness sampling length 701
 - roughness spacing 700
 - roughness topography 700
 - sampling length 700–701
 - spatial resolution 700
 - standard roughness sampling lengths 707
 - symbols 606, 705–706
 - symbols, proportions of 706
 - system height resolution 700
 - topography 700
 - measured 700
 - modified 700
 - traversing length 701
 - use of symbols 706
 - valley 700
 - waviness 699
 - evaluation length 700, 702
 - height 702, 708
 - long-wavelength cutoff 700
 - parameters 702
 - profile 700
 - sampling length 700–701
 - short-wavelength cutoff 700
 - spacing 700
 - topography 700
 - Surface texture symbols
 - drawing practices for 705
 - Surveyor's measure 2517, 2523
 - SUS (Saybolt Universal Seconds) 2313, 2319
 - Swing frame grinding 1192
 - Swiss pattern files 1432–1433
 - S-word, NC 1251
 - Symbols
 - ANSI Y14.5M Standard geometric characteristic engineering drawing 609
 - datum referencing 614
 - section lining 606, 608
 - applying surface texture 706–708
 - arc and gas welding 1393–1401
 - brazing 1361
 - concentricity, ANSI 609, 1223
 - diameter, ANSI 609, 1222
 - diamond wheel marking 1163–1166
- (continued)*
- Symbols *(continued)*
- drawing practices for surface texture 704–705
 - fits 631
 - Greek 2554
 - grinding wheel markings 1141–1142
 - involute splines 2129, 2139
 - mechanics 115
 - nondestructive testing 1408–1409
 - parallelism, ANSI 609, 1223
 - perpendicularity, ANSI 609, 1224
 - roundness, ANSI 609, 1222
 - runout, ANSI 609, 1224
 - screw thread, for tap marking 896–897
 - surface profile, ANSI 609, 1222
 - surface texture 704–708
 - tolerances 642–644
 - total runout, ANSI 609, 1224
 - welding 1393–1409
- Symbols and abbreviations 2, 2554–2555
- Synchronous belts 2407–2419
- System of measurement
 - absolute 114
 - gravitational 114
- System, flexible manufacturing, NC 1234
- Système International d'Unites
 - in strength of materials calculations 195
- Système International d'Unites 2520–2524
 - definition of units 2523–2524
 - in mechanics calculations 116–118
 - use of 113–114, 116–118
-
- ## T
- Tangent 83
- Tangent plane 2001
- Tangential force 2044
- Tanks
 - contents at given level 58–59
 - cylindrical, capacity in gallons 58–59
 - quenching bath 490–491
- Tantung alloy 981
- Tap drill diameters 1889–1908
 - Acme 901
 - British Standard ISO metric 1901–1902
 - cold form tapping 1905–1907
 - effect of diameter when tapping 1889–1890
 - machine screw sizes 1900
 - pipe taps 1907–1908
- Taper
 - keys 2342–2354, 2359–2364
 - measurement methods 682–686
 - per foot and corresponding angles 684
 - pin reamers 826, 1657
 - pins, standard 1655–1658
 - drills for 1655–1658
 - strength 215–216
 - pipe taps 879–881, 894
 - pipe threads 1846–1850

- Taper
reamers
Brown & Sharpe 825
Morse 824
shaft ends, SAE Standard 2352
- Tapered
land thrust bearing 2218–2219, 2227–2232
roller bearings 2252–2254
roller thrust bearings 2252–2254
- Tapers
American (ANSI) Standard 906–918
applications of standard 917
British Standard 907–908
Brown & Sharpe 906, 915–916
collets 971–973
gages for self-holding 914
Jacobs 919
Jarno 906, 917
machine tool spindles 917
measuring with
sine bar 674
V-block and sine bar 682
milling machine spindles, arbors and spindle noses 920–924
Morse 906–917
stub taper shanks 907–908
rules for figuring 685
self-holding and self-releasing 906–914
steep machine 913, 918
- Tapping and thread cutting 1885–1917
automatic screw machine 1095
British Standard drill sizes 1901–1903
cold form 1904–1907
cutting oils 1110
cutting speed for 1030–1039, 1041–1043
high-speed CNC 1908–1909
holes
for tapping miniature screw threads 1901–1902
sizes before tapping, Unified threads 1889–1902
lubrication 1110
maximum pitches of die cut threads 1929–1930
power required for pipe taps 1907–1908
removing a broken tap 1905–1908
specific materials 1887–1890
speeds 1030–1039, 1041–1043, 1095, 1886–1887
square threads 883, 887–890, 903
tap drills
Acme threads 901
clearance drills for machine screws 1900
diameters 1889–1890, 1907–1908
for American form threads 1898–1900
for ISO metric threads 1903
tap thread H- and L-limits 879–880, 896–897
- (continued)
- Taps 872–875
Acme 898–901
adjustable 901
ANSI Standard 872–898
British Standard ISO metric series 902–903
collapsing 901
cut thread limits 876–882, 891
definitions 872–875
fits, classes obtained 895
fractional inch sizes 876–878, 891
ground thread limits 877–883, 892
H- and L-limits 879–880, 896–897
hand, dimensions of standard 875, 883, 888–892
hand, types of 872
limit numbers for ground-thread taps 897–898
machine screw 883–893
marks or symbols for identifying threads on taps 880, 896–898
metric sizes 876, 883–893
multiple-thread taps, marking 898
nitriding of 1885–1886
nut 872, 884, 890–891
pipe 872, 879–882, 894
power for driving 1907–1908
tap drills for 1907–1908
taper 879–882, 894
pitch increased to compensate for shrinkage 1929–1930
pulley 872, 884, 890
rake angles of 1886–1887
removing broken 1905–1908
selection of 1885–1887
serial 1885–1886
sparkplug 876, 891
spiral
fluted 883, 886, 892, 1885–1886
pointed 885–893, 1885–1886
square thread 898–901
steel for 456, 1885–1886
straight fluted 875, 883, 888–889, 892
straight pipe 879–882, 894
surface treatment of 1885–1886
terms 872
thread series designations 896–897
tolerances 876–897
types of 872
Unified thread form 1706
- Tar, specific gravity 371
- Taylor
principle in grinding 606
tool life equation 992
- T-bolts and T-slots, ANSI Standard 1645–1646
- tebi 2533
- Teflon (TFE) bearings 2242, 2245
- Temper designations, aluminum alloy 543–546

- Temperature
 absolute 2514
 bearings 2204–2211
 boiling points, various substances 364
 changes in length due to 668
 critical, heat treating of steel 480, 483–484
 effect on working stresses, of
 springs 295–296
 Fahrenheit and Celsius
 (Centigrade) 2514–2516
 ignition 368
 influence on strength of metals 475–478
 judging by color, steel 495
 maximum operating
 ceramics 379
 plastics 380
 melting point metals 368–370
 of carbon dioxide, solid 623
 of freezing mixtures 367
 of ignition, various materials 367
 of lead bath alloys 494
 of nitrogen, solid 623
 required to develop tightening stress in
 bolt 1480–1481
 Temperature criterion 2045
 Tempering 414–417, 482, 493–495
 double 494
 steel 414, 493–495
 Ten-degree modified square thread 1817
 Tensile
 modulus (plastics) 380, 572–573
 strength 196–197
 stress 195
 Tensile strength
 aluminum alloys 550–555
 ceramics 379
 copper alloys 526–542
 copper-beryllium alloys 566
 copper-silicon alloys 565
 ferrous and non-ferrous metals and metal
 alloys 473, 475–477
 heat-treated steel 432–436
 Investment casting alloy 381
 iron and steel 473, 475
 magnesium alloys 560
 nickel 562–563
 stainless steel 439
 steel 430–436, 441
 relation to hardness 473–477, 521–524
 titanium alloys 564
 wood 376
 Thermal
 conductance 366
 conductivity 366, 368–370
 contraction 623
 cracking of cutting tools 1111
 energy 2514
 expansion coefficients 368–370, 379–380, 579, 668
 stresses 585–586, 668
 Thermal flash factor 2045
 Thermometer scales 2514–2516
 Thicknesses, preferred
 metal products 2503
 uncoated metals and alloys 2501
 Thin flat plate 148
 Thin spherical shell 150
 Thread
 Acme 1792–1816
 angle, wire method of testing 1872
 change gears for lathe 1912–1916
 for fractional output 1913–1914
 modifying the quick change gearbox
 output 1913–1916
 chasing, cutting speeds for 1030–1043
 checking by three-wire method,
 tables 1866–1868, 1872
 cutting 1910–1916
 numerically controlled 1262–1263,
 1908–1909
 square 898–901
 designation symbols for 896–897, 1752–1754
 on taps, marks and symbols for
 identifying 896–897
 dies, maximum pitches 1930
 grinding 1923–1927
 accuracy obtainable 1923
 centerless method 1926–1927
 crushing method of forming
 wheels 1926
 from the solid 1924–1927
 number of wheel passes 1924
 truing wheels 1925
 wheel and work rotation 1925
 wheel grain size 1926–1927
 wheel hardness of grade 1926–1927
 wheel speeds 1925
 wheel types for 1923–1926, 1928
 work speeds 1925
 milling 1928–1930
 changing pitch of thread slightly 1929
 classes of work for 1929–1930
 multiple cutter method 1928–1929
 on numerically controlled
 machines 1262–1263, 1908–1909
 planetary method 1929
 single cutter method 1928
 rolling 1918–1922
 advantages of process 1918
 automatic screw machines 1919
 blank diameter 1918–1919
 diameter of threading roll 1919
 dies
 cylindrical 1918–1919
 flat 1918
 steels for 456
 dies, flat 1918
 machines used 1918
 precision thread rolling 1918–1919
 production rates 1918–1919

- Thread *(continued)*
 speeds and feeds 1920–1922
 steels 1918–1919
 screws 1620, 1623, 1625
 self-forming screws 1620–1622, 1624, 1628
 single-point cutting tools for 692–694
 stress area 1482, 1490, 1794
 symbols for taps 896–897
 tap drill sizes 1889–1898
 tools
 angles of sides for given clearance and helix angles 1910
 for square threads 898–901
 relief angles for single-point 1910–1911
 Threading cam, screw machine 1094, 1098
 cutting speeds, threading dies 1094
 Three-dimensional stress 210–212
 Three-wire measurement of screw threads 1860–1877
 Throw away carbide inserts 730–732
 Thrust bearings 2250–2254
 allowable loads 2220
 ball 2250–2254
 flat plate type 2218–2224
 plain 2218–2235
 rated life 2290–2296
 roller 2251–2252
 static equivalent load 2301–2302
 static load rating 2300–2301
 step type 2218–2219, 2224–2227
 tapered land type 2218–2219, 2227–2232
 tilting pad type 2218–2219, 2232–2235
 tolerances 2261–2262
 Thumb screws, flat-head type 1697, 1700–1701
 Tilting pad thrust bearing 2218–2219, 2232–2235
 Tin
 plating 1451
 tin lead, plating 1446
 Tin-base alloys, die casting 1343
 Tin-bronze bearings 2238–2242
 Tin-lead alloys for soldering 1353
 Tip relief 2001
 Titanium and titanium alloys
 cutting speeds for turning, milling, and drilling 1007
 properties 561, 564
 Titanium carbides as cutting tool materials 747–752, 980
 Titanium Metals Corp. 564
 T-nuts, ANSI Standard 1647
 Toggle joint 133
 Tolerance
 bilateral 613
 geometric 613
 unilateral 613
 zone symmetry 613
 Tolerance grades, relative to machining processes 630, 657
 Tolerances
 ANSI Standard 630
 bilateral and unilateral 621–622
 symbols 609, 642–644, 1221
 application 622
 ball and roller bearing 2255–2266
 compression spring 310–313
 cylindrical fits 621–667
 defined 621
 designation of limits and fits 642–644
 dimensions on drawings 621–622
 drilled holes 856–857
 extension spring 310–314
 gages
 direction of tolerances on 622
 thread 1882–1884
 gear, composite tooth to tooth 2042
 gear, composite total 2042
 hand taps 876–879, 891
 honing 1199
 how to apply 622
 indicating on drawings 609–611, 622
 involute splines, inch 2126–2134
 involute splines, metric 2148–2153
 keys and keyways 2345–2354
 knurling 1212, 1215
 machine screw taps 878–879, 895
 obtainable by various operations 630
 pipe taps 879–882, 894
 positional 611
 preferred series of 630
 projected zone 611
 relationship to surface roughness 702–704
 symbols 609, 1221
 taps 872–895
 torsion springs 325–326
 twist drill, metric 853
 unilateral and bilateral 621–622
 Tolerancing and geometric dimensioning 606, 610–611
 Ton
 long and short 2518
 metric 2523, 2546
 Tool
 and cam design, pointers 1098–1099
 compensation, NC 1281–1284
 contour, cutting tools 723
 data table 1251
 forming 758–770
 function, NC 1251–1253
 grinding, angles 723–731
 holders 732–738
 indexable inserts 729–738, 753, 1281–1284
 knurling 1211–1215
 length offset, NC 1253
 life 982–983, 992–994

- Tool** *(continued)*
- adjusting 755–757, 1004–1005, 1009, 1012, 1028
 - materials 747–757, 978–982
 - NC machines ??–1286
 - nose radius compensation, NC 1253, 1281–1284
 - offset, NC 1252
 - shanks, ANSI Standard for milling machines 922
 - sharpening
 - carbide tools 937
 - grinding wheels for 937–940
 - twist drills 934–937
 - single-point 723–746, 859–864
 - steels 444–458, 460, 462, 464–471
 - air hardening 464–466
 - alloying elements, effects of 447, 451
 - carbon 452–454
 - chromium types 458, 460, 462
 - classification of 451–454
 - cold work 464
 - cutting speed for 1000, 1018–1019, 1035
 - decarburization limits 471
 - dimensional tolerances 471
 - faults and failures, common 447–450
 - grindability of 446, 1151–1152
 - high-carbon, high-chromium 464
 - high-speed 457
 - hot work 458, 462, 464
 - machining allowances 471
 - mill production forms 470–471
 - mold 466, 468–469
 - molybdenum types 457–458, 464
 - numbering system 403, 405
 - oil hardening 464
 - properties of 444–447
 - selection of 452–456
 - shock resisting 466, 468–469
 - special purpose 466–469
 - speeds drilling, reaming, and threading 1035
 - speeds, milling 1018–1019
 - speeds, turning 1000
 - tolerances on dimensions 471
 - tungsten types 458, 460
 - water hardening 469–471
 - wear 933–935
 - Tool trouble-shooting checklist 983
 - Tooling, carbide 747, 754–757
 - Tooth face 2001
 - Tooth rest position
 - milling cutter grinding 806
 - reamer grinding 811
 - Tooth surface 2001
 - Torches, metal cutting 1428–1429
 - Torque 113
 - calculating, for tightening bolts 135, 1475–1491
- Torque** *(continued)*
- electric motor 2445–2448
 - pull-up 2446
 - relationship to angular acceleration 156
 - starting, small bearings 2280–2281
 - tightening, for bolts 1475, 1486–1487
 - torsion springs 315
- Torsion**
- and bending of shafts, combined
 - formulas 204, 210, 280–283
 - deflection of shafts, formula 277–280
 - formulas for shafts 275–277
 - modulus 204, 326–329
 - springs, design 325
 - strength of shafts 275–277
 - metric calculations 276–277
- Torus**
- polar moment of inertia 145
 - volume 71
- Total face width** 2001
- Total indicator reading, NC** 1238
- Translating, screws** 1910–1943
- Transmission chains** 2421
- cast roller chains 2421
 - detachable chains 2421
 - pintle chains 2421
 - roller chains 2421–2444
 - attachments 2425
 - center distances and chain links 2436
 - cutters for sprockets 2439–2441
 - cutting sprocket tooth forms 2437
 - design procedure 2444
 - dimensions 2423
 - hob design 2439
 - horsepower ratings 2431–2435, 2442
 - idler sprockets 2436
 - installation and alignment 2443
 - keys, keyways and set-screws 2426
 - length of driving chain 2436
 - lubrication 2443
 - manufacture 2437
 - materials 2437
 - nomenclature 2422–2424
 - nonstandard 2421
 - numbers for 2424
 - parts 2422
 - selection 2431, 2436
 - sprockets 2423–2442
 - tooth form 2438
 - types 2421
- Transmission shafting design** 280–283
- Transposition of terms in formulas** 20–21
- Transverse plane** 2001
- Trap rock, strength** 478
- Trapezium area** 62
- Trapezoid**
- area 61
 - center of gravity 137
- Trapezoidal metric threads** 1779
- Trepanning** 871
- Tresca shear theory (plastics)** 584–585

- Triangle
 acute 83
 area 61
 center of gravity 136
 equilateral 83
 geometry of 46–48
 isosceles 83
 obtuse 83
 right-angle 83
 solution 83–89
 oblique-angle 88–89
 right angle 86
 right-angle 87
- Triaxial stress 210–212
- Trigonometric
 formulas 84–85
 functions
 of angles 83–101
 signs of 84
 using calculator to find 97
 identities 84–85
 tables 93–96
- Trimming dies, steels for 456
- Trochoid 2001
- Troostite 493
- Trouble-shooting
 broaching 932
 drilling 1034
 reaming 812
 tools 448–450
- Troy weight for gold and silver 2518
- True involute form diameter 2001
- Truing and dressing grinding wheels 1158–1162
- T-slot cutters, standard 775
- T-slots and T-bolts, ANSI Standard 1645–1646
- TT-C-490D 1449
- Tube 2504
 collapsing pressure 272–274
 gages 2499
 maximum allowable pressures 274
 strength of 272–274
 subjected to external pressure
 factor of safety 274
 thickness and working pressure 273–274
 wall thickness gages 2488, 2499
- Tungsten
 carbide tools
 materials 979
 electrodes, welding 1382–1388
- Tungsten steels 458, 460, 516
 compositions 452–454, 460
 high-speed, heat-treatment of 508–511
 tool steels 458, 460
- Tungsten-carbide tools
 grinding 937–939
 single-point 738, 859–864
- Turner's sclerometer 521, 524
- Turning
 cutting speeds for
 copper alloys 1006
 ferrous cast metals 1002–1003
 hard-to-machine materials 1008–1009
 light metals 1007–1008
 plain carbon and alloy steels 996–999
 stainless steels 1001
 superalloys 1008–1009
 titanium and titanium alloys 1007
 tool steels 1000
 cutting time for 1044
 cycles, NC 1262
 grinding tools for 726–731
 speeds and feeds 995–1009, 1095
 wood 378
- Turning, cutting speeds for copper alloys 1006
- Twist drill 831–858
 equivalent of gage or letter size 829–833, 2499–2500
 grinding (sharpening) 934–936
 tolerances, metric 853
 types 827
- T-word, NC 1251–1253
-
- ## U
- U.S.
 Board of Supervising Inspectors 268
 Dept. of Commerce, formula for pressure in tubes 272–273
 gallons into liters 2545
 standard screw threads 1706
 Standard sheet metal gage 2502
 standard sheet metal gage 2501–2502
- UK gallons to liters 2544
- Ultimate strength
 common materials 478
 compressive 196
 iron and steel 476
 nonferrous alloys 477
 plastics 583
 shear 197
- Ultrasonic fluxless soldering 1352–1355
- Uncoated metals and alloys, preferred thicknesses, metric 2501
- Undercut, in spur gearing 2019–2028
- Unified 1785
 bolts, screws, and nuts 1492
 miniature screw thread, standard 1781–1785
 numbering system (UNS) for metals and alloys 403
 copper alloys 525
 plain carbon, alloy and tool steel 403, 405, 409, 411–412
 stainless steel 409, 413
 screw thread standard
 ANSI 1706–1710, 1712–1754

Unifed
 British UNJ 1825–1826
 Uniform motion 151
 Unit
 conversions 2520–2524
 horsepower for machining 870, 1046–
 1047, 1051
 systems 2520–2524
 Unit systems 2520–2524
 116
 cgs 114
 MKS 114
 Universal joints 2327
 UNS
 no. 406–408
 series of different metal 404
 Upsetting, steel for cold 420

V

Van Keuren gear measuring tables 2094–
 2106
 Variable speed belts 2401–2407
 Varnish, pattern 1339–1340
 V-belts
 arc of contact 2379–2407
 belt lengths and center distances 2379
 classical 2379–2386
 cross-sections 2397, 2413
 degree 2407
 double 2386–2394
 horsepower ratings 2372, 2407
 light duty 2390–2397
 narrow 2373–2379
 SAE Standard V-belts 2420
 service factors 2418–2419
 sheave dimensions 2373–2377, 2381–
 2382, 2398–2416
 sheaves 2372–2420
 storage and handling 2417–2418
 synchronous 2407–2417, 2419
 variable speed 2401–2407
 V-ribbed 2397–2401
 Vector and scalar quantities 118
 Velocity 113, 151, 154
 angular 151–153, 187
 rpm to radian per second
 conversion 187
 constant 151
 converting to rpm 985–990
 linear 151–152
 of points on rotating bodies 187
 Vernier scale
 dual metric-inch 670–671
 reading 669
 reading a metric 670
 reading on a protractor 669
 Versed sine and versed cosine 97
 V-flange tool shanks and retention
 knobs 1284–1286

(continued)
 Vickers hardness 520–521
 Viscosity 2201–2203, 2311–2313
 conversion table for lubricating
 oils 2201–2202
 Viscosity-pressure relationship 2324
 Viscosity-temperature chart for SAE
 oils 2202–2203
 Vitrified bonded wheels 937–938, 1140
 coolants for 1108–1109
 thread grinding 1923
 Volume
 air at different temperatures 393
 barrel 71
 cone 68
 frustum of 68
 cube 66
 cylinder
 hollow 68
 portion of 67–68
 ellipsoid 69
 geometrical figures 66–71
 nozzles 390
 of flow in pipes and tubes 388–389, 392,
 2509
 of solids 66–71
 paraboloid 70
 paraboloidal segment 71
 prism 66
 prismatic formula 56
 pyramid 66
 frustum of 67
 ratio of 71
 solid of revolution 56
 sphere 69
 hollow 70
 spherical
 sector 69
 segment 69
 wedge 70
 zone 70
 square prism 66
 torus 71
 water at different temperature 387
 wedge 67

Volumes
 of fuel 372
 V-process, casting 1336–1338
 V-projections, fine-blanking tools 1314
 V-ribbed belts 2397–2401
 V-shaped groove, checking by pins 690
 V-thread 1706
 Vulcanized fiber, strength 478

W

Wahl spring curvature correction factor 295
 Warding files 1431–1432
 Washburn & Moen wire gage 2499–2500
 Washers
 ANSI, plain 1512–1517, 1547, 1549

- Washers
 Belleville 326
 British Standard metric 1565–1566
 metric spring 1563–1565
 metric 1547, 1549
 preferred sizes 1512–1513
 spring lock type 1516
 tooth lock type 1515–1519
- Washers
 spring lock type 1519
- Watch screw threads 1781–1785
- Water
 boiling point 386
 composition 386
 flow in pipes 388–391, 2509
 flow through nozzles 390
 horsepower, equivalent to given head 389
 inches of, and equivalent pressure 388
 pressure 386
 pressure, head or depth known 386
 pressures, methods of measuring 388
 velocity due to head 391
 volume at different temperatures 388
 volume of flow in pipes and tubes 392,
 2509
 weight at different temperatures 389
- Watt equivalent 2551
- Waviness 697
 height values 702
- Wear and wear resistance cutting tool 933–
 934
- Wedge 130
 center of gravity 140
 mechanical principle of 130
 volume 67
- Weight 116
 air 393–394
 at different pressures 394
 at different temperatures 394
 per cubic foot 393–394
 angles, structural steel 2495–2497
 avoirdupois or commercial 2518
 castings, from pattern weight 1340
 channels, structural 2494, 2498
 charcoal, coal and coke 371
 fuels 371
 hollow shafts 283–284
 I-beams 2489–2493
 metals 368–370
 metric 2523, 2546
 nails and spikes 1455
 of natural piles 373
 per feet of wood 372
 pipe, per foot 2505–2508
 specific gravity known 370
 steel S-sections 2493
 troy, for gold and silver 2518
 water 386, 388
 wide flange, steel 2489–2492
 wood 371–372, 376–377
- Weights and measures 2517–2519
- Welding 1362–1409, 1418–1421
 aluminum 1365, 1385–1390
 ANSI welding symbols 1393–1409
 application of 1397–1401
 nondestructive testing 1408–1409
 application of symbols 1397–1401
 arc cutting of metals 1428–1429
 codes, rules, regulations,
 specifications 1394–1395
 complete fusion 1405
 cutting metals, with electric arc 1428–
 1429
 with oxidizing flame 1428
 cutting with lasers 1414–1419
 definitions and symbols 1393–1401
 designations 1396
 dies 1408
 electrodes 1363, 1367, 1385–1387
 electron beam 1392
 FCAW (flux-cored arc) 1371–1378
 contact tip recess 1373–1374
 deposition rates 1376–1378
 electrodes 1371–1373
 porosity and worm tracks 1374
 settings 1374–1376
 shielding gases 1378
 fill and cover pass procedures for 5G
 welds 1406–1407
 fill passes 1403
 GMAW (gas metal arc) 1363–1371
 electrode diameters 1363
 shielding gases 1364–1366
 spray transfer 1367–1371
 welding sheet steel 1364
 GTAW (gas tungsten arc) 1382–1387
 filler metals 1387
 selecting tungsten electrode 1385–1387
 shielding gases 1387
 welding current 1392–1394
 hard-facing 1423–1427
 horizontal pipe welding 1403
 laser
 cutting 1414–1418
 welding 1418–1421
 letter designations for processes 1396
 materials used in welding 1393
 nondestructive testing 1408–1409
 PAW (plasma arc) 1387–1391
 applications 1389–1390
 cutting 1391
 gases for 1388–1389
 of aluminum 1389–1390
 surface coating 1390–1391
 pipe 1402
 positioning of joint components in pipe
 welding 1402
 process letter designation 1396
 root passes 1403
 root welding procedure for 5G
 welds 1407

- Welding *(continued)*
 root welding procedures for fcaw 5G pipe welds 1406
 SMAW (shielded metal arc) 1378–1382
 characteristic of electrodes 1379–1382
 specifications 1394–1395
 symbols 1394
 tack welding procedures for FCAW 5G pipe welds 1406
 thick-walled carbon-steel pipes 1405–1406
 thin-wall pipe 1404
 thin-walled carbon-steel pipes 1407
 use of flux-cored electrodes 1404
 vertical-down welding 1403
 vertical-up welding 1403
 wire extension 1406
 Welding and hard-facing 1423–1427
 Welding factor 2045
 Weldon shanks, dimensions of 779–789
 Wheels
 abrasive cutting 1204
 buffing 1440
 diamond 937–939, 1163–1169
 dressing 1158–1161
 grinding 1139–1174
 mechanical principles of 134
 polishing 1439
 polishing, speed of 1440
 silicon carbide 937–938
 Wheels and pulleys in mechanics 134–135
 White cast iron 1330
 White metal bearing alloys 2237–2238
 Whitworth
 standard bolts, screws, nuts, washers, and studs 1551–1554, 1595–1598, 1619
 wire size for measuring threads 1861–1862
 Whole depth 2001
 Wide-flange shapes, steel 2489–2492
 moment of inertia 2489–2492
 radius of gyration 2489–2492
 section modulus 2489–2492
 weight per foot 2489–2492
 Winding drums, wire rope and chain 342–343, 360
 Windlass 134
 Wing nuts, standard 1693–1696
 Wing screws 1693–1701
 Wire
 brass, phosphor bronze, strength of 477
 checking gear sizes 2094–2108, 2111–2112
 backlash allowances 2103
 diameters 2094, 2103
 helical gears 2103–2109
 checking screw threads 1860–1877
 Acme threads 1866–1874
 buttress threads 1875–1877
 contact pressure 1862–1863
 formulas for large lead angles 1863–1874
 limits for diameters 1861–1863, 1870
 specifications 1862–1863
 taper screws 1872, 1875
 circular mill measurement 2517
 copper, strength of 477
 diameters, squares, cubes, fourth powers of 330
 EDM 1318, 1328–1329
 music 330, 385, 2499–2500
 plow steel, strength of 336–341
 preferred thicknesses 2501
 rod gages 2499
 rope 333–350
 sheet metal gages 2499–2503
 spring, tensile strength of 385
 tensile strength 385
 tubing, wall thickness gages 2499
 wire gages 2499–2500
 Wire nails and spikes, standard 1455
 Wire rope 333–350
 bending stresses 344
 breaking strengths 334
 classes 335–338
 construction 333
 cutting and seizing 344
 definitions of terms 333–334
 drum or reel capacity 342–343
 drum score for winding 360
 factors of safety 339–340
 installation 340–346
 life 344–345
 lubrication 345
 maintenance 344–345
 properties 334–335
 rated capacities of 349–350
 replacement 345
 rope loads due to bending 344
 safe loads for 339–340
 sheave and drum dimensions 342
 simplified practice recommendations 338
 sizes 336–341
 slings and fittings 345–350
 specification 334
 strength 336–341
 weight 336–341
 Wood
 bearings 2242, 2245
 bonding 2460–2463
 compression perpendicular to grain 375
 crushing strength 375
 density 376
 dimensions of sawn lumber 378
 hardmetal tooling for 757
 ignition temperatures 367
 machinability 377–378
 maximum crushing strength 375
 mechanical properties of 375–376
 effect of pressure treatment 376

- Wood
 mechanical property 375
 modulus of rupture 375
 patterns 1339–1340
 screws 1456
 shear strength parallel to grain 376
 tensile strength perpendicular to grain 376
 tooling for wood and nonmetals 757
 weight of 371
- Wood screws, pilot hole for 1456
- Woodruff keys 2365
- Woodruff keyseat cutters 795
- Word address format, NC 1243–1245
- Word, NC 1243–1245
- Work 113, 158–159
 formulas 158–159
 general formulas 162
 relation to energy 158–159
- Work and Energy 158
- Work hardening factor 2044–2045
- work to maximum load in bending
 wood 375
- Working depth 2001
- Working strength of bolts 1489–1491, 1559–1561
 stresses 200
 for springs 291–297
- Working stress
 shafts, maximum allowable 282
- Worm gear
 effect of cutting diameter on profile and pressure angle 2066
 effect of production method on profile and pressure angle 2066
- Worm gearing 2064–2066
 addendum 2065
 ANSI Standard, fine-pitch 2064–2066
 center distance 2065
 effect of cutting method on profile 2066
 fine-pitch 2064–2066
 formulas for dimensions 2065
 hobs for 2064
 lead angles 2064–2065
 material for 2067
 materials for 2066
 multithread 2066
 multi-thread worms 2067
 number of threads or “starts” 2067
 outside diameter 2065
 pitch diameter range 2066
 pitches 2064
 pitches, standard 2064
 pressure angle 2066
 pressure angles 2064
 proportions 2065
 ratios 2066
 single-thread 2066
 single-thread worms 2067
- Worm gearing (continued)
 tooth form 2066
 tooth form of worm and wormgear 2066
- Worm gearing, hobs 2064
- Wrapped spring clutches 2332–2333
- Wrench clearances
 for box wrenches 1510
 for open end wrenches 1511
 for socket wrenches 1511
 for spacing of bolts 1510–1511
- Wrench openings, ANSI Standard 1510
- Wrought
 copper 566
 iron
 strength 476
 temperature effect on 478
 thickness gage for sheet 2502
 steel pipe 2504–2505
- Wurtzite 755–757
-
- ## Y
- Yield
 strength
 perforated metal 235
- Yield point 196
 for various materials 196
 heat-treated steels 432–436
 iron and steel 473, 475–476
 nonferrous metals 477
 plastics 583
- Yield strength 196, 376, 379, 385
 aluminum alloys 550–555
 compressive 196
 copper alloys 526–542
 copper-beryllium alloys 566
 copper-silicon alloys 565
 Investment casting alloy 381
 magnesium alloys 560
 nickel alloys 562–563
 perforated metal 235
 plastics 573–574
 shear 197
 stainless steel 439
 steel 430–436, 441
 titanium alloys 564
- Young’s modulus 196
 spring materials 326–329
-
- ## Z
- Zero suppression, NC 1245
- Zero, absolute 2514
- Zerol bevel gears 1998, 2050–2051
- Zinc
 plating 1451
 specific gravity 370
- Zinc-base alloys, die casting 1342
- Zone factor 2044–2045